



Doc. no: SW-DS-GFZ-GS-0001

Rev: 2X

Date: 2017-12-21

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

British Geological Survey (BGS)
National Space Institute – DTU Space (DTU)
Delft Institute of Earth Observation and Space Systems (DEOS)
Helmholtz Centre Potsdam - German Research Centre for Geosciences (GFZ)
Eidgenössische Technische Hochschule Zürich (ETH)
Institut de Physique du Globe de Paris (IPGP)

with additional contributions from

NASA Goddard Space Flight Center (GSFC)
University of Colorado (CIRES)
Charles University Prague (CUP)

Prepared:

Checked:

Guram Kervalishvili

Date 2017-12-21

Scientist

Stefanie Weege

Date 2017-12-21

Project Manager

Approved:

Claudia Stolle

Date 2017-12-21

Team Leader

© GFZ, Germany, 2017. Proprietary and intellectual rights of GFZ, Germany are involved in the subject-matter of this material and all manufacturing, reproduction, use, disclosure, and sales rights pertaining to such subject-matter are expressly reserved. This material is submitted for a specific purpose as agreed in writing, and the recipient by accepting this material agrees that this material will not be used, copied, or reproduced in whole or in part nor its contents (or any part thereof) revealed in any manner or to any third party, except own staff, to meet the purpose for which it was submitted and subject to the terms of the written agreement.

Product specification for L2 Products and Auxiliary Products

Page 2 of 136

Reason	Description	Rev	Date
Initial version	Released	1	2011-01-30
Revision	Tables 5.1 and 5.2 transferred to document L2PS ADD. Include aux product names for CAT-2 chains. Include revised WP8000/9000 product. Adapted changes in Sections 5.5 – 5-14 Modification in Section 4.2 in response to some PDR RID's 66(2), 221 Update Product names to after TM2. Add section 4.3 describing the agreed data formats. Section describing File names (former 4.3) is now numbered as Section 4.4. Including responses to PDR-RIDs 30,32, 66, 221, 243,249 Third column in tables 5.1 – 5.3 is used for format description	1dA	2011-02-11 2011-02-28 2011-03-03
Revision	Corrections following the internal review Including comments from IPGP, GFZ and ETH, BGS (all sections), e.g.: Including MLI_SHA_2E (RID-274, AI-31).	1A	2011-03-18
Revision	Including information on AUX_F10_2F , AUX_DST_2F, and correcting web reference for AUX_KP__2F, based on information from GFZ and IPGP.	1A dA	2011-03-21
	Including new data source for AUX_F10_2F	1A dB	2011-03-23
	Including names of CAT-2 AUX providers (Section 5.13)	1A dC	2011-04-01
PDR Update	Add the specification of the Product Reports (modifications in 4.3.6, 4.4, 5.4., and 5.15)	1B	2011-04-04

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 3 of 136

Reason	Description	Rev	Date
	Change ftp download file names yyyyymm_ace_mag_1h.txt to yyyyymm_ace_mag_1h.txt in section 5.13 for AUX_IMF_2F and AUX_SWV_2F	1B dA	2011-04-28
ARO Update	Add that “only final products are released to the end user” in section 5.2.1; 5.3 (AI-75) Describe product flow (AI-73) Corrections due to ARO-123 (add missing reference in section 4.3)	1C	2011-06-08
Up1DMi2date after TM3/PM3	Describe and define the intermediate validation products (xxx_VALi2Z) (Sections 5.2.1, 5.3, 5.5- 5.9, Table 5.1) Replace specification tables with new/corrected input from DEOS (Sections 5.10 and 5.11) MMA_SHA_2Z being CDF format as time series of external and induced SH coefficients. AUX_PMF_2F insert: “new format expected from partners.” Delete references which concerned now embedded aux models (formerly RD13-RD21). AUX_COR_2_/F has been set to be initially the CHAOS3 model. Definition of AUX_GPSEPH to be clarified. Deletion of the tags “input parameters”, “output parameters”, “processing demands”, and “language” for all AUX models, because all aux models are files with coefficients. No software is delivered for any existing AUX model anymore. (Section 5.14) Description of validation reports in 5.2.1 and 5.5 ff according to point 3.1.1 of SW-MN-DTU-GS- 0002_ICD_Clarification_Meeting.pdf Delete product MOD_QL_2_ Adding “Update rate” and CDF variable content for DEOS products; section 5.10 and 5.11	1C dA	2011-07-01 2011-07-03 2011-07-07 2011-08-19 2011-08-23

Product specification for L2 Products and Auxiliary Products

Page 4 of 136

The use and/or disclosure, etc. of the contents of this document (or any part thereof) is subject to the restrictions referenced on the front page.

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 5 of 136

Reason	Description	Rev	Date
Internal review	<p>Minor editorial changes</p> <p>Delete repetition of SP3-format description (was a c/p from a website) in section 4.3.2.</p> <p>Delete section "Product flow".</p> <p>Extending section 4.4.</p> <p>Minor changes specification tables.</p> <p>Identified TBDs (probably not all) are marked yellow. The document is not yet complete, and partly cannot be completed now due to open decisions.</p>	2dA	2011-09-16
CDR RIDs	<p>RID-10: Section 4.4 is adapted by stating that the validity time is similar (not identical) to the description in [AD-8]</p> <p>RID-14: change all remaining AUX_IGS_2F to AUX_GPSEPH</p> <p>Correct typos in Table for MIO_VALi2D (no RID)</p>	2dB	2011-09-27
	<p>RID-52: Description for Fast Track products has been adapted.</p> <p>RID-12: Update CDF library version (section 4.2.5)</p> <p>RID-86: Update Table 5 – 3.</p> <p>RID-11: Add a List of TBDs</p>	2dC	2011-09-28
	Update AUX_IMF/F10_2_	2	2011-09-30
	Include format definition for MIO_SHA products	2A dA	2011-10-10
	Move format description for mantle conductivity into section 4.3.4.2		2011-10-11
	Include updated tables for al CI products *i2C, and corresponding final products and validation reports for Q3D_CI_i2_ , and CAT-1 AUX_KP, AUX_DST, AUX_F10, AUX_IMF, AUX_IGR, and REP_L2PS_	2A dB	2011-10-27
	Delete all per-se N/A field in all validation report product specification tables		
	Update MIO format (section 4.3.)	2A dC	2011-10-28
	Update DEOS tables (sections 5.9 and 5.10)	2A dE	2011-11-02

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 6 of 136

Reason	Description	Rev	Date
Internal review	Update GFZ CAT-1 and CAT-2 tables, Update BGS table.	2A dF	2011-11-15
	Update MIO format (section 4.3.4.3) – introducing h, R and northern dipole positions in line 3		
	Insert comments from IPGP: tables MLI, MIO and EEF tables, and minor editorial changes	2A dG	2011-11-29
	Table for MCO_SHAi2D: Change “Output time span and resolution” to “Output time span”, transfer time resolution information to “Time representation”		
	Update tables MIN_ and MCR_ from comments by ETH		
Internal review	Table of figures and Table of tables added. Minor editorials	2A	2011-12-01
	Minor editorials, and adapt Has become obsolete. Deleted.	2BdA	2011-12-20
	Table 4-7 to L2PS ICD Adapt MIO format (section 4.3.4.3)		
Revision after PM5	SPH described in section 4.2.2.2 is also valid for AUX_IGR_2F, AUX_COR_2F, AUX_LIT_2F	2BdC	2012-01-12
	Include new AUX product AUX_IRZ_2F	2BdD	2012-02-06
	Update format description for AUX_OBS_2_		
	ARO-51: remove GPSx_RN_1B from TECxTMS_2F table	2BdE	2012-02-15
	Add examples for tags 1. 5.1 and 1.5.3 in Table 4-4		
	Update description for AUX_OBS_2_		
	Introduce AUX_APX_2F	2BdF	2012-02-16
	Complete list of “original_filename” in Table 4-4 for AUX_OBS_2_		

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 7 of 136

Reason	Description	Rev	Date
	Included a tag for List_of_Auxiliary_File_Names in the Specific Product Header (Table 4-3). Add Format description for MMA_SHAI2C (section 0) Adding cdf epoch definition and unit in section 4.3.5.	2B	2012-03-08
	Delete AD-11, AD-12 is now AD-11 Adapt "Data Source" link in EEfXTMS_2F table Add Syntetic_Exit_Code to Product reports Add "RPRO" as a File_Class definition in the Filename and in the header files Delete tables for AUX_APX_2F and AUX_GPSEPH in section 5.12; add AUX_USLEAP and AUX_USNEOP in Table 5-3; add a comment to all these four products in Table 5-3 that they are specified in AD-11. All CAT-3 chains are converted to CAT-1 chains. (see section 3.2.4 in Swarm L2PS CDR Board Report) Necessary adaptations in the document made.	2CdA	2012-03-17
Internal review	Several editorial issues in response to internal review by the PA. Some of the TBDs and TBCs defined.	2CdA	2012-04-30
	Adapt tables for AUX_COR2_/F to current status, and delete respective item in List of TBDs. Adapt ASCII format for MSW_EUL_2C/D/F. Error estimates for MSW_EUL_2C/D products to be included in the internal product validation report (section 4.3.4.1).	2C	2012-05-02
Updates in response to AR1 review	Response to ARI-2: Add tag 1.5.n in Table 4-3. Response to AR-11: EEfXTMS variable named adopted to EEf DPM (section 5.8.2).	2DdA	2012-05-07

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 8 of 136

Reason	Description	Rev	Date
	ARI-12, ARI-13, ARI-14 included	2DdB	2012-05-10
	ARI-19: TBD's replaced with information from GFZ.	2DdC	2012-05-16
	Add input data to MLI_SHAi2D and MLI_SHAi2E (section 5.6.1)		
	Delete second (unused) format option for describing SHC, and adding two optional numbers in the first data line in the accepted SHA format (Section 4.3.1)		
	Tag 1.5 in Table 4-3 applies for CAT-1 and CAT-2 products from after V1 tests.		
	Set resolution for MCO_SHAi2C is set from Spherical Harmonics degree 20 to degree 18		
	Change flag type to CDF_UINT4 (for FAC_TMS_2F and FACxTMS_2F in section 5.8.2).	2DdE	2012-05-21
	Add kinematic orbit product SP3_KIN_2_ from information by DEOS		
	Change update rate and latency of AUX_F10_2F to one day.		
	Add definition of SPH of Cat-2 products in Table 4-3.		
	Delete products MI3_VALi2a/b and MI3_VAL_2a/b		
Release		2D	2012-05-24

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 9 of 136

Reason	Description	Rev	Date
	ARI-10 Nr. 11, correct to "20 headerlines" (section 5.12)	2EdA	2012-06-01
	Change flag type to CDF_DOUBLE (for FAC_TMS_2F and FACxTMS_2F in section 5.8.2). Describe quality indicator for Cat-2 products in header (Table 4-3).	2EdB	2012-06-07
	Change Date_Time_of_operation from UTC=yyyy-yy-ddThh_mm.ssssss to UTC=YYYY-MM-DDThh_mm.ssssss	2EdC	2012-06-28
	Describe quality indicators and/or flags for Cat-2 products EEf, IBI, FAC in section 5.8.2 in Table 4-3		
	Add section 5.2.3 about L2 Cat-1 product selection process		
	Add lines for Maneuver_Id in tag 1.3 in Table 4-3.	2EdD	2012-07-03
	Add extra lines for specific header of Product Reports in Table 4-2.		
	SPR-94: add link to format descriptions to products AUX_F10_2F, AUX_IMF_2F, AUX_SWV_2F, AUX_IRZ_2F, AUX_DCB_2F in section 5.12	2EdE	2012-07-04
	Put hyperlinks to tables in changelock, delete comment line for Maneuver_Id in tag 1.3 in Table 4-3.		
	SPR-95: Sentence deleted that MPH is valid for all Swarm products in section 4.1		
	SPR-96: noted that variable headers for all "other" CAT-2 aux files are provided in [AD-11], section 4.2.2		
	SPR-98: remaining columns for AUX_KP__2F format description updated, section 5.12		
	SPR-99: AUX_F10_2F added that header lines start with # or : , section 5.12		2012-07-05
	Adding information on variable number of header lines that start with # for AUX_KP__2_ (section 5.12)		

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 10 of 136

Reason	Description	Rev	Date
	Update revision number to document number 2EdB	2EdF	2012-07-09
	Time stamp format for Date_Time_of_Operation set to UTC=yyy-mm-ddThh:mm:ss.uuuuuu in section 4.3.3	2EdG	2012-07-11
	Correct for reference to format description for MIO_SHAi2C to section 4.3.4.3 (from section 4.3.4.2) (section 5.8.1)		
	More detailed format description for AUX_IRZ_2F (section 5.12)		
	Change “The format for products MCR_1DM_2_ and MCR_1DM_2_ “ to “The format for products MCR_1DM_2_ and MCR_3DM_2_ “ and change variables dC0_k -> Err0_k; dC3D_k -> Err3D_k (section 4.3.4.2)		
	Replace tables for AUX_PMF_2F, AUX_PSM_2F, AUX_PGM_2F, AUX_IRZ_2F with updated format description (sections 5.13.4 and 5.12)	2EdH	2012-07-13
	Change flag type to CDF_UINT4 (for FAC_TMS_2F and FACxTMS_2F in section 5.8.2).	2EdI	2012-07-18
	Change latency for FAC_TMS_2F and FACxTMS_2F from 6 to 10 minutes. (section 5.8.2).	2EdJ	2012-07-18
e-mail by NiO 29-08-12	Add error estimates for gauss coefficients for MMA_SHAi2C product and correct for array dimensions section 5.8.1	2E	2012-08-29
	Add description for cdf variables of AUX_IMF_2_ file (section 5.12)		
SPR-104	Adapt format description of AUX_KP__2F following. (section 5.12)	2FdA	2012-09-04
Release	Added signatures.	2F	2012-09-07

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 11 of 136

Reason	Description	Rev	Date
Email communication DTU/BGS	Aux Original filename for AUX_COR_2_: change from "MF7.cof" to "Freely chosen by the chain" (Table 4-4 Level 2 Specific Product Header (SPH) – For CAT-1 AUX products and for AUX_IGR_2F, AUX_COR_2F and AUX_LIT_2F) Specify in more detail 1.5.1 for AUX_OBS_2_ in Table 4-4 Level 2 Specific Product Header (SPH) – For CAT-1 AUX products and for AUX_IGR_2F, AUX_COR_2F and AUX_LIT_2F	2GdA	2012-10-22
Typo found	Change 1-10 to 1-12 in the format description for the first column for AUX_DST_2_ product (section 5.12).	2GdB	2012-11-06
e-mail G Hulot > L T-C on 30-11-2012 18:10	Add MCO_SHAi2C and MLI_SHAi2C as input products for MIO_SHAi2D (section 5.8.1)	2GdC	2012-12-10
Review and approval	Update to rev. 2G	2G	2012-12-13
Email from nio 20-12-2012 10:33	Page 118: from: 64-72 f9.1 Centered (B_r) component (nT) to: 64-72 f9.1 Centered (-B_r) component (nT)	2HdA	2013-01-17
Email from gernot plank 14:22 04-02-2013	Change product name MMA_SHA_2_ to MMA_SHAi2C in the input tab for product description tables of MCO_SHAi2D and all mantle conductivity products Add MCO_SHA_2D to the input table for MMA_SHA_2F	2HdB	2013-02-05
Email from Vincent Lesur 13 March 2013 18:29	Change update rate of MCO_SHA_2F from 1 to 3 months (Section 5.5.2)	2HdC	2013-03-20
SPR-117	Delete entries for product reports and adapt Specific Product Header (entry 5 is changed to Input files and entry 6 has been added)(section 4.2.2.2) Remove TEST mode for entry 1.3 in Table 4-2 and for entry 5 in Table 4-1: Level 2 Fixed Header.	2HdD	2013-04-10
Signature		2H	2013-04-12

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 12 of 136

Reason	Description	Rev	Date
Email from Max to Gernot "Swarm L2PS AR2 TDS & Products Spec. (2H)" 04/23/2013 05:16 PM	Correct "input file" to "output file" in point 1.6 for Cat-1 products (Table 4-3 , section 4.2.2.2)	2IdA	2013-04-24
Signature		2I	2013-05-06
Email from Gernot to Poul Erik: "L2PS PDD updated to version 2I" 08.05.2013, 15h36	Remove TEST in section 4.4 as possible identifier in file name	2JdA	2013-06-13
Email from Brian to Poul Erik: "Update to MMA entry in Project Specification Document" 13.05.2014, 19h49	section 5.8.2: Description update of the quality flag for the MMA_SHA_2F product. Specification in detail what each flag value means (q-flag).	2JdB	2014-05-22
Signature		2J	2014-05-23
Email from Max to Lars: "SW-DS-DTU-GS- 0001_Product_Specification, Issue 2I (Need For An Update)" 25.06.2014, 15h14	Section 5.12: Description update of the content of AUX_KP_2F in the field "Notes" according to SW-CP-AR-245 (a PDGS AR) and GMV-L2CAT2- SPR-70 (an EEF GMV SPR).	2L	2015-04-28
Correction, flags definitions	Section 5.8.2: In FAC_TMS_2F table, the texts in Digit-Nos. 5 and 7 have been interchanged.	2M	2015-07-28
Email from Jose to Poul Erik: "L2 product spec" 25.02.2015, 10h46	Table 5-2: Velocity removed from SP3xKIN_2_ product. Section 5.9.1: "CODE" added to External data for SP3xCOM_2_ and SP3xKIN_2_. SP3xKIN_2_ Data volume increased from < 2 MB to < 15 MB per satellite per day.	2N	2015-09-03
New and redefined ACC products	Added/modified products ACCxDISi2_, ACCx_FMi2_, ACCxCAL_2_, ACCxVAL_2_: Updated Table 5-1, Table 5-2, Chapter 5.9 and Chapter 5.10	2PdA	2015-11-30

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 13 of 136

Reason	Description	Rev	Date
Change of product file extensions to native format (AI-328)	Changed product file description from .DBL to native format in Sections 4.1 and 4.4. Added "Extension" column to Table 5-1, Table 5-2 and Table 5-3. Added AUX_OBSM2_ to Table 5-3 and Section 5.12	2PdB	2016-02-19
Signature		2P	2016-02-22
Email from Igino to Poul Erik: "L2 PDD has been updated: some clarification" 23.02.2016, 16h48	Rev 2P rolled back to Rev 2PdA with AUX_OBSM2 still added to Table 5-3 and Section 5.12	2QdA	2016-02-24
Signature		2Q	2016-02-25
Email from Christian to Poul Erik: 08.03.2016, 12h	Section 5.10.2: Data format corrected for ACCx_AE_2_ and Definition corrected for DNSxWND_2_	2RdA	2016-03-08
Signature		2R	2016-03-10
Include new product DNSxPOD_2_	Table 5-2: Insert new product Section 5.10.2: Edit Table on product DNSxWND_2_ in order to highlight difference to new product DNSxPOD_2_ Section 5.10.2: Add Table for new DNSxWND_2_ product DNSxPOD_2_	2SdA	2017-12-21
Email from Igino to Poul Erik: 21.06.2016, 12h12	Subsection on Quick Look reports removed in Section 5.2.1	2SdB	2016-09-08
Email from Christian to Igino: 22.06.2016, 08h35	Data volume inserted in ACCxDISi2_ Table in Section 5.10.1 and ACCxVal_2_ Table in Section 5.10.2		
Include new product AUX_OBSS2_	Added AUX_OBSS2_ to Table 5-3 and Section 5.12 'Data volume', 'Data format', 'Update rate' and 'Latency' updated in AUX_OBSM2_ Table in Section 5.12		
Email from Jonas to Claudia: 10.11.2016, 09h26	Subsection 1.4 is added: a link to Swarm Wiki webpage "Swarm Product Data Handbook"		2016-11-21
Email from Poul Erik to Guram: 30.11.2016, 13h22	Subsection 5.12: AUX_OBS_2_, AUX_OBSM2_, AUX_OBSS2_ Tables are updated	2SdC	2016-12-01
Signature		2S	2016-12-01

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 14 of 136

Reason	Description	Rev	Date
Email from Poul Erik to Guram: 01.12.2016, 19h16	Changed product file description from .DBL to native format in subsections 4.1 and 4.4. Added "Extension" column to Table 5-1, Table 5-2 and Table 5-3.	2TdA	2016-12-05
Email from Poul Erik to Claudia: 18.01.2017, 16h33	Table 5-3: all extensions changed to ".DBL" Subsection 4.4: "Level 2 product the names could be" changed to "Level 2 product the names are" and extension ".DBL" changed to ".shc"		2017-01-18
Signature		2T	2017-01-19
Email from Poul Erik to Claudia: 22.02.2017, 10h41	Table 5-2: CAT-1 Validation report for DNSxVAL_2_ is added. Subsection 5.9.1: table for ACCxPOD_2_ is updated. Subsection 5.10.2: table for DNSxPOD_2_ is updated and table for DNSxVAL_2_ is added.	2UdA	2017-03-06
Email from Poul Erik to Claudia: 28.02.2017, 15h12	Subsection 5.8.2: table for FAC_TMS_2F is updated (MAGB -> MAGC and SwB -> SwC). Subsection 5.8.2: table for TECxTMS_2F is updated (Time representation and Notes).	2UdB	2017-03-07
Signature		2U	2017-03-08
Email from Leda to Guram: 30.06.2017, 17h00	Two new variables are added for TECxTMS_2F product table (page 93) in section 5.8.2: Absolute-VTEC and Elevation-Angle	2VdA	2017-07-02
Signature		2V	2017-07-04
Email from Poul Erik to Guram: 25.07.2017, 13h45	Subsection 5.9.1: table for ACCxPOD_2_ is updated. Subsection 5.10.2: tables for ACCxCAL_2_, DNSxPOD_2_ and DNSxVAL_2_ are updated.	2WdA	2017-08-22
Email from Lars to Guram: 25.07.2017, 13h54	The description of DNSxVAL_2_ in Table 5-2 is corrected: DNSxVAL_2_ -> DNSxPOD_2_	2WdB	2017-08-22
Email from Christian to Guram: 22.08.2017, 14h35	Subsection 5.12: data source link is corrected in table for AUX_KP_2_	2WdC	2017-08-23
Signature		2W	2017-08-24
Email from Christian to Guram: 16.11.2017, 12h32	Subsection 5.10.2: Quality indicator information in table for ACCxCAL_2_ is updated	2XdA	2017-11-26
Signature		2X	2017-12-21

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 15 of 136

Table of Contents

1	Introduction.....	20
1.1	Purpose	20
1.2	Scope	20
1.3	Document structure	20
1.4	Online version	20
2	Applicable and Reference Documentation	21
2.1	Applicable Documents	21
2.2	Reference Documents.....	21
2.3	Abbreviations	22
3	The Swarm Science Objectives	26
4	Structure of product files	27
4.1	General Structure of products.....	27
4.2	XML Header File	28
4.2.1	Level 2 Products Fixed Header (Standard Swarm Header).....	28
4.2.2	Level 2 Products Variable Header (Product Header)	30
4.2.3	Input Files.....	38
4.3	Product File Formats	38
4.3.1	ASCII Listing (SHC format)	38
4.3.2	ASCII Listing (SP3 format).....	40
4.3.3	ASCII Listing (XML format)	40
4.3.4	ASCII Listing (others).....	41
4.3.5	CDF format.....	46
4.3.6	PDF reports.....	46
4.4	File Names.....	46
5	Specification of Level 2 Products and Auxiliary Products.....	48
5.1	Product name convention	48

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 16 of 136

5.2	Product classification	49
5.2.1	Level 2 products	49
5.2.2	Auxiliary products	50
5.2.3	Level 2 product selection.....	50
5.3	Product overview.....	50
5.4	Euler Angles	56
5.4.1	Intermediate Level 2 Candidate Products.....	56
5.4.2	Final Level 2 Products.....	58
5.5	Core Field Models	61
5.5.1	Intermediate Level 2 Candidate Products.....	61
5.5.2	Final Level 2 Products.....	62
5.6	Lithospheric Field Models.....	65
5.6.1	Intermediate Level 2 Candidate Products.....	65
5.6.2	Final Level 2 Products.....	68
5.7	Mantle Conductivity.....	71
5.7.1	Intermediate Level 2 Products.....	71
5.7.2	Final Level 2 Products.....	76
5.8	External Field and Current Systems	80
5.8.1	Intermediate Level 2 Candidate Products.....	80
5.8.2	Final Level 2 Products.....	85
5.9	Precise Orbit Determination Products	98
5.9.1	Final Level 2 Products.....	100
5.10	Magnetic Forcing of the Upper Atmosphere	102
5.10.1	Intermediate Level 2 Products.....	102
5.10.2	Final Level 2 Products.....	104
5.11	Quick Look reports for L1b products	111

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 17 of 136

5.12	Auxiliary data	111
5.13	Auxiliary models	128
5.13.1	Magnetic field models	128
5.13.2	Mantle conductivity model	132
5.13.3	Surface conductance models	133
5.13.4	Magnetospheric models	133

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 18 of 136

Figures

Figure 4.1 General Product Structure	27
--------------------------------------	----

Tables

Figure 4.1 General Product Structure	27
--------------------------------------	----

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 19 of 136

List of TBDs

RID	Section(s)	Actor	Due Date
None			

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 20 of 136

1 Introduction

1.1 Purpose

This document specifies the Swarm Level 2 products and auxiliary products.

This document is a constituent of the design definition file and is provided in response to the requirement of the Deliverable Item List, SW-LI-ESA-GS-0176, DIL-ID Sys-8.

1.2 Scope

The *Swarm* Level 1b data products are the corrected and formatted output from each of the three *Swarm* satellites. By a complex assimilation of these individual satellite measurements into one set of products for the satellite constellation, the *Swarm* Level 2 Processor ensures a very significant improvement of the quality of the final scientific data products.

This document specifies the intermediate and final data products, the auxiliary products of the *Swarm* Level 2 Processor, and the Quick look reports of L1b data. The definition and justification of Swarm Level 2 data and auxiliary products are documented in [AD-1] and [AD-2] of the ESA Swarm study under ESA contract no. 20969/07/NL/JA.

Originally, the document was proposed to be named “Product specification for Level 2 Products, Quick Look products and Auxiliary Data Products”. It was agreed during the PDGS to L2PS ICD Clarification Meeting on 15-10-2010 that Quick Look reports are included in the L2 products; and that the title of this document will be modified to “Product Specification for Level 2 products and Auxiliary Products”.

1.3 Document structure

The document is structured in the following way:

- The document starts with an overview of applicable and reference documents, and a table of abbreviations in chapter 2.
- The Swarm science objectives are represented in chapter 3.
- Chapter 4 recalls the product structure and format.
- Product specifications are provided in chapter 5. After a comprehensive overview of the different products, each product is specified in detail.

1.4 Online version

An online version in the form of a website called “Swarm Product Data Handbook” is available for information on Swarm, which also includes the information from this document:

http://swarm-wiki.spacecenter.dk/mediawiki-1.21.1/index.php/Main_Page

The Swarm Product Data Handbook provides a detailed description of the Swarm Level 1b and Swarm Level 2 products including supporting information distributed to the Swarm users.

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 21 of 136

2 Applicable and Reference Documentation

2.1 Applicable Documents

- [AD-1] PDD – Product Definition Document (SWL2_SPT_PDD)
- [AD-2] LPM – List and Description of Auxiliary Data and Prior Models Needed (SWL2-SPT-LPM)
- [AD-3] ADD – Architecture Design Document (SWL2_SPT_ADD)
- [AD-4] SWRD – Software Requirement Document (SWL2_SPT_SWRD)
- [AD-5] Swarm Level 1b Product Definition (SW-RS-DSC-SY-0007)
- [AD-6] Swarm Level 0 Product Format, Doc. No: SWARM-GSEG-EOPG-05-001, ESA ESTEC, Noordwijk, The Netherlands
- [AD-7] Earth Explorer File Format Standards Doc. No: PE-TN-ESA-GS-0001 ESA ESTEC, Noordwijk, The Netherlands
- [AD-8] Tailoring of File Format Standards to Swarm Mission Doc. No: SW-TN-ESA-GS-0074 ESA ESTEC, Noordwijk, The Netherlands
- [AD-9] Preparation of the Swarm Level 2 Data Processing, Final Report Doc. No: SWL2-SPT-FR
- [AD-10] Statement of work (SoW) for the Development of the Swarm Level 2 Algorithms and Associated Level 2 Processing Facility, Doc. No: SW-SW-ESA-GS-0179
- [AD-11] L2 CAT-2 Processors Auxiliary Data Providers to Swarm PDGS Interface Control Document, Doc ID: SWAM-GSEG-EOPG-IC-011-0004

2.2 Reference Documents

- [RD-1] Swarm Level 1b Processor Characterisation and Calibration Data Base Doc. No: SW-TN-DSC-SY-0005 National Space Institute, Technical University of Denmark
- [RD-2] Swarm Level 1b Processor Algorithms Doc. No: SW-RS-DSC-SY-0002 National Space Institute, Technical University of Denmark
- [RD-3] Finlay, C. C. et al., International Geomagnetic Reference Field – the eleventh generation, Geophys. J. Int., 183, 1216-1230, doi: 10.1111/j.1365-246X.2010.04804.x, 2010
- [RD-4] Olsen, N., H. Lühr, T. J. Sabaka, M. Manda, M. Rother, L. Tøffner-Clausen and S. Choi, CHAOS—a model of the Earth's magnetic field derived from CHAMP, Ørsted, and SAC-C magnetic satellite data, Geophys. J. Int., 166, doi: 10.1111/j.1365-246X.2006.02959.x, 2006
- [RD-5] <http://core2.gsfc.nasa.gov/CM/>
- [RD-6] Wardinski, I., Continuous Covariant Constrained-end-points field model (C3FM) published online at www.gfz-potsdam.de/pb2/pb23/Models/index.html, 2007

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 22 of 136

- [RD-7] Lesur, V., I. Wardinski, M. Rother, and M. Manda, GRIMM - The GFZ Reference Internal Magnetic Model based on vector satellite and observatory data, *Geophys. J. Int.*, doi:10.1111/j.1365-246X.2008.03724.x, 2008
- [RD-8] Maus, S., M. Rother, C. Stolle, W. Mai, S. Choi, H. Lühr, D. Cooke, and C. Roth, Third generation of the Potsdam Magnetic Model of the Earth (POMME), *Geochem. Geophys. Geosyst.*, 7, Q07008, doi:10.1029/2006GC001269, 2006
- [RD-9] Maus, S., H. Lühr, M. Rother, K. Hemant, G. Balasis, P. Ritter, and C. Stolle, Fifth-generation lithospheric magnetic field model from CHAMP satellite measurements, *Geochem. Geophys. Geosyst.*, 8, Q05013, doi:10.1029/2006GC00152, 2007
- [RD-10] Kuvshinov, A., and N. Olsen, A global model of mantle conductivity derived from 5 years of CHAMP, Ørsted, and SAC-C magnetic data, *Geophys. Res. Lett.*, 33, L18301, doi:10.1029/2006GL027083.3, 2006
- [RD-11] Maus, S., Rother, M., Hemant, K., Stolle, C., Lühr, H., Kuvshinov, A., and Olsen, N., Earth's lithospheric magnetic field determined to spherical harmonic degree 90 from CHAMP satellite measurements, *Geophys. J. Int.*, 164, 319–330, doi: 10.1111/j.1365-246X.2005.02833.x, 2006
- [RD-12] Manoj C., A. Kuvshinov, S. Maus and H. Lühr, Ocean circulation generated magnetic signals, *Earth, Planets and Space*, 58, 429-437, 2006
- [RD-13] Olsen, N., T. J. Sabaka, and F. Lowes: New Parameterization of External and Induced Fields in Geomagnetic Field Modeling, and a Candidate Model for IGRF 2005, *Earth, Planets and Space*, 57, 1141-1149, 2005
- [RD-14] Lühr, H.; Maus, S.: Solar cycle dependence of quiet-time magnetospheric currents and a model of their near-Earth magnetic fields. *Earth Planets and Space*, 62 (No. 10), 843-848, 2010
- [RD-15] Olsen, N., Sabaka, T. J. and Gaya-Pique, L. R., Study of an Improved Comprehensive Magnetic Field Inversion Analysis for Swarm. Final report to ESA study with contract number 19690/06/NL/CB
- [RD-16] Swarm Level 0 Products, doc. no: SW.IF.EAD.GS.00017, EADS Astrium, Friedrichshafen, Germany

2.3 Abbreviations

<i>Acronym</i>	<i>Description</i>
ACC	Accelerometer
ADC	Analogue to Digital Converter
ADD	Architecture Design Document
APDF	Archiving and Payload Data Facility
AOCS	Attitude & Orbit Control Subsystem
ANGARA	Analysis of Non-Gravitational Accelerations due to Radiation and Aerodynamics

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 23 of 136

<i>Acronym</i>	<i>Description</i>
ASM	Absolute Scalar Magnetometer
BGS	British Geological Survey
CCDB	Characterisation and Calibration Data Base
CDC	Compact Detector Coil
CDR	Critical Design Review
CI	Comprehensive Inversion
CoG	Center of Gravity
CSC	Compact Spherical Coil
CRC	Cycle Redundancy Code
CRF	Common Reference Frame
DCG	Document Contents Guidelines
DS	Data Set
DSD	Data Set Description
DSR	Data Set Records
DNSC	Danish National Space Center (now DTU Space)
DTU	Technical University of Denmark
EADS	European Aeronautic Defence and Space
EEF	Earth Explorer Format
	Eastward Electric Field
EESS	End-to-End System Simulator
EFI	Electric Field Instrument
EPS	Electrical Power Subsystem ITRF
ESA	European Space Agency
eu	engineering unit
FAC	Field-Aligned Current
GFZ	GeoForschungsZentrum, Potsdam, germany
GNSS	Global Navigation Satellite System
GPS	Global Positioning System
GPSR	GPS/GNSS Receiver
GS	Ground Segment
HWM	Horizontal Wind Model

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 24 of 136

<i>Acronym</i>	<i>Description</i>
ICRS	International Celestial Reference System
ICGFM	International Center for Global Earth Models
IERS	International Earth Rotation Service
IGRF	International Geomagnetic Reference Field
IGS	International GNSS Service
IPGP	Institut de Physique du Globe de Paris, France
IRI	International Reference Ionosphere
ITRF	International Terrestrial Reference Frame
ISP	Instrument Source Packet
ITRS	International Terrestrial Reference System
JPL	Jet Propulsion Laboratory
KO	Kick-Off
LDA	Local Data Archive
LP	Langmuir Probe
L2PS	Level 2 Processing System
MSIS	Mass Spectrometer and Incoherent Scatter
MOD	Medium precision Orbit Determination
MPH	Main Product Header
MPPF	Mission Performance & Planning System
NEC	North-East-Centre reference frame
N/A	Not Applicable
NRL	Naval Research Laboratory
PC	Polar Cap index
PDGS	Payload Data Ground Segment
PDS	Payload Data Segment
PPS	Pulse per Second
POD	Precise Orbit Determination
S/C	Spacecraft
SCARF	Satellite Constellation Application and Research Facility
SMART	Swarm Magnetic and Atmospheric Research Team
SOW	Statement of Work
SPH	Specific Product Header

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 25 of 136

<i>Acronym</i>	<i>Description</i>
SRD	System Requirements Document
STR	Star Tracker
SV	Secular Variation
TBC	To Be Confirmed
TBD	To Be Defined
TCF	Temporal Calibration File
TII	Thermal Ion Imager
uc	unsigned character
UTC	Universal Time Coordinated
VFM	Vector Field Magnetometer

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 26 of 136

3 The Swarm Science Objectives

According to ESA SP-1279(6) “Swarm – The Earth Magnetic Field and Environment Explorer, Report for Mission Selection”, the five research objectives of the *Swarm* mission are:

- O1: Studies of core dynamics, geodynamo processes, and core-mantle interaction
- O2: Mapping of the lithospheric magnetisation and its geological interpretation
- O3: Determination of the 3-D electrical conductivity of the mantle
- O4: Investigation of electric currents flowing in the magnetosphere and ionosphere
- O5: Magnetic Forcing of the Upper Atmosphere

During the ESA *Swarm* study “Preparation of the *Swarm* Level 2 Data Processing” [AD-9] advanced models for the various contributions to the Earth’s magnetic field have been identified as Level 2 products. In particular, the Comprehensive Inversion (CI) providing mathematical descriptions of the various geomagnetic field contributions is required. In order to derive the best model for each of the various contributions to the geomagnetic field, it is necessary to co-estimate or correct for various other parts to the field. As an example, fields from magnetospheric and ionospheric currents and their Earth-induced counterparts have to be considered when modelling the internal part of the field. If a typical user of magnetic field models relies only on standard models, he/she may not be able to take full advantage of the constellation measurements and thus miss the advantages offered by *Swarm*. This clearly argues for advanced *Swarm* Level 2 magnetic field models.

Also the other science objectives, for instance determination of the electrical conductivity of the mantle, require data products with a good description of the time-space structure of the external (magnetospheric) field and its Earth-induced counterpart.

How the products are attributed to the Swarm Science Objectives is described in Table 5-1 and Table 5-2.

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 27 of 136

4 Structure of product files

This section describes the general structure of the Level 2 product files, which is derived from and similar as described for the Level 1b product format description in [AD-5].

4.1 General Structure of products

The structure of the products produced for delivery to the PDGS follows the requirements of [AD-7] as represented in Figure 4.1 below.




Figure 4.1 General Product Structure

Each product is composed of two physical files:

- XML Header file with extension .HDR
- Product file with an extension depending on the product (see section 5.3)

The XML Header file is an ASCII file containing data information that users can easily access for identifying the product without needs to look inside the product file.

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 28 of 136

It consists of

- Fixed Header, a common header for all files in the Swarm Ground Segment
- Variable Header, including
 - Main Product Header (MPH) containing general information.
 - Specific Product Header (SPH) containing product specific information. The Specific Product Header will also contain references to auxiliary and/or input files relevant for the specific product.

The product file is the real product containing the processing results.

4.2 XML Header File

The XML Header file contains information identifying the product.

The Fixed Header (hereafter called Standard Swarm Header) is the common header for all files in the Swarm Ground Segment, which means it is applied to all files flowing amongst the sub-systems composing the PDGS.

The format of the Standard Swarm Header is under ESA responsibility and is specified in [AD-7] and [AD-8].

The Variable Header (hereafter called Product Header) is the header with format and content depending on the file type and kind of product.

The next sub-paragraphs specify the content of these headers.

4.2.1 Level 2 Products Fixed Header (Standard Swarm Header)

The Standard Swarm Header is completely ASCII and based on XML syntax and conventions proposed in [AD-7].

Table 4-1: Level 2 Fixed Header

Field #	Description	Units		Format
1	File_Name	Tag		
	Product file name (without extension) (see Section 4.4)			55*uc
2	File_Description	Tag		
	Description such as mid column in Table 5-1 - Table 5-3 (For CAT-2 AUX products, allowed entries are described in [AD-11].)			x*uc
3	Notes	Tag		

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 29 of 136

Field #	Description	Units	Format
	This field will be empty.		
4	Mission	Tag	
	Will be “Swarm”.		5*uc
5	File_Class	Tag	
	Type of processing; character 9 – 18 in the file name (see Section 4.4), this can be: OPER = Routine operations RPRO = Reprocessing		4*uc
6	File_Type	Tag	
	Product name, first column in Table 5-1- Table 5-3		10*uc
7	Validity_Period	Tag	
7.1	Validity_Start	Tag	
	Start time of validity period UTC=yyyy-mm-ddThh:mm:ss		23*uc
7.2	Validity_Stop	Tag	
	Stop time of validity period UTC=yyyy-mm-ddThh:mm:ss		23*uc
8.	File_Version	Tag	
	Version number of the product Start with 0001 and increases by one if following product versions are generated.		%04d
9.	Source	Tag	
9.1	System	Tag	
	Name of the Ground Segment component: L2PS: for CAT_1 products APDF: for CAT-2 products		4*uc
9.2	Creator	Tag	
	Name of Level 2 processor , such as <i>CI</i> for comprehensive inversion, or <i>IBI</i> for bubble index, <i>SwarmLevel2Create</i> for CAT-1 AUX products, <i>ADF Preprocessor</i> for CAT-2 AUX products.		x*uc

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 30 of 136

Field #	Description	Units	Format
9.3	Creator_Version	Tag	
	Version of Level 2 processor VV.rr		5*uc
9.4	Creation_Date	Tag	
	Date of file creation: UTC=yyyy-mm-ddThh:mm:ss		23*uc

4.2.2 Level 2 Products Variable Header (Product Header)

The XML Variable Header (hereafter called Product Header) for the Level 2 products is composed by:

- an XML Main Product Header (XML MPH), and
- an XML Specific Product Header (XML SPH)

Each header is completely ASCII and based on XML syntax and conventions proposed in the [AD-7].

The following sections describe the MPH and SPH for Level 2, Cat-1 Auxiliary products, and Cat-2 Auxiliary products AUX_LIT_2F, AUX_COR_2F and AUX_IGR_2F. MPH and SPH for all other CAT-2 AUX products are described in [AD-11].

4.2.2.1 XML Main Product Header (XML MPH)

The Main Product Header (MPH) has the following format – very similar to the Level 0 and Level 1b Main Product Header ([AD-5],[AD-6]), see also [AD-8]:

Table 4-2 Level 2 Main Product Header (MPH)

Field #	Description	Units	Format
1	MPH	Tag	
Following fields 1.1 – 1.9 are valid for all L2, Cat-1 Auxiliary products, and Cat-2 AUX_LIT_2F, AUX_COR_2F and AUX_IGR_2F Auxiliary products (not for other Cat-2 Auxiliary products)			
1.1	Product	Tag	
	Product file name (without extension) (see Section 4.4)		55*uc
1.2	Product_Format	Tag	
	Format of the Product file: CDF, PDF or ASCII		5*uc
1.3	Proc_Stage_Code	Tag	
	character 9 – 18 in the file name (see Section 4.4), this can be:		4*uc

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 31 of 136

Field #	Description	Units		Format
	OPER = Routine operations RPRO = Reprocessing			
1.3	Ref_Doc	Tag		
	Reference Document describing the product, shall be <i>SW-DS-DTU-GS-0001</i>			17*uc
<i>Data Processing Information</i>				
1.4	Proc_Center	Tag		
	Processing Center ID code: BGS = British Geological Survey DEOS = DEOS DTU = DTU Space ETH = Eidgenössische Technische Hochschule GFZ = GeoForschungsZentrum Potsdam IPGP = Institut de Physique du Globe de Paris PDGS = Payload Data Ground Segment			4*uc
1.5	Proc_Time	Tag		
	Processing Time, UTC (Product Generation Time) UTC=yyyy-mm-dd Thh:mm:ss.uuuuuu			30*uc
1.6	Software_Version	Tag		
	Processor Name and software version number <i>ProcessorName/VV.rr</i> (<i>Processor name</i> as tag 9.2 of Fixed header)			x*uc
<i>Product Confidence Data Information</i>				
1.7	Product_Err	Tag		
	Product Error Flag. Set to 0 if product is fully ok, non-zero if any problems or errors are present			uc
<i>Product Size Information</i>				
1.8	Tot_Size	Tag		
	unit="bytes"	Attribute		

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 32 of 136

Field #	Description	Units	Format
	Total size of product	bytes	%+021d
1.9	CRC	Tag	
	Cyclic Redundancy Code computed as overall value of all records of the Measurement Data Set. Will be set to “-0000000001” if not computed.		%+011d

4.2.2.2 XML Specific Product Header (XML SPH)

The formats of the Specific Product Headers (SPHs) are described. The SPHs are separately described for Level-2 Products (Cat-1 and Cat-2) and for CAT-1 AUX products. The SPH for CAT-1 AUX products applies also to the CAT-2 AUX products AUX_IGR_2F, AUX_COR_2F and AUX_LIT_2F. The SPH's for all other CAT-2 AUX products are described in [AD-11].

Table 4-3 Level 2 Specific Product Header (SPH) – For L2 Cat-1 and L2 Cat-2 products

Following fields 1.1 – 1.6 are valid for L2 Cat-1 products				
Field #	Description	Units		Format
1	SPH	Tag		
1.1	SPH_Descriptor	Tag		
	Product Name, first column of Tables 5.1 – 5.3			10*uc
1.2	Original_Filename	Tag		
	Name of original files, e.g, “*.SP3” for GPS orbit files			x*uc
Information on Time of Data				
1.3	Sensing_Time_Interval	Tag		
1.3.1	Sensing_Start	Tag		
	Start time in UTC of sensing data UTC=yyyy-mm-ddThh:mm:ss.uuuuuu			30*uc
1.3.2	Sensing_Stop	Tag		
	Stop time in UTC of sensing data UTC=yyyy-mm-ddThh:mm:ss.uuuuuu			30*uc
Product Confidence Section – various information on the quality of the product, such as number of missing				

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 33 of 136

<i>or erroneous ISPs (Instrument Source Packets) and number of rejected or suspicious samples.</i>				
1.4	Product_Confidence_Data	Tag		
1.4.1	Quality_Indicator	Tag		
	General product quality indicator, 000 if best quality is expected, 001 if the quality is acceptable.			%03d
<i>List of Input files</i>				
1.5	List_of_Input_File_Names	Tag		
	count="n"	Attribute		
<i>This part is repeated n times, one for each input file</i>				
1.5.i	File_Name			*uc
	Name of processor input file <i>i</i>			
<i>List of Output files</i>				
1.6	List_of_Output_File_Names	Tag		
	count="n"	Attribute		
<i>This part is repeated n times, one for each output file</i>				
1.6.i	File_Name			*uc
	Name of processor output file <i>i</i>			
Following fields 1.1 – 1.5 are valid for L2 Cat-2 products				
Field #	Description	Units		Format
1	SPH	Tag		
1.1	SPH_Descriptor	Tag		
	Product Name, first column of Tables 5.1 – 5.3			10*uc
<i>Information on Time of Data</i>				
1.2	Orbit_Information	Tag		
1.2.1	Sensing_Start	Tag		

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 34 of 136

	Start time in UTC of sensing data UTC=yyyy-mm-ddThh:mm:ss.uuuuuu			30*uc
1.2.2	Sensing_Stop	Tag		
	Stop time in UTC of sensing data UTC=yyyy-mm-ddThh:mm:ss.uuuuuu			30*uc
<i>Information on manoeuvre</i>				
1.3	Maneuver_Information	Tag		
	count="n"	Attribute		
1.3.i	Maneuver_Id	Tag		
	i=1, ..., n			
	The i^{th} , distinct maneuver identification code [RD-16]			%03d
<i>Product Confidence Section – various information on the quality of the product, such as number of missing or erroneous ISPs (Instrument Source Packets) and number of rejected or suspicious samples.</i>				
1.4	Product_Confidence_Data	Tag		
1.4.1	Quality_Indicator	Tag		
	General product quality indicator			%03d
	FAC_TMS_F and FACx_TMS_2F: 000 no problems at all occurred 001 quality_indicators is 001 in the L1b header of one of the MAGx_LR_1B 010 Flags(1) or Flags(2) is/are larger than 0 (data gaps occurred) 100 if one or all of Flags(3...8) are larger than 0 (problems with auxiliary data for magnetospheric field calculation occurred); And combinations of quality indicators IBIxTMS_2F: 000 no problems at all occurred 001 quality_indicators is 001 in the L1b header of one of the MAGx_LR_1B or EFix_PL_1B 010 all of the Bubble_Index within the output are -1 (unanalyzable) TECxTMS_2F: 000 no problems at all occurred			

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 35 of 136

	001 L1b header of one of the MODx_SC_1B or GPSx_RO_1B quality_indicators is 001 010 daily average of Relative_STEC_RMS or daily average of DCB_Error is larger than 2 TECU EFFxTMS_2F: 000: no problems at all occurred 001: L1b header of one of the MAGx_LR_1B quality indicators is 001 010: Flags(4) is larger than 0 (data gap prevented processing)			
<i>List of input files</i>				
1.5	List_of_DSDs	Tag		
	count="n"	Attribute		
<i>This part is repeated n times, one for each input file</i>				
1.5.i	DSD	Tag		
	Data Set <i>i</i> descriptor, <i>i</i> = 1,2,...,n			
1.5.i.1	Data_Set_Name	Tag		
	Product name (see Table 5-2 Final Level 2 products)			10*uc
1.5.i.2	Data_Set_Type	Tag		
	Type of Data Set: M – measurement R – reference			uc
1.5.i.3	File_Name	Tag		
	Name of Input File (without extension)			55*uc
1.5.i.4	Data_Set_Offset	Tag		
	unit="bytes" Offset (in bytes) of first byte of first DS record within Product File. Only used if Data_Set_Type = "M", otherwise set to zeros.	Attribute		%+021d
1.5.i.5	Data_Set_Size	Tag		
	unit="bytes"	Attribute		

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 36 of 136

	Total number of bytes in DS Only used if Data_Set_Type = “M”, otherwise set to zeros.			%+021d
1.5.i.6	Num_of_Records	Tag		
	Number of Data Set records. Only used if Data_Set_Type = “M”, otherwise set to zeros.			%+011d
1.5.i.7	Record_Size	Tag		
	unit=”bytes” Size of Data Set records If variable set to –0000000001 Only used if Data_Set_Type = “M”, otherwise set to zeros.	Attribute		%+011d
1.5.i.8	Byte_Order	Tag		
	Byte ordering information. 3210 → Big-endian 0123 → Little-endian Only used if Data_Set_Type = “M”, otherwise set to “0000”.			4*uc

Table 4-4 Level 2 Specific Product Header (SPH) – For CAT-1 AUX products and for AUX_IGR_2F, AUX_COR_2F and AUX_LIT_2F

Field #	Description	Units		Format
1	SPH	Tag		
1.1	SPH_Descriptor	Tag		
	Product Name, first column of Tables 5.1 – 5.3			10*uc
<i>Information on Time of Data</i>				
1.2	Validity_Time_Interval	Tag		
1.2.1	Validity_Start	Tag		
	Start time in UTC of sensing data UTC=yyyy-mm-dd Thh:mm:ss.uuuuuu			33*uc
1.2.2	Validity_Stop	Tag		

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 37 of 136

	Stop time in UTC of sensing data UTC=yyyy-mm-dd Thh:mm:ss.uuuuuu			33*uc
<i>Product Confidence Section – various information on the quality of the product, such as number of missing or erroneous ISPs (Instrument Source Packets) and number of rejected or suspicious samples.</i>				
1.4	Product_Confidence_Data	Tag		
1.4.1	Quality_Indicator	Tag		
	General product quality indicator, 000 if best quality is expected. A different number than 000, if problems occurred during processing.			%03d
<i>Originator information</i>				
1.5	Source	Tag		
1.5.1	Original_Filename	Tag		
	Name of the original file before reformatting Examples: AUX_KP_2_ : kpyyyy.wdc AUX_DST_2_ : dstyyyyymm.ig2 AUX_F10_2_ : DAILYPLT.OBS AUX_IMF_2_ : omni2_h0_mrg1hr_yyyymmdd_v01.cdf AUX_OBS_2_ : *yyyy*.min (if only obsyyyyymmddqmin.min files as input) *yyyy.wdc (if only obsyyyy.wdc as input) wdc_mixed (if obsyyyyymmddqmin.min and obsyyyy.wdc as input) AUX_COR_2_ : freely chosen by the chain AUX_LIT_2_ : freely chosen by the chain AUX_IGR_2_ : igrf12coeffs.txt AUX_COR_2F : as for AUX_COR_2_ AUX_LIT_2F : as for AUX_LIT_2_ AUX_IGR_2F : as for AUX_IGR_2_ with yyyy=year, mm=month and dd=day			x*uc
1.5.2	Creator_Date	Tag		
	Date of creation of the original file UTC=yyyy-mm-ddThh:mm:ss			23*uc
1.5.3	Creator	Tag		

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 38 of 136

	Name of the external facility creating the original file, e.g., AUX_KP_2_ : Niemegk observatory AUX_DST_2_ : WDC Kyoto AUX_F10_2_ : NGDC NOAA AUX_IMF_2_ : NASA AUX_OBS_2_ : INTERMAGNET and WDC Edinburgh AUX_COR_2_ : GFZ AUX_LIT_2_ : IPGP AUX_IGR_2_ : IAGA AUX_COR_2F : <i>as for AUX_COR_2_</i> AUX_LIT_2F : <i>as for AUX_LIT_2_</i> AUX_IGR_2F : <i>as for AUX_IGR_2_</i>			x*uc
--	--	--	--	------

4.2.3 Input Files

Input files to the Level 2 Processor (Level 1b and auxiliary products) used in the generation of the products are specified in the specific product header (section 4.2.2.2).

4.3 Product File Formats

The L2 and Auxiliary Product File consist of data sets with specific formats that have been agreed during the SCARF Technical Meeting 2 on February 22/23, 2010. Five different formats exist:

- ASCII Listing (SHC format)
- ASCII Listing (SP3 format)
- ASCII Listing (XML)
- ASCII Listing (others)
- CDF-format
- PDF-files

The following section describes the format categories in more detail. The format category for the individual products is provided in Table 5-1 – Table 5-3.

4.3.1 ASCII Listing (SHC format)

All core and lithosphere magnetic field model products (final and intermediate) obey the SHC format. Missing data values are marked with NaN.

The Gauss coefficients g and h of spherical harmonic models are given as snapshots at different time instants. A static field (i.e. the high-degree lithospheric field) is given as one snapshot; the core field is provided as a series of snapshot models.

Each file contains one or more blocks. Each of these blocks describes a certain range of Gauss coefficients with the same description of time dependence (i.e. either static, linear time dependent, cubic splines, or order-6 splines, or others).

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 39 of 136

Each block contains a header part and a coefficient part of length $K = N_{\max}*(N_{\max}+2) - (N_{\min}-1)*(N_{\min}+1)$ lines with the Gauss coefficients stored row-wise in natural order ($g_1^0, g_1^1, h_1^1, g_2^0, g_2^1, h_2^1, \dots$). The first column of this coefficient part contains spherical harmonic degree n , the second contains spherical harmonic order m . Non-negative values of the order refer to the Gauss coefficients g_n^m while negative orders indicate the Gauss coefficients h_n^m . Rows 3 to $N_{\text{times}}+2$ of this coefficient part contains the Gauss coefficients of the N_{times} snapshot models, provided at the time instants t (given in decimal years).

Such a series of snapshot models is sufficient to completely describe a model if its time dependence is constant, a Taylor expansion in time, or a piecewise linear varying spline (order 2 spline).

In the case of a time dependence described by splines of order larger than 2 (e.g. cubic splines, i.e. spline of order 4), additional information is needed to reconstruct the time dependence from the N_{times} snapshot models. Within SCARF, following format applies: providing `spline_order` snapshot models for each knot interval (i.e. an “oversampling” of the model), indicated by the value `N_step` (which is equal to `spline_order-1` in this case). This is explained in Table 4-5 SHA format used in SCARF. Every `N_step` value of time t (in decimal years) are the spline knots, and therefore `N_step = spline_order - 1`. It is possible to read the whole block using space-delimited free format read instructions.

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 40 of 136

# Comment line part. An arbitrary number of comment lines, each starting with '#',						
# may be added before or after each block						
N_min	N_max	N_times	spline_order	N_step =spline_order -1	Start validity time (optional)	Stop validity time (optional)
		t (1)	t (2)	t (3)	...	t (N_times)
N_min	0	g (1)	g (2)			g (N_times)
N_min	1	g (1)	g (2)			g (N_times)
N_min	-1	h (1)	h (2)			h (N_times)
n	m	g (1)	g (2)			g (N_times)
n	-m	h (1)	h (2)			h (N_times)
N_max	N_max	g (1)	g (2)			g (N_times)
N_max	- N_max	h (1)	h (2)			h (N_times)

Table 4-5 SHA format used in SCARF. Every N_step value of time t (in decimal years) are the spline knots, and therefore N_step = spline_order - 1.

Table 4-6 Has become obsolete. Deleted.

4.3.2 ASCII Listing (SP3 format)

The National Geodetic Survey Standard GPS Format SP3 is a specific format which is applied to represent ephemeris and other orbit characteristics of satellites.

The format is described and discussed in detail in http://www.ngs.noaa.gov/orbits/sp3_docu.txt . All times in a SP3 files refer to GPS time.

4.3.3 ASCII Listing (XML format)

Has become obsolete. Deleted.

Table 4-7 Has become obsolete. Deleted.

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 41 of 136

4.3.4 ASCII Listing (others)

Products that are given in standardized formats are represented as ASCII listing. Formats for Euler angles Mantle conductivity and ionospheric field products are described below. Other products may have different ASCII formats, which are described in respective tables of sections 5.7 - 5.13.

4.3.4.1 Format for Euler Angle Products (MSW_EUL)

Euler angles are represented in the reference frame described in Fig 5.2 and Eqs. (5.4)-(5.7) of [RD-15]. Following 3 comment lines, each line presents one time instant. After the time stamp the lines consist of 9 values; 3 Euler angles (in degree) for each of the 3 Swarm satellites. Quality indicators for the Euler angle estimation are part of internal product validation reports (MSW_VALi2C, MSW_VALi2D).

```
# Header line
# Header line
# MD2000 SW-A(alpha) SW-A(beta) SW-A(gamma) SW-B(alpha) SW-B(beta) SW-B(gamma) SW-C(alpha) SW-C(beta) SW-C(gamma)
-534.00 -0.478881 0.968858 -0.171713 0.224457 -0.120588 -0.342825 0.617217 0.830820 0.865270
-504.00 -0.478882 0.968854 -0.171712 0.224457 -0.120592 -0.342825 0.617209 0.830820 0.865277
...
```

Table 4-8 Format example of Euler Angle products MSW_EUL

4.3.4.2 Format for mantle conductivity products (MIN_1DM, MIN_3DM, MCR_1DM, MCR_3DM)

The format for products MIN_1DM_2_, MIN_3DM_2a, MIN_3DM_2b and corresponding intermediate products is described as follows:

```
# Arbitrary number of comment lines starting with # sign
N_layer N_theta N_phi
theta_b phi_b
<layer_1>
<layer_2>
<layer_3>
...
<layer_Nlayer>
```

where

N_layer is the number of layers;

N_theta is the number of colatitude nodes. Colatitude of the first node is $90.0/\text{real}(N_theta)$. Step in colatitude is $180.0/\text{real}(N_theta)$, index increases from North to South;

N_phi is the number of longitude nodes. Longitude of the first node is $180.0/\text{real}(N_phi)$. Step in colatitude is $360.0/\text{real}(N_phi)$, index increases from West to East;

theta_b, phi_b are the geographic colatitude and longitude of the North pole in degrees. For example, if (theta_b,phi_b)=(0.00,00.00) the coordinate system used in this file coincides with geographic. If (theta_b,phi_b)=(9.92,287.78) the coordinate system used in this file coincides with dipolar IGRF11 at epoch 2010.0.

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 42 of 136

Each `<layer_k>` block consists of:

```
k r_k sigma0_k 3Dflag  
[sigma_k]
```

where

`k` is the number of layer. Layers are numbered from surface to bottom, starting from 1;

`r_k` is the radius of the outer boundary of the `k`-th layer in kilometers. For Earth, `r_1` should be 6371.2.

`sigma0_k` is the conductivity in the `k`-th layer (Siemens per meter)

`3Dflag` if it equals to 1; the `k`-th layer is laterally homogeneous (1-D) with conductivity `sigma0_k`. No 3-D conductivity is stored, and next block `<layer_k+1>` immediately follows; if it equals to 3, the `k`-th layer is laterally heterogeneous (3-D). Array `sigma_k` is expected in the next `N_theta` lines

`sigma_k` is an array containing the conductivity distribution in the `k`-th layer. It is present only if corresponding `3Dflag` is 3. Each line corresponds to one colatitude, ordered north to south, each column to one longitude ordered eastwards. Unit is S/m.

Additional notes: If the conductivity model is only 1-D, without any lateral heterogeneities, values assigned to `N_theta`, `N_phi`, `theta_b`, and `phi_b` do not influence the model definition, and are in principle arbitrary. For consistency in reading, they should be included in the file with safe values $(N_theta, N_phi) = (1, 1)$, and $(theta_b, phi_b) = (0.00, 00.00)$. Similarly, for 3-D layers, where `sigma_k` is given, the corresponding `sigma0_k` doesn't influence the model definition, and can be arbitrary. It can be used to store any auxiliary conductivity value related to the given layer (i.e., background 1-D value, arithmetic or geometric average of conductivity etc.) but shouldn't be relied upon.

The format for products `MCR_1DM_2_` and `MCR_1DM_2_` and corresponding intermediate products is described as follows:

The files are in ASCII format with LF control character used for newline (unix style), and arbitrary number of spaces used as variable separator in a line. General structure of the files is as follows:

```
# Arbitrary number of comment lines starting with # sign  
N_periods N_theta N_phi 3Dflag  
<block_1>  
<block_2>  
<block_3>  
...  
<block_N_periods>
```

where

`N_periods` is the number of periods;

`N_theta` is the number of colatitude nodes. Colatitude of the first node is $90.0/\text{real}(N_theta)$. Step in colatitude is $180.0/\text{real}(N_theta)$, index increases from North to South;

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 43 of 136

N_phi is the number of longitude nodes. Longitude of the first node is $180.0/real(N_phi)$. Step in colatitude is $360.0/real(N_phi)$, index increases from West to East;

$3Dflag$ equals to 1 for global 1D responses, or equals to 3 if we 2-D maps of C-responses are provided

Each $\langle block_k \rangle$ block consists of:

k T_k $ReC0_k$ $ImC0_k$ $Err0_k$ $Coh20_k$

$[ReC3D_k]$

$[ImC3D_k]$

$[Err3D_k]$

$[Coh23D_k]$

where

k is the index of period. Ordering of periods is arbitrary.

T_k is the k -th period in days.

$ReC0_k$ is the real part of C response at period T_k in kilometers.

$ImC0_k$ is the imaginary part of C response at period T_k in kilometers.

$Err0_k$ is the uncertainty of C response estimation at period T_k in kilometers.

$Coh20_k$ is the squared coherence at period T_k (dimensionless).

$ReC3D_k$ is an array of real parts of local C responses on a $N_theta \times N_phi$ grid at period T_k in kilometers. Each line corresponds to one colatitude, ordered north to south, each column to one longitude ordered eastwards. It is present only if $3Dflag$ equals to 3.

$ImC3D_k$ is an array of imaginary parts of local C responses on a $N_theta \times N_phi$ grid at period T_k in kilometers. Each line corresponds to one colatitude, ordered north to south, each column to one longitude ordered eastwards. It is present only if $3Dflag$ equals to 3.

$Err3D_k$ is an array of uncertainty estimates of local C responses on a $N_theta \times N_phi$ grid at period T_k in kilometers. Each line corresponds to one colatitude, ordered north to south, each column to one longitude ordered eastwards. It is present only if $3Dflag$ equals to 3.

$Coh23D_k$ is an array of squared coherencies on a $N_theta \times N_phi$ grid at period T_k . Each line corresponds to one colatitude, ordered north to south, each column to one longitude ordered eastwards. It is present only if $3Dflag$ equals to 3.

Additional notes:

If the responses are 1-D, values assigned to N_theta , N_phi do not influence the response definition, and are in principle arbitrary. For consistency in reading, they should be included in the file with safe values $(N_theta, N_phi) = (1, 1)$.

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 44 of 136

Similarly, for 2-D maps of responses, where $\text{ReC3D_k}(:, :)$, $\text{ImC3D_k}(:, :)$, $\text{dC3D_k}(:, :)$ and $\text{Coh23D_k}(:, :)$ are given, the corresponding ReC0_k , ImC0_k , dC0_k , Coh20_k don't influence the responses definition, and can be arbitrary. It can be used to store any auxiliary responses/uncertainty etc. values related to the given period (i.e. arithmetic mean or median etc.) but shouldn't be relied upon.

4.3.4.3 Format for ionospheric field products (MIO_SHA)

The primary ionospheric field scalar potential is expressed as follows:

For $a < r < a + h$:

$$V(r, \theta_d, \varphi_d, t, t_m) = (1 + N \cdot F_{10.7}) \sum_{s=smin}^{smax} \sum_{p=pmin}^{pmax} \sum_{n=1}^{nmax} \sum_{m=0}^{mmax} a \left(\frac{r}{a}\right)^n P_n^m(\theta_d) \left\{ \left[q_{nsp}^{m(c)} \cos m\varphi_d + s_{nsp}^{m(c)} \sin m\varphi_d \right] \cos(\omega_s st + \omega_p pt_m) + \left[q_{nsp}^{m(s)} \cos m\varphi_d + s_{nsp}^{m(s)} \sin m\varphi_d \right] \sin(\omega_s st + \omega_p pt_m) \right\} \quad (1)$$

For $r > a + h$:

$$V(r, \theta_d, \varphi_d, t, t_m) = (1 + N \cdot F_{10.7}) \sum_{s=smin}^{smax} \sum_{p=pmin}^{pmax} \sum_{n=1}^{nmax} \sum_{m=0}^{mmax} a \left(\frac{a}{r}\right)^{n+1} P_n^m(\theta_d) \left\{ \left[g_{nsp}^{m(c)} \cos m\varphi_d + h_{nsp}^{m(c)} \sin m\varphi_d \right] \cos(\omega_s st + \omega_p pt_m) + \left[g_{nsp}^{m(s)} \cos m\varphi_d + h_{nsp}^{m(s)} \sin m\varphi_d \right] \sin(\omega_s st + \omega_p pt_m) \right\} \quad (2)$$

where

- r, θ_d and φ_d are the radius, dipole colatitude and longitude based on a location of the Northern dipole at co-latitude θ_{NGP} and longitude φ_{NGP}
- t, t_m are the time of the year counted from January 1, 00 UT, and the magnetic universal time (MUT)
- $a = 6371.2$ km is the radius at the Earth's surface, $h = 110$ km is the altitude of the ionospheric current system
- $P_n^m(\theta_d)$ is the Schmidt semi-normalized Legendre functions
- $\omega_s = 2\pi$ rads/yr and $\omega_p = 2\pi/24$ rads/hr are the fundamental seasonal and diurnal angular frequencies
- $q_{nsp}^{m(c,s)}, s_{nsp}^{m(c,s)}$ are the (real) Gauss coefficients for $a < r < a + h$
- $g_{nsp}^{m(c,s)}, h_{nsp}^{m(c,s)}$ are the (real) Gauss coefficients for $a + h < r$
- $nmax, mmax$ are the maximum degree and order of the Gauss coefficients
- $pmin, pmax$ are the minimum and maximum diurnal wavenumbers
- $smin, smax$ are the minimum and maximum seasonal wavenumbers
- $F_{10.7}$ is solar flux in units of $10^{-22} W m^{-2} Hz^{-1}$
- N is the Wolf ratio in units of $1/(10^{-22} W m^{-2} Hz^{-1})$.

Magnetic universal time (in hours) is given by $t_m = (180 - \varphi_{d,s})/15$ with $\varphi_{d,s}$ as dipole longitude of the subsolar point.

The coefficients describing the primary field above and below the ionosphere are related according to

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 45 of 136

$$g_{nsp}^{m(c,s)} = -\frac{n}{n+1} \left(\frac{a+h}{a} \right)^{2n+1} q_{nsp}^{m(c,s)} \quad (3)$$

The secondary (induced) ionospheric field scalar potential is expressed using equation (2) but with another set of Gauss coefficients, $g_{nsp}^{m(c,s)}$, $h_{nsp}^{m(c,s)}$, for all $r > a$.

The MIO product contains a header of arbitrary length (these header lines start with #), a line containing information about model parameterization

```
nmax mmax pmin pmax smin smax theta_NGP phi_NGP h N
```

(where theta_NGP and phi_NGP are co-latitude and longitude of the Northern dipole in degrees, h is the altitude of the ionospheric current sheet in km, and N is the Wolf ratio that indicates the dependence of the currents on solar flux F10.7), followed by the SH model of the primary field coefficients below the ionosphere, $q_{nsp}^{m(c,s)}$, $s_{nsp}^{m(c,s)}$ and the model of the secondary field coefficients, $g_{nsp}^{m(c,s)}$, $h_{nsp}^{m(c,s)}$.

The general structure of all MIO_SHA product files is as follows:

```
# Header
# Header
nmax mmax pmin pmax smin smax theta_NGP phi_NGP h N
1 0  $q_{1,smin,pmin}^{0(c)}$   $q_{1,smin,pmin}^{0(s)}$  ...  $q_{1,smax,pmax}^{0(c)}$   $q_{1,smax,pmax}^{0(s)}$ 
1 1  $q_{1,smin,pmin}^{1(c)}$   $q_{1,smin,pmin}^{1(s)}$  ...  $q_{1,smax,pmax}^{1(c)}$   $q_{1,smax,pmax}^{1(s)}$ 
1 -1  $s_{1,smin,pmin}^{1(c)}$   $s_{1,smin,pmin}^{1(s)}$  ...  $s_{1,smax,pmax}^{1(c)}$   $s_{1,smax,pmax}^{1(s)}$ 
2 0  $q_{2,smin,pmin}^{0(c)}$   $q_{2,smin,pmin}^{0(s)}$  ...  $q_{2,smax,pmax}^{0(c)}$   $q_{2,smax,pmax}^{0(s)}$ 
2 1  $q_{2,smin,pmin}^{1(c)}$   $q_{2,smin,pmin}^{1(s)}$  ...  $q_{2,smax,pmax}^{1(c)}$   $q_{2,smax,pmax}^{1(s)}$ 
2 -1  $s_{2,smin,pmin}^{1(c)}$   $s_{2,smin,pmin}^{1(s)}$  ...  $s_{2,smax,pmax}^{1(c)}$   $s_{2,smax,pmax}^{1(s)}$ 
2 2  $q_{2,smin,pmin}^{2(c)}$   $q_{2,smin,pmin}^{2(s)}$  ...  $q_{2,smax,pmax}^{2(c)}$   $q_{2,smax,pmax}^{2(s)}$ 
2 -2  $s_{2,smin,pmin}^{2(c)}$   $s_{2,smin,pmin}^{2(s)}$  ...  $s_{2,smax,pmax}^{2(c)}$   $s_{2,smax,pmax}^{2(s)}$ 
...
1 0  $g_{1,smin,pmin}^{0(c)}$   $g_{1,smin,pmin}^{0(s)}$  ...  $g_{1,smax,pmax}^{0(c)}$   $g_{1,smax,pmax}^{0(s)}$ 
1 1  $g_{1,smin,pmin}^{1(c)}$   $g_{1,smin,pmin}^{1(s)}$  ...  $g_{1,smax,pmax}^{1(c)}$   $g_{1,smax,pmax}^{1(s)}$ 
1 -1  $h_{1,smin,pmin}^{1(c)}$   $h_{1,smin,pmin}^{1(s)}$  ...  $h_{1,smax,pmax}^{1(c)}$   $h_{1,smax,pmax}^{1(s)}$ 
2 0  $g_{2,smin,pmin}^{0(c)}$   $g_{2,smin,pmin}^{0(s)}$  ...  $g_{2,smax,pmax}^{0(c)}$   $g_{2,smax,pmax}^{0(s)}$ 
2 1  $g_{2,smin,pmin}^{1(c)}$   $g_{2,smin,pmin}^{1(s)}$  ...  $g_{2,smax,pmax}^{1(c)}$   $g_{2,smax,pmax}^{1(s)}$ 
2 -1  $h_{2,smin,pmin}^{1(c)}$   $h_{2,smin,pmin}^{1(s)}$  ...  $h_{2,smax,pmax}^{1(c)}$   $h_{2,smax,pmax}^{1(s)}$ 
2 2  $g_{2,smin,pmin}^{2(c)}$   $g_{2,smin,pmin}^{2(s)}$  ...  $g_{2,smax,pmax}^{2(c)}$   $g_{2,smax,pmax}^{2(s)}$ 
2 -2  $h_{2,smin,pmin}^{2(c)}$   $h_{2,smin,pmin}^{2(s)}$  ...  $h_{2,smax,pmax}^{2(c)}$   $h_{2,smax,pmax}^{2(s)}$ 
...
```

Each of the two models (describing the primary, resp. secondary, field) is stored as a $N_{nm} \times (2N_{sp})$ block of coefficients, where

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 46 of 136

$$N_{nm} = mmax(mmax + 2) + (nmax - mmax)(2mmax + 1)$$

$$N_{sp} = (pmax - pmin + 1)(smax - smin + 1)$$

The first two columns contain the n, m values for each series of $2N_{sp}$ coefficients; negative m values indicate that the line is that of $\sin m\varphi_d$ coefficients. Coefficients are stored by iterating on s, p in that order (same as in equations (1) and (2)), i.e. p is nested within s such that in each line

$$\begin{array}{cccccccc} n, m, q_{n,smin,pmin}^{m(c)} & q_{n,smin,pmin}^{m(s)} & q_{n,smin,pmin+1}^{m(c)} & q_{n,smin,pmin+1}^{m(s)} & q_{n,smin,pmin+2}^{m(c)} & q_{n,smin,pmin+2}^{m(s)} & \cdots \\ q_{n,smin,pmax}^{m(c)} & q_{n,smin,pmax}^{m(s)} & q_{n,smin+1,pmin}^{m(c)} & q_{n,smin+1,pmin}^{m(s)} & \cdots & q_{n,smax,pmax}^{m(c)} & q_{n,smax,pmax}^{m(s)} \end{array}$$

4.3.5 CDF format

The CDF format is applied for many L1b products. The data volume will be minimized with gzip applied to each variable separately, rather than to the whole file content. This allows a faster access to single variables, if needed. Missing data values are marked with NaN.

CDF time variables are given in CDF epoch. The CDF epoch is defined in UTC and as the number of milliseconds since 01-Jan-0000 00:00:00.000. The CDF epoch unit is ms (milliseconds).

As of September 2011, CDF library version 3.3 is required to read all CDF files described in the document.

The number and content of the variables are provided in detail in appropriate sections 0 - 5.13.

4.3.6 PDF reports

Validation and Quick look reports are provided in PDF format.

4.4 File Names

The file names of each **Level 2 product** is defined in [AD-8], that is:

MM_CCCC_TTTTTTTTTT_yyyymmddThhmmss_YYYYMMDDTHHMMSS_vvvv.HDR

MM_CCCC_TTTTTTTTTT_yyyymmddThhmmss_YYYYMMDDTHHMMSS_vvvv.EXT

where the meaning of the elements composing the file name is described in section 4 of [AD-8] and are:

MM = SW (Mission ID)

CCCC = OPER or RPRO (for “Operational” or “Reprocessing”)

TTTTTTTTTT = Product name, as defined in section 5.1

yyymmddThhmmss = validity start time
(e.g. 20050608T121500 represents 08-JUN-2005 12:15:00.000000)

YYYYMMDDTHHMMSS = validity stop time

vvvv = version number

EXT = Product extension, as defined in section 5.3

The validity start and end time is similar to the description in section 4.1.5.3 “*Shape 1, Context 3: Validity Period with respect to Time of Contents Relevance*” in [AD-8] where it is also stated: “As validity time

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 47 of 136

values may have greater precision than a second, all validity start times shall be round down and all validity stop times shall be rounded up. “

For example, in case of the MCO_SHA_2D Level 2 product the names are:

```
SW_OPER_MCO_SHA_2D_20120924T075728_20130228T230231_0001.HDR
```

```
SW_OPER_MCO_SHA_2D_20120924T075728_20130228T230231_0001.shc
```

The file with the extension .HDR is the XML Header file and the file with the extension .DBL is the Level 2 product file. Both files will be zipped together into one file with the extension .ZIP .

For some products, such as lithospheric field products, a validity time is not applicable, because the lithospheric field is regarded as time-invariant. For such cases, the consortium has proposed following convention for validity start and stop time: 00000000T000000_99999999T999999.

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 48 of 136

5 Specification of Level 2 Products and Auxiliary Products

This chapter starts with the description of the product name convention in section 5.1 and the product classification in section 5.2. The chapter follows on with a product overview (section 5.3) and then specifies each product in detail (section 5.4 ff.).

5.1 Product name convention

According to [AD-8], Swarm product names consist of 10 digits, which are subdivided into two sub-fields as follows: TTTTTTTTTT = FFFFDDDDDD, where FFFF = File Category and DDDDDD = Semantic Descriptor.

For Level 2 products FFFF = FFFx. FFF describes the product type (e.g., MCO – Magnetic Core Field, AUX – Auxiliary Product), and x = _ if the product is derived from (available for) the satellite constellation, and x = A, B or C, respectively for Swarm A, Swarm B or Swarm C, if single satellite products are derived.

For Level 2 products DDDDDD = DDDy2z. DDD provides a description which is specific for each product, for example TMS for time series or SHA for spherical harmonics. y = i for intermediate products and y = _ when final products are concerned.

The last two digits describe the product level [AD-8]. Therefore digit 9 is always 2, identifying the product as a Level 2 product.

The last digit z indicates the origin or the purpose of the product. This applies especially when different chains lead to the same science product. This last digit z can be:

C	Derived from Comprehensive Inversion
D	Derived from dedicated chain
F	Fast Track product
E	Extended, only applied for extended lithospheric field maps (MLI_SHA_2E)
_	Only one chain has been identified to lead to this product type
a	Product derived from candidate chain a (only applied for mantle conductivity products – derived in the frequency domain)
b	Product derived from candidate chain b (only applied for mantle conductivity products – derived in the time domain)

For example, the intermediate product of the spherical harmonic model of the core field derived from CI is named MCO_SHAi2C, and the final product of the spherical harmonic model of the core field derived from dedicated inversion is named MCO_SHA_2D. The product of Eastward Electric Field derived from Swarm C is called EEECTMS_2F. The Auxiliary data product for the KP index is called AUX_KP__2_.

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 49 of 136

5.2 Product classification

Different product types exist in the Level 2 processor.

5.2.1 Level 2 products

Three Categories have been defined in [AD-10]. Each Level 2 product is attributed to one of these categories.

CAT-1: Complex algorithms contributing to the generation of a Level 2 product of the various sources of the Earth's magnetic field, of thermospheric products, and for Precise Orbit determination. The generation of CAT-1 products require interaction with experienced scientists. The products will be processed by SCARF, and will be distributed by ESA.

CAT-2: Algorithms leading to a Level 2 product with minimum delay with respect to the generation of the corresponding Level 1b data. The generation of CAT-2 products is designed to run automatically. The CAT-2 products will be generated and distributed by ESA.

Intermediate and final products

Some Level 2 products are further characterized by product types. These are:

- **Intermediate products** are Level 2 products which are independently validated before their release to final Level 2 products. Intermediate products are delivered to PDGS together with an **intermediate validation report**. An intermediate validation report exists to each chain that submit an intermediate product. The intermediate validation report product name is FFF_VALi2z, e.g., MCO_VALi2C.
- **Final Level 2 products** are validated intermediate products or products which are released on Fast Track including internal quality check (Fast Track Products). Only Final products are distributed to the end users.

Candidate products

For all magnetic field products and the 3D-mantle conductivity product two or three different candidates can be identified reaching to the same product quantity. For all magnetic field products, the candidates are derived in the Comprehensive Inversion Chain or in Dedicated Inversion Chains or as Fast Track products. This identification is indicated by the last character in the product name C, D or F (see also section 5.1).

In the case of 3D mantle conductivity model, the two candidates differ in that they are derived in the frequency domain or in the time domain. This differentiation, a or b, is indicated by the last character in the product name.

All other products have only one candidate.

Fast Track products

Fast Track products have no intermediate stage. The validation is performed by means of an internal quality check in the algorithms of each of these products, and the quality of the product is provided, e.g., by a quality flag. Fast Track products are released without a validation report.

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 50 of 136

Three CAT-1 magnetic products will be derived on Fast Track (Euler angles, core field model, magnetospheric model). All CAT-2 products are Fast Track products. For all Fast Track products, the last letter of the product name is F (see section 5.1).

Final validation reports

For non-Fast Track products a validation report is required when releasing the intermediate products to the final product stage. A final validation report is provided for each product chain, e.g., MCO_VAL_2D, for the final validation report for the dedicated chain for the core field model. The input of the final validation report is the intermediate product, the intermediate validation report and auxiliary products.

The intercomparison between products of two chains in one product family (e.g., MCO_SHA_2D and MCO_SHA_2C), will be released in one validation report called, e.g, MCO_VAL_2_.

Validation report products exist for following product families: Euler angles, core field models, lithospheric field models, ionospheric models, magnetosphere models, 1D-mantle conductivity (mantle conductivity model and C-response), 3D-mantle conductivity (mantle conductivity model and C-response maps), precise orbit determination and thermospheric winds and density.

Final validation reports are Final Level 2 products. **Auxiliary products**

Auxiliary products are necessary prior or during processing of high precision Swarm Level 2 products but do not result from the Swarm L0 or L1b processor. Auxiliary products are further classified in auxiliary models and auxiliary data.

For auxiliary products that are needed in CAT-1 as well as in CAT-2 chains, two different products are defined. The acquisition of auxiliary products for CAT-2 products lies in the responsibility of PDGS in the course of the mission. The name of all CAT-2 auxiliary products end with the letter F – Fast track.

5.2.3 Level 2 product selection

All Level 2 Cat-1 Fast-Track, Quick-Look, Orbit Determination, and Upper Atmosphere products (see Table 5-2) will be transferred from the product creator (L2PS) to PDGS at ESA for immediate dissemination to the user community.

Level 2 Cat-1 magnetic products (all non Fast-Track magnetic field model and mantle conductivity products, see Table 5-2) are subject to independent validation by BGS. The validation reports together with the model products are further subject to an independent review performed by the product creator (L2PS), external experts and the Agency. Based on this review, accepted Level 2 products will be transferred from BGS to PDGS for dissemination to the user community.

All Level 2 Cat-2 products are produced and distributed by PDGS and are not subject to external validation.

5.3 Product overview

This section provides an overview about all L2 products, intermediate (Table 5-1), final (Table 5-2), and auxiliary products (Table 5-3). Each product is described in more detail in sections 5.4 - 5.13. Please note that in Table 5-3 the column “Extension” is only present for conformance with Table 5-1 and Table 5-2 and it only contains "DBL".

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 51 of 136

Table 5-1 Intermediate Level 2 products

<i>Science Objective</i>	<i>Product Name</i>	<i>Description</i>	<i>Format</i>	<i>Extension</i>
All, Needed for L1b processing	MSW_EULi2C	CAT-1: Euler angles for all satellites	ASCII listing	.txt
	MSW_VALi2C	Intermediate validation report	PDF report	.pdf
	MSW_EULi2D	CAT-1: Euler angles for all satellites	ASCII listing	.txt
	MSW_VALi2D	Intermediate validation report	PDF report	.pdf
O1: Core Field	MCO_SHAi2C	CAT-1: Spherical harmonic model of the main (core) field and its temporal variation	ASCII listing (SHC)	.shc
	MCO_VALi2C	Intermediate validation report	PDF report	.pdf
	MCO_SHAi2D	CAT-1: Spherical harmonic model of the main (core) field and its temporal variation	ASCII listing (SHC)	.shc
	MCO_VALi2D	Intermediate validation report	PDF report	.pdf
O2: Lithospheric Field	MLI_SHAi2C	CAT-1: Spherical harmonic model of the lithospheric field	ASCII listing (SHC)	.shc
	MLI_VALi2C	Intermediate validation report	PDF report	.pdf
	MLI_SHAi2D	CAT-1: Spherical harmonic model of the lithospheric field.	ASCII listing (SHC)	.shc
	MLI_VALi2D	Intermediate validation report	PDF report	.pdf
	MLI_SHAi2E	CAT-1: Extended spherical harmonic model of the lithospheric field	ASCII listing (SHC)	.shc
	MLI_VALi2E	Intermediate validation report	PDF report	.pdf
O3: Mantle Conductivity	Q3D_CI_i2_	CAT-1: Q-matrix of 3D mantle conductivity including oceans	ASCII listing	.txt
	MIN_1DMi2_	CAT-1: 1D model of mantle conductivity	ASCII listing	.txt
	MI1_VALi2_	Intermediate validation report	PDF report	.pdf
	MIN_3DMi2a	CAT-1: 3D model of mantle conductivity (frequency domain)	ASCII listing	.txt
	MIN_3DMi2b	CAT-1: 3D model of mantle conductivity (time domain)	ASCII listing	.txt
	MI3_VALi2_	Intermediate validation report	PDF report	.pdf
	MCR_1DMi2_	CAT-1: 1D C-response	ASCII listing	.txt
	MC1_VALi2_	Intermediate validation report	PDF report	.pdf
	MCR_3DMi2_	CAT-1: 3D C-response maps	ASCII listing	.txt
	MC3_VALi2_	Intermediate validation report	PDF report	.pdf
O4: External	MMA_SHAi2C	CAT-1: Spherical harmonic model of the large-scale magnetospheric field and its Earth-induced	CDF	.cdf

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 52 of 136

<i>Science Objective</i>	<i>Product Name</i>	<i>Description</i>	<i>Format</i>	<i>Extension</i>
Current Systems		counterpart		
	MMA_VALi2C	Intermediate validation report	PDF report	.pdf
	MIO_SHAi2C	CAT-1: Spherical harmonic model of the daily geomagnetic variation at middle latitudes (Sq and low latitudes – EEJ)	ASCII listing	.txt
	MIO_VALi2C	Intermediate validation report	PDF report	.pdf
	MIO_SHAi2D	CAT-1: Spherical harmonic model of the daily geomagnetic variation at middle latitudes (Sq and low latitudes – EEJ)	ASCII listing	.txt
	MIO_VALi2D	Intermediate validation report	PDF report	.pdf
Accelerometry	ACCxDISi2_	CAT-1: List of disturbances in accelerometer data	CDF	.cdf
	ACCx_FMi2_	CAT-1: Time series of non-gravitational accelerations from force models	CDF	.cdf

O=Science Objective

Table 5-2 Final Level 2 products

<i>Science Objective</i>	<i>Name</i>	<i>Description</i>	<i>Format</i>	<i>Extension</i>
All. Needed for L1b processing	MSW_EUL_2C	CAT-1: Euler angles describing transformation from STR-CRF to VFM frame for satellites A, B, and C	ASCII listing	.txt
	MSW_EUL_2D	CAT-1: Euler angles describing transformation from STR-CRF to VFM frame for satellites A, B, and C	ASCII listing	.txt
	MSW_VAL_2C	CAT-1: Validation report about Euler angles	PDF	.pdf
	MSW_VAL_2D	CAT-1: Validation report about Euler angles	PDF	.pdf
	MSW_VAL_2_	CAT-1: Validation report about Euler angles	PDF	.pdf
	MSW_EUL_2F	CAT-1: Euler angles describing transformation from STR-CRF to VFM frame for satellites A, B, and C	ASCII listing	.txt
O1: Core Field	MCO_SHA_2C	CAT-1: Spherical harmonic model of the main (core) field and its temporal variation	ASCII listing (SHC)	.shc
	MCO_SHA_2D	CAT-1: Spherical harmonic model of the main (core) field and its temporal variation	ASCII listing (SHC)	.shc
	MCO_VAL_2C	CAT-1: Validation report on core magnetic field	PDF	.pdf

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 53 of 136

<i>Science Objective</i>	<i>Name</i>	<i>Description</i>	<i>Format</i>	<i>Extension</i>
	MCO_VAL_2D	CAT-1: Validation report on core magnetic field	PDF	.pdf
	MCO_VAL_2_	CAT-1: Validation report on core magnetic field	PDF	.pdf
	MCO_SHA_2F	CAT-1: Spherical harmonic model of the main (core) field and its temporal variation	ASCII listing (SHC)	.shc
O2: Lithospheric Field	MLI_SHA_2C	CAT-1: Spherical harmonic model of the lithospheric field	ASCII listing (SHC)	.shc
	MLI_SHA_2D	CAT-1: Spherical harmonic model of the lithospheric field	ASCII listing (SHC)	.shc
	MLI_SHA_2E	CAT-1: Extended spherical harmonic model of the lithospheric field	ASCII listing (SHC)	.shc
	MLI_VAL_2C	CAT-1: Validation report on lithospheric field	PDF	.pdf
	MLI_VAL_2D	CAT-1: Validation report on lithospheric field	PDF	.pdf
	MLI_VAL_2E	CAT-1: Validation report on lithospheric field	PDF	.pdf
	MLI_VAL_2_	CAT-1: Validation report on lithospheric field	PDF	.pdf
O3: Mantle Conductivity	MIN_1DM_2_	CAT-1: 1D model of mantle conductivity	ASCII listing	.txt
	MIN_3DM_2a	CAT-1: 3D model of mantle conductivity (frequency domain)	ASCII listing	.txt
	MIN_3DM_2b	CAT-1: 3D model of mantle conductivity (time domain)	ASCII listing	.txt
	MCR_1DM_2_	CAT-1: 1D C-response maps	ASCII listing	.txt
	MCR_3DM_2_	CAT-1: 3D C-response maps	ASCII listing	.txt
	MI1_VAL_2_	CAT-1: Validation report on 1D mantle conductivity	PDF	.pdf
	MI3_VAL_2_	CAT-1: Validation report on 3D mantle conductivity	PDF	.pdf
	MC1_VAL_2_	CAT-1: Validation report on 1D C-response	PDF	.pdf
	MC3_VAL_2_	CAT-1: Validation report on 3D C-response	PDF	.pdf
O4: External Current Systems	MMA_SHA_2C	CAT-1: Spherical harmonic model of the large-scale magnetospheric field and its Earth-induced counterpart	CDF	.cdf
	MMA_VAL_2C	CAT-1: Validation report magnetospheric magnetic model	PDF	.pdf
	MMA_SHA_2F	CAT-1: Spherical harmonic model of the large-scale magnetospheric field and its Earth-induced counterpart	CDF	.cdf
	MIO_SHA_2C	CAT-1: Spherical harmonic model of the daily geomagnetic variation at middle	ASCII listing	.txt

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 54 of 136

<i>Science Objective</i>	<i>Name</i>	<i>Description</i>	<i>Format</i>	<i>Extension</i>
		latitudes (Sq and low latitudes (EEJ))		
	MIO_SHA_2D	CAT-1: Spherical harmonic model of the daily geomagnetic variation at middle latitudes (Sq and low latitudes (EEJ))	ASCII listing	.txt
	MIO_VAL_2C	CAT-1: Validation report on ionospheric magnetic model	PDF	.pdf
	MIO_VAL_2D	CAT-1: Validation report on ionospheric magnetic model	PDF	.pdf
	MIO_VAL_2_	CAT-1: Validation report on ionospheric magnetic model	PDF	.pdf
	IBIxTMS_2F	CAT-2: Ionospheric bubble index	CDF	.cdf
	TECxTMS_2F	CAT-2: Time series of the ionospheric total electron content	CDF	.cdf
	FAC_TMS_2F	CAT-2: Time series of field-aligned currents	CDF	.cdf
	FACxTMS_2F	CAT-2: Time series of field-aligned currents	CDF	.cdf
	EEFxTMS_2F	CAT-2: Equatorial Electric Field	CDF	.cdf
Precise Orbit Determination	SP3xCOM_2_	CAT-1: time series of position and velocity of the center of mass of each satellite (reduced-dynamic POD)	ASCII listing (SP3)	.sp3
	SP3xKIN_2_	CAT-1: time series of position of the center of mass of each satellite (kinematic POD)	ASCII listing (SP3)	.sp3
	SP3xVAL_2_	CAT-1: Validation report for SP3xCOM_2_	PDF	.pdf
	ACCxPOD_2_	CAT-1: Time series of non-gravitational accelerations estimated by POD	CDF	.cdf
Accelerometry	ACCxCAL_2_	CAT-1: Corrected and calibrated accelerometer observations	CDF	.cdf
	ACCxVAL_2_	CAT-1: Validation report for ACCxCAL_2_	PDF	.pdf
O5: Magnetic Forcing of the Upper Atmosphere	ACCx_AE_2_	CAT-1: Time series of calibrated and pre-processed accelerometer observations and of aerodynamic accelerations	CDF	.cdf
	DNSxWND_2_	CAT-1: time series of neutral thermospheric density and wind speed from precise orbit determination and accelerometer data	CDF	.cdf
	DNSxPOD_2_	CAT-1: time series of neutral thermospheric density from precise orbit determination data only	CDF	.cdf
	TDWxVAL_2_	CAT-1: Validation report for DNSxWND_2_	PDF	.pdf
	DNSxVAL_2_	CAT-1: Validation report for DNSxPOD_2_	PDF	.pdf
Quick Look	MAG_QL_2_	Quick Look of magnetic field products MAGx_LR_1B	PDF	.pdf

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 55 of 136

<i>Science Objective</i>	<i>Name</i>	<i>Description</i>	<i>Format</i>	<i>Extension</i>
Reports	EFI_QL_2_	Quick Look of EFix_PL_1B	PDF	.pdf

O=Science Objective

Table 5-3 Auxiliary data and model

<i>Product Name</i>	<i>Description</i>	<i>Format</i>	<i>Extension</i>
AUX_KP_2_	Planetary index of geomagnetic activity	ASCII listing	.DBL
AUX_DST_2_	Equivalent equatorial magnetic disturbances index	ASCII listing	.DBL
AUX_F10_2_	Index of daily solar radio flux	ASCII listing	.DBL
AUX_IMF_2_	Interplanetary magnetic field, 3-component magnetic field, solar wind density and velocity	CDF	.DBL
AUX_KP_2F	Planetary index of geomagnetic activity	ASCII listing	.DBL
AUX_DST_2F	Equivalent equatorial magnetic disturbances index	ASCII listing	.DBL
AUX_F10_2F	Index of daily solar radio flux	ASCII listing	.DBL
AUX_IMF_2F	Interplanetary magnetic field, 3-component magnetic field	ASCII listing	.DBL
AUX_SWV_2F	Solar wind density and velocity	ASCII listing	.DBL
AUX_IRZ_2F	12 month smoothed sunspot number	ASCII listing	.DBL
AUX_APX_2F	Apex magnetic coordinates ¹	ASCII listing	.DBL
AUX_GPSEPH	GPS ephemeris ¹	ASCII listing (SP3)	.DBL
AUX_USLEAP	Leap second information ¹	ASCII listing	.DBL
AUX_DCB_2F	GPS satellite differential code biases	ASCII listing	.DBL
AUX_OBS_2_	Hourly Geomagnetic observatory data; 3-component magnetic field at INTERMAGNET and other magnetic observatories	ASCII listing	.DBL
AUX_OBSM2_	1 minute geomagnetic observatory data; 3-component magnetic field at INTERMAGNET and other magnetic observatories	ASCII listing	.DBL
AUX_OBSS2_	1 second geomagnetic observatory data; 3-component magnetic field at INTERMAGNET and other magnetic observatories	ASCII listing	.DBL
AUX_IGR_2_	IGRF (International Geomagnetic Reference Field) latest generation, model of the Earth's core magnetic field.	ASCII listing (SHC)	.DBL
AUX_COR_2_	Model for the core magnetic field	ASCII listing (SHC)	.DBL
AUX_LIT_2_	Model for the lithospheric magnetic field	ASCII listing (SHC)	.DBL

¹ Used internally by operational processor, product is specified in [AD-11].

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 56 of 136

<i>Product Name</i>	<i>Description</i>	<i>Format</i>	<i>Extension</i>
AUX_IGR_2F	IGRF (International Geomagnetic Reference Field) latest generation, model of the Earth's core magnetic field.	ASCII listing (SHC)	.DBL
AUX_COR_2F	Model for the core magnetic field	ASCII listing (SHC)	.DBL
AUX_LIT_2F	Model for the lithospheric magnetic field	ASCII listing (SHC)	.DBL
AUX_PMF_2F	Magnetospheric model	ASCII listing	.DBL
AUX_PSM_2F	Coefficients to transform from Solar Magnetic (SM) to geographic coordinates for computing the external magnetic field	ASCII listing	.DBL
AUX_PGM_2F	Coefficients to transform from Geocentric Solar Magnetospheric (GSM) to geographic coordinates for computing the external magnetic field	ASCII listing	.DBL
AUX_MTI_2_	Model of magnetic signals of major tidal constituents	ASCII listing	.DBL
AUX_MCM_2_	A priori radially-symmetric (1D) model of mantle conductivity	ASCII listing	.DBL
AUX_OCM_2_	2D model of surface conductance	ASCII listing	.DBL

5.4 Euler Angles

5.4.1 Intermediate Level 2 Candidate Products

Product identifier	MSW_EULi2C
Definition	3 sets of Euler angles, one set for each satellite
Input Data	MAGx_LR_1R, AUX_DST_2_, AUX_KP_2_, AUX_F10_2_, Q3D_CI_i2_
Input Time Span	All available quiet time observations from the mission
Spatial representation	N/A
Time representation	time series (snapshots)
Units	Degree
Resolution	10 ⁻⁶
Uncertainty	Refer to product quality report
Quality indicator	Statistics of data misfit provided in validation report
Data volume	~1 kB
Data format	ASCII listing (section 4.3.4.1)
Output Data	For each satellite A, B, and C: Euler angles, type 1-2-3
Output time span	As input
Update rate	First after 1 year, updated every year
Latency	1.5 months
Notes	

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 57 of 136

Product identifier	MSW_VALi2C
Definition	Intermediate validation report for Euler angle determination from CI
Input Data	MSW_EULi2C
Data volume	< 1 MB
Data format	PDF format
Output Data	PDF file
Latency	Same as for MSW_EULi2C
Notes	

Product identifier	MSW_EULi2D
Definition	3 sets of Euler angles, one set for each satellite.
Input Data	MAG _x _LR_1B (x=[A,B,C]), AUX_IGR_2_, AUX_COR_2_, AUX_LIT_2_, AUX_DST_2_, AUX_KP_2_, AUX_IMF_2_ ; optional: MMA_SHAi2C, MMA_SHA_2F, MIN_1DMi2_
Input Time Span	1 year to full mission, but limited to quiet periods passing the selection
Spatial representation	N/A
Time representation	Time series (snapshots) for the three Euler Angle sets, the time is given in MJD 2000.0 midnight
Units	Degree for Euler Angles, Days, Fraction for leading MJD
Resolution	10 ⁻⁶ for the Euler Angles, 0.01 for MJD
Uncertainty	See notes in this table, otherwise refer to product quality report
Quality indicator	e.g. RMS error or histograms in product quality report
Data volume	~1 kB
Data format	ASCII table (section 4.3.4)
Output Data	For each satellite A, B, and C: three Euler angles, type 1-2-3 preceded by time in MJD
Output time span	Same as input, resolution N/A (adaptive to data)
Update rate	First after 1 year, updated every year.
Latency	6 weeks
Notes	See also Notes in MSW_VAL_2D. If possible, results of three different segmentation windows sizes (i.e. for 5, 10 and 20 days -- the decision to apply for three window sizes and the definitive sizes will depend on data quality) will be, together with the scatter of the time series, used to assess stability and validity of the Euler Angles.

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 58 of 136

5.4.2 Final Level 2 Products

Product identifier	MSW_VALi2D
Definition	Intermediate validation report for Euler angle determination from Dedicated Core
Input Data	MSW_EULi2D
Data volume	< 1 Mb per day
Data format	PDF format
Output Data	PDF file
Update rate	Same as for MSW_EULi2D
Latency	Same as for MSW_EULi2D
Notes	If possible, results of three different segmentation windows sizes (i.e. for 5, 10 and 20 days, the decision to apply for three window sizes and the definitive sizes will depend on data quality) will be, together with the scatter of the time series internally and in conjunction with previous results, used to assess stability and validity of the Euler Angles.

Product identifier	MSW_VAL_2C
Definition	Validation report for Euler angle determination
Input Data	MSW_EULi2C, MSW_VALi2C
Data volume	< 1 Mb per day
Data format	PDF format
Output Data	PDF file
Update rate	Same as MSW_EUL_2C
Latency	1 month
Notes	

Product identifier	MSW_VAL_2D
Definition	Validation report for Euler angle determination
Input Data	MSW_EULi2D, MSW_VALi2D
Data volume	< 1 Mb per day
Data format	PDF format
Output Data	PDF file
Update rate	Same as MSW_EUL_2D
Latency	1 month
Notes	If possible, results of three different segmentation windows sizes (i.e. for 5, 10 and 20 days, the decision to apply for three window sizes and the definitive sizes will depend on data quality) will be, together with the scatter of the time series internally and in conjunction with previous results, used to assess stability and validity of the Euler Angles.

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 59 of 136

Product identifier	MSW_VAL_2_
Definition	Comparison validation report for Euler angle determinations
Input Data	MSW_EULi2C, MSW_EULi2D, MSW_VAL_2C, MSW_VAL_2D
Data volume	< 1 Mb per day
Data format	PDF format
Output Data	PDF file
Update rate	Each time both, MSW_EUL_2C and MSW_EUL_2D have been released
Latency	1 month
Notes	

Product identifier	MSW_EUL_2C
Definition	3 sets of Euler angles, one set for each satellite
Input Data	MSW_EULi2C, MSW_VAL_2_
Input Time Span	As for MSW_EULi2C
Spatial representation	As for MSW_EULi2C
Time representation	As for MSW_EULi2C
Units	As for MSW_EULi2C
Resolution	As for MSW_EULi2C
Uncertainty	As for MSW_EULi2C
Quality indicator	As for MSW_EULi2C
Data volume	As for MSW_EULi2C
Data format	As for MSW_EULi2C
Output Data	As for MSW_EULi2C
Output time span	As for MSW_EULi2C
Update rate	As for MSW_EULi2C
Latency	As for MSW_EULi2C
Notes	

Product identifier	MSW_EUL_2D
Definition	3 sets of Euler angles, one set for each satellite.
Input Data	MSW_EULi2D, MSW_VAL_2_
Input Time Span	Same as for MSW_EULi2D

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 60 of 136

Product identifier	MSW_EUL_2D
Spatial representation	Same as for MSW_EULi2D
Time representation	Same as for MSW_EULi2D
Units	Same as for MSW_EULi2D
Precision	Same as for MSW_EULi2D
Quality indicator	Same as for MSW_EULi2D
Data volume	Same as for MSW_EULi2D
Data format	Same as for MSW_EULi2D
Output Data	Same as for MSW_EULi2D
Output time span and resolution	Same as for MSW_EULi2D
Update rate	Same as for MSW_EULi2D
Latency	Same as for MSW_EULi2D
Notes	

Product identifier	MSW_EUL_2F
Definition	3 sets of Euler angles, one set for each satellite.
Input Data	MAGx_LR_1B(x=[A,B,C]), AUX_IGR_2_, AUX_COR_2_, AUX_LIT_2_, AUX_DST_2_, AUX_KP_2_, AUX_IMF_2_ ; optional: MMA_SHAi2C, MMA_SHA_2F, MIN_1DMi2_
Input Time Span	At least 4 months
Spatial representation	N/A
Time representation	Time series (snapshots) for the three Euler Angle sets, the time is given in MJD 2000.0 midnight
Units	Degree for Euler Angles, Days. Fraction for leading MJD
Resolution	10^{-6} for the Euler Angles, 0.01 for MJD
Uncertainty	See Notes in this table, otherwise refer to product quality report
Quality indicator	E.g. RMS error or histograms provided in the product quality report.
Data volume	~1 kB
Data format	ASCII table (section 4.3.4)
Output Data	For each satellite A, B, and C: Euler angles, type 1-2-3 preceded by time in MJD
Output time span	Same as input, resolution N/A (adaptive to data)
Update rate	3 months
Latency	2 weeks
Notes	See also Notes in MSW_VAL_2D. If possible, results of three different segmentation windows sizes (i.e. for 5, 10 and 20 days

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 61 of 136

Product identifier	MSW_EUL_2F
	-- the decision to apply for three window sizes and the definitive sizes will depend on data quality) will be, together with the scatter of the time series internally and in conjunction with previous results, used to assess stability and validity of the Euler Angles.

5.5 Core Field Models

5.5.1 Intermediate Level 2 Candidate Products

Product identifier	MCO_SHAi2C
Definition	Spherical harmonic model of the main (core) field and its temporal variation
Input Data	Same as MSW_EULi2C
Input Time Span	Same as MSW_EULi2C
Spatial representation	Spherical Harmonics up to degree 18
Time representation	Snapshot models, based on order 5 splines with 6 months knots spacing
Units	nT
Resolution	1 pT
Uncertainty	Refer to quality report
Quality indicator	Statistics of data misfit provided in validation report
Data volume	~10 kB
Data format	ASCII table (SHC, see section 4.3.1)
Output Data	Gauss coefficients
Output time span	As input time span but with some extrapolations
Update rate	Same as MSW_EULi2C
Latency	Same as MSW_EULi2C
Notes	

Product identifier	MCO_VALi2C
Definition	Intermediate validation report for core field from CI
Input Data	MCO_SHAi2C
Data volume	< 1 MB
Data format	PDF format
Output Data	PDF file
Update rate	Same as for MCO_SHAi2C
Latency	Same as for MCO_SHAi2C
Notes	

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 62 of 136

Product identifier	MCO_SHAi2D
Definition	Spherical harmonic model of the core field and its temporal variation
Input Data	MAGx_LR_1B]), (x=[A,B,C]), AUX_IGR_2_, AUX_COR_2_, AUX_LIT_2_, AUX_DST_2_, AUX_KP_2_, AUX_IMF_2_ ; optional: MMA_SHAi2C, MMA_SHA_2F, MIN_1DMi2_
Input Time Span	Nominal minimum of 1 year up to the full Swarm data span.
Spatial representation	Spherical Harmonics up to degree 18
Time representation	Snapshot models (corresponding to 1/2 year knot separation and order 6 splines)
Units	nT
Resolution	1 pT
Uncertainty	Refer to quality report
Quality indicator	Statistics of data misfit, power spectra etc. provided in validation report
Data volume	~10 kB
Data format	ASCII table (SHC, see section 4.3.1)
Output data	Gauss coefficients
Output time span	Time span same as for input.
Update rate	1 per year
Latency	6 weeks
Notes	Latency may be increased if data quality has to be investigated.

Product identifier	MCO_VALi2D
Definition	Intermediate validation report for dedicated core field
Input Data	MCO_SHAi2C
Data volume	< 1 Mb per day
Data format	PDF format
Output Data	PDF file
Update rate	Same as for MCO_SHAi2D
Latency	Same as for MCO_SHAi2D
Notes	

5.5.2 Final Level 2 Products

Product identifier	MCO_VAL_2C
Definition	Validation report for core field model from CI chain
Input Data	MCO_SHAiC, MCO_VALi2C, AUX_OBS_2_, AUX_IGR_2_

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 63 of 136

Product identifier	MCO_VAL_2C
Data volume	< 1 Mb per day
Data format	PDF format
Output Data	PDF file
Update rate	Same as for MCO_SHA_2C
Latency	1 month
Notes	

Product identifier	MCO_VAL_2D
Definition	Validation report for core field model from dedicated chain
Input Data	MCO_SHAi2D, MCO_VALi2D, AUX_OBS_2_, AUX_IGR_2_
Data volume	< 1 Mb per day
Data format	PDF format
Output Data	PDF file
Update rate	Same as for MCO_SHA_2D
Latency	1 month
Notes	

Product identifier	MCO_VAL_2_
Definition	Comparative validation report for core field models
Input Data	MCO_SHA_2C, MCO_SHA_2D, MCO_VAL_2C, MCO_VAL_2D, AUX_OBS_2_, AUX_IGR_2_
Data volume	< 1 Mb per day
Data format	PDF format
Output Data	PDF file
Update rate	Each time both, MCO_SHA_2C and MCO_SHA_2D have been released
Latency	1 month
Notes	

Product identifier	MCO_SHA_2C
Definition	Spherical harmonic model of the main (core) field and its temporal variation
Input Data	MCO_SHAi2C, MCO_VAL_2_
Input Time Span	Same as for MCO_SHAi2C
Spatial representation	Same as for MCO_SHAi2C
Time representation	Same as for MCO_SHAi2C

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 64 of 136

Product identifier	MCO_SHA_2C
Units	Same as for MCO_SHAi2C
Resolution	Same as for MCO_SHAi2C
Uncertainty	Same as for MCO_SHAi2C
Quality indicator	Same as for MCO_SHAi2C
Data volume	Same as for MCO_SHAi2C
Data format	Same as for MCO_SHAi2C
Output Data	Same as for MCO_SHAi2C
Output time span	Same as for MCO_SHAi2C
Update rate	Same as for MCO_SHAi2C
Latency	Same as for MCO_SHAi2C
Notes	

Product identifier	MCO_SHA_2D
Definition	Spherical harmonic model of the core field
Input Data	MCO_SHAi2D, MCO_VAL_2_
Input Time Span	As for MCO_SHAi2D
Spatial representation	As for MCO_SHAi2D
Time representation	As for MCO_SHAi2D
Units	As for MCO_SHAi2D
Resolution	As for MCO_SHAi2D
Uncertainty	As for MCO_SHAi2D
Quality indicator	As for MCO_SHAi2D
Data volume	As for MCO_SHAi2D
Data format	As for MCO_SHAi2D
Output Data	As for MCO_SHAi2D
Output time span	As for MCO_SHAi2D
Update rate	As for MCO_SHAi2D
Latency	As for MCO_SHAi2D
Notes	The model accuracy strongly depends on the LT offset between satellite C and the A,B satellite pair.

Product identifier	MCO_SHA_2F
Definition	Spherical harmonic model of the main (core) field and its temporal variation
Input Data	MAG _x _LR_1B (x=[A,B,C]),

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 65 of 136

Product identifier	MCO_SHA_2F
	AUX_IGR_2_, AUX_COR_2_, AUX_LIT_2_, AUX_DST_2_, AUX_KP__2_, AUX_IMF_2_ ; optional: MMA_SHAi2C, MMA_SHA_2F, MIN_1DMi2_
Input Time Span	Minimum of 4 months
Spatial representation	Spherical Harmonics up to degree 18
Time representation	Snapshot models
Units	nT
Resolution	1 pT
Uncertainty	Refere to quality report
Quality indicator	Statistics of data misfit, power spectra etc. provided in validation report
Data volume	~10 kB
Data format	ASCII table (SHC, see section 4.3.4)
Output Data	Gauss coefficients
Output time span and resolution	Time span: Minimum 4 months Time resolution: corresponding to 3 month knots separation and order 2 splines
Update rate	First after 4 month, afterwards update is three months (if granted by data quality).
Latency	1 week
Notes	Assumed updated rate is three month

5.6 Lithospheric Field Models

5.6.1 Intermediate Level 2 Candidate Products

Product identifier	MLI_SHAi2C
Definition	Spherical harmonic model of the lithospheric field
Input Data	Same as MSW_EULi2C
Input Time Span	Same as MSW_EULi2C
Spatial representation	Spherical Harmonics from degree 16 to 150
Time representation	Snapshot
Units	nT
Resolution	1 pT
Uncertainty	Refer to product quality report
Quality indicator	Statistics of data misfits provided in validation report
Data volume	~0.5 MB
Data format	ASCII table (SHC, see section 4.3.1)
Output Data	Gauss coefficients
Output time span	N/A (lithospheric field is considered constant over the analysed time range)

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 66 of 136

Product identifier	MLI_SHAi2C
Update rate	Same as MSW_EULi2C
Latency	Same as MSW_EULi2C
Notes	

Product identifier	MLI_VALi2C
Definition	Intermediate validation report for lithospheric field from CI
Input Data	MLI_SHAi2C
Data volume	< 1 MB
Data format	PDF format
Output Data	PDF file
Update rate	Same as for MLI_SHAi2C
Latency	Same as for MLI_SHAi2C
Notes	

Product identifier	MLI_SHAi2D
Definition	Spherical harmonic model of the lithospheric field
Input Data	MAGx_LR_1B, AUX_KP_2_, AUX_DST_2_, AUX_F10_2_, AUX_IMF_2_, AUX_MTI_2_, AUX_LIT_2_, AUX_COR_2_, IBIXTMS_2_, MCO_SHAi2D, MCO_SHA_2F, MMA_SHAi2C, MMA_SHA_2F, MCO_SHAi2C, MIO_SHAi2C, MIO_SHAi2D, MSW_EULi2C, MSW_EULi2D
Input Time Span	One to four years of full Swarm data set.
Spatial representation	Spherical Harmonics from degree 16 to 150
Time representation	Snapshot
Units	nT
Resolution	1 pT
Uncertainty	Refer to product quality report
Quality indicator	Statistics of data misfits provided in validation report
Data volume	~0.5 MB
Data format	ASCII table (SHC, see section 4.3.1)
Output Data	Gauss coefficients
Output time span	N/A (lithospheric field is considered constant over the analysed time range)
Update rate	One model every year
Latency	One month
Notes	

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 67 of 136

Product identifier	MLI_VALi2D
Definition	Intermediate validation report for dedicated lithospheric field
Input Data	MLI_SHAi2D
Data volume	< 100 Mb per report
Data format	PDF format
Output Data	PDF file
Update rate	Same as for MLI_SHAi2D
Latency	Same as for MLI_SHAi2D
Notes	

Product identifier	MLI_SHAi2E
Definition	Map of the lithospheric field from the Revised Spherical Cap Harmonic analysis (R-SCHA) Dedicated Lithospheric Inversion, expressed in terms of high degree Spherical Harmonics
Input Data	MAGx_LR_1B, AUX_KP_2_, AUX_DST_2_, AUX_F10_2_, AUX_IMF_2_, AUX_MTI_2_, AUX_LIT_2_, AUX_COR_2_, IBIXTMS_2_, MCO_SHAi2D, MCO_SHA_2F, MMA_SHAi2C, MMA_SHA_2F, MCO_SHAi2C, MIO_SHAi2C, MIO_SHAi2D, MSW_EULi2C, MSW_EULi2D
Input Time Span	Same as MLI_SHAi2D
Spatial representation	Spherical harmonics from degree 16 to 200
Time representation	Snapshot
Units	nT
Resolution	1 pT
Uncertainty	Refer to product quality report
Quality indicator	Statistics of data misfits provided in validation report
Data volume	~3MB
Data format	ASCII table (SHC, see section 4.3.1)
Output Data	Gauss coefficients
Output time span	N/A (lithospheric field is considered constant over the analysed time range)
Update rate	One model every year
Latency	One month
Notes	The product has the same format as the other lithospheric field models, but at a higher SH degree to be used for mapping purpose only. SH Gauss coefficients are here a mean to store the map, but the product itself is a map. The map should not be computed at altitudes lower than the minimum altitude of Swarm measurements

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 68 of 136

5.6.2 Final Level 2 Products

Product identifier	MLI_VALi2E
Definition	Intermediate validation report for dedicated lithospheric field with revised spherical cap harmonics
Input Data	MLI_SHAi2E
Data volume	< 100 Mb per report
Data format	PDF format
Output Data	PDF file
Update rate	Same as for MLI_SHAi2E
Latency	Same as for MLI_SHAi2E
Notes	

Product identifier	MLI_VAL_2C
Definition	Validation report for lithospheric field model from CI chain
Input Data	MLI_SHAi2C, MLI_VALi2C, AUX_LIT_2_
Data volume	< 1 Mb per day
Data format	PDF format
Output Data	PDF file
Update rate	Same as for MLI_SHA_2C
Latency	1 month
Notes	

Product identifier	MLI_VAL_2D
Definition	Validation report for lithospheric field model from dedicated
Input Data	MLI_SHAi2D, MLI_VALi2D, AUX_LIT_2_
Data volume	< 1 Mb per day
Data format	PDF format
Output Data	PDF file
Update rate	Same as for MLI_SHA_2D
Latency	1 month
Notes	

Product identifier	MLI_VAL_2E
Definition	Validation report for lithospheric field model
Input Data	MLI_SHAi2E, MLI_VALi2E, AUX_LIT_2_

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 69 of 136

Product identifier	MLI_VAL_2E
Data volume	< 1 Mb per day
Data format	PDF format
Output Data	PDF file
Update rate	Same as for MLI_SHA_2E
Latency	1 month
Notes	

Product identifier	MLI_VAL_2_
Definition	Comparison validation report for lithospheric field model
Input Data	MLI_SHA_2C, MLI_SHA_2D, MLI_SHA_2E, MLI_VAL_2C, MLI_VAL_2D, MLI_VAL_2E, AUX_LIT_2_
Data volume	< 1 Mb per day
Data format	PDF format
Output Data	PDF file
Update rate	Each time both, MLI_SHA_2C , MLI_SHA_2D and MLI_SHA_2D have been released
Latency	1 month
Notes	

Product identifier	MLI_SHA_2C
Definition	Spherical harmonic model of the lithospheric field
Input Data	MLI_SHAi2C, MLI_VAL_2_
Input Time Span	Same as MLI_SHAi2C
Spatial representation	Same as MLI_SHAi2C
Time representation	Same as MLI_SHAi2C
Units	Same as MLI_SHAi2C
Resolution	Same as MLI_SHAi2C
Uncertainty	Same as MLI_SHAi2C
Quality indicator	Same as MLI_SHAi2C
Data volume	Same as MLI_SHAi2C
Data format	Same as MLI_SHAi2C
Output Data	Same as MLI_SHAi2C
Output time span	Same as MLI_SHAi2C
Update rate	Same as MLI_SHAi2C
Latency	Same as MLI_SHAi2C

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 70 of 136

Product identifier	MLI_SHA_2C
Notes	

Product identifier	MLI_SHA_2D
Definition	Spherical harmonic model of the lithospheric field
Input Data	MLI_SHAi2D, MLI_VAL_2_
Input Time Span	Same as MLI_SHAi2D
Spatial representation	Same as MLI_SHAi2D
Time representation	Same as MLI_SHAi2D
Units	Same as MLI_SHAi2D
Resolution	Same as MLI_SHAi2D
Uncertainty	Same as MLI_SHAi2D
Quality indicator	Same as MLI_SHAi2D
Data volume	Same as MLI_SHAi2D
Data format	Same as MLI_SHAi2D
Output Data	Same as MLI_SHAi2D
Output time span	Same as MLI_SHAi2D
Update rate	Same as MLI_SHAi2D
Latency	Same as MLI_SHAi2D
Notes	

Product identifier	MLI_SHA_2E
Definition	Final map of the lithospheric field from the Revised Spherical Cap Harmonic analysis (R-SCHA) Dedicated Lithospheric Inversion, expressed in terms of high degree Spherical Harmonics
Input Data	MLI_SHAi2E, MLI_VAL_2_
Input Time Span	Same as MLI_SHAi2E
Spatial representation	Same as MLI_SHAi2E
Time representation	Same as MLI_SHAi2E
Units	Same as MLI_SHAi2E
Resolution	Same as MLI_SHAi2E
Uncertainty	Same as MLI_SHAi2E
Quality indicator	Same as MLI_SHAi2E
Data volume	Same as MLI_SHAi2E
Data format	Same as MLI_SHAi2E

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 71 of 136

Product identifier	MLI_SHA_2E
Output Data	Same as MLI_SHAi2E
Output time span	Same as MLI_SHAi2E
Update rate	Same as MLI_SHAi2E
Latency	Same as MLI_SHAi2E
Notes	Same as MLI_SHAi2E

5.7 Mantle Conductivity

5.7.1 Intermediate Level 2 Products

Product identifier	Q3D_CI_i2_
Definition	Q-matrix of 3-D mantle conductivity model including oceans
Input Data	AUX_OCM_2_, AUX_MCM_2_, MIN_1DMi2_, MIN_3DMi2a, MIN_3DMi2b
Input Time Span	N/A
Spatial representation	Spherical harmonic (SH) expansion in dipolar coordinates.
Time representation	Four time harmonics (at periods of 24, 12, 8 and 6 hours)
Units	dimensionless
Resolution	10 ⁻⁵
Uncertainty	N/A
Quality indicator	N/A
Data volume	500 Mb
Data format	<p>The files are in ASCII format with LF control character used for newline (unix style), and arbitrary number of spaces used as variable separator in a line. General structure of the files is as follows:</p> <pre># Arbitrary number of comment lines starting with # sign N_periods N_max M_max <block_1> <block_2> <block_3> ... <block_N_periods></pre> <p>where N_periods is a number of periods N_max is a maximum degree of spherical harmonic expansion (SHE) of the external field M_max is a maximum order of SHE of the external field</p> <p>Each <block_k> block consists of: T_k # Comment line with degrees and orders of SHE of internal</p>

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 72 of 136

Product identifier	Q3D_CI_i2_
	<p>field</p> <p>Then matrix(array) of dimension $[M_{\max}*(M_{\max} + 2) + (N_{\max} - M_{\max})*(2*M_{\max}+1)] \times [N_{\max}*(N_{\max}+2)]$ follows which columns are:</p> <p><Columns 1 - 2>: degree and order of SHE of external field <Columns 3 - $N_{\max}*(N_{\max}+2)+1$>: elements of Q-matrix</p> <p>where T_k is the k-th period in days.</p>
Output Data	Transfer function connecting induced and inducing SH expansion coefficients
Output time span	N/A
Update rate	First version 1 year after launch updated when required
Latency	N/A
Notes	

Product identifier	MIN_1DMi2_
Definition	1-D model of mantle conductivity
Input Data	MMA_SHAi2C, AUX_OCM_2_, AUX_MCM_2
Input Time Span	2 years
Spatial representation	Conductivity distribution with respect to depth (1-D layered model of the Earth)
Time representation	N/A
Units	Kilometers (for layer radii), Siemens per meter (for conductivities)
Resolution	N/A
Uncertainty	Refer to product quality report
Quality indicator	N/A
Data volume	A few Kb
Data format	ASCII listing (section 4.3.4.2)
Output Data	Conductivities within the layer, and radii of the top of the layer
Output time span	N/A
Update rate	First version after 2 years, update every year
Latency	1 months
Notes	This 1-D model is foreseen as the output of the 1-D frequency domain inversion

Product identifier	MI1_VALi2_
Definition	Intermediate validation report for 1-D model of mantle conductivity
Input Data	MIN_1DMi2_

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 73 of 136

Product identifier	MI1_VALi2_
Data volume	< 1 Mb per day
Data format	PDF format
Output Data	PDF file
Update rate	Same as for MIN_1DMi2_
Latency	Same as for MIN_1DMi2_
Notes	

Product identifier	MIN_3DMi2a
Definition	3-D model of mantle conductivity (frequency domain)
Input Data	MMA_SHAi2C, AUX_OCM_2_, AUX_MCM_2
Input Time Span	> 2 years
Spatial representation	3-D grid, laterally regular, radially irregular
Time representation	N/A
Units	Kilometers (for layer radii), Siemens per meter (for conductivities)
Resolution	N/A
Uncertainty	Refer to product quality report
Quality indicator	N/A
Data volume	A few Mb
Data format	ASCII listing (section 4.3.4.2)
Output Data	Conductivities in cells of a 3-D grid
Output time span	N/A
Update rate	First version after 2 years, updates every year
Latency	4 months
Notes	This 3-D model is foreseen as the output of the 3-D frequency domain inversion

Product identifier	MIN_3DMi2b
Definition	3-D model of mantle conductivity (time domain)
Input Data	MMA_SHAi2C, AUX_OCM_2_, AUX_MCM_2
Input Time Span	> 2 years
Spatial representation	3-D grid, laterally regular, radially irregular
Time representation	N/A
Units	Kilometers (for layer radii), Siemens per meter (for conductivities)
Resolution	N/A
Uncertainty	Refer to product quality report

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 74 of 136

Product identifier	MIN_3DMi2b
Quality indicator	N/A
Data volume	A few Mb
Data format	ASCII listing (section 4.3.4.2)
Output Data	Conductivities in cells of a 3-D grid
Output time span	N/A
Update rate	First version after 2 years, updates every year
Latency	4 months
Notes	This 3-D model is foreseen as the output of the 3-D time domain inversion

Product identifier	MI3_VALi2_
Definition	Intermediate validation report for 3-D model of mantle conductivity candidate a and b
Input Data	MIN_3DMi2a, MIN_3DMi2b
Data volume	< 1 Mb per day
Data format	PDF format
Output Data	PDF file
Update rate	Same as for MIN_3DMi2a
Latency	Same as for MIN_3DMi2a
Notes	

Product identifier	MCR_1DMi2_
Definition	Global 1D C-responses
Input Data	MMA_SHAi2C, AUX_OCM_2_, AUX_MCM_2
Input Time Span	2 year
Spatial representation	N/A
Time representation	N/A
Units	km
Resolution	N/A
Uncertainty	For periods between 4-15 days the relative error should be less than 30 %
Quality indicator	Uncertainties and squared coherencies coming from signal processing
Data volume	A few Kb
Data format	ASCII listing (section 4.3.4.2)
Output Data	C-responses (real and imaginary parts), their uncertainties and squared coherencies on a set of periods
Output time span and	N/A

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 75 of 136

Product identifier	MCR_1DMi2_
resolution	
Update rate	Same as MIN_1DMi2_
Latency	Same as MIN_1DMi2_
Notes	These responses are foreseen as the by-product of the 1-D frequency domain inversion

Product identifier	MC1_VALi2_
Definition	Intermediate validation report for 1-D maps of C-responses
Input Data	MCR_1DMi2_
Data volume	< 1 Mb per day
Data format	PDF format
Output Data	PDF file
Update rate	Same as MCR_1DMi2_
Latency	Same as MCR_1DMi2_
Notes	

Product identifier	MCR_3DMi2_
Definition	3-D maps of C-responses
Input Data	MMA_SHAi2C, AUX_OCM_2_, AUX_MCM_2_
Input Time Span	4 years
Spatial representation	2-D (lon, lat) grid
Time representation	N/A
Units	km
Resolution	N/A
Uncertainty	For periods between 4-15 days the relative error should be less than 30 %
Quality indicator	Uncertainties and squared coherencies coming from signal processing
Data volume	A few Mb
Data format	ASCII listing (section 4.3.4.2)
Output Data	C-responses (real and imaginary parts), their uncertainties and squared coherences on 2-D (lon, lat) grid on a set of periods
Output time span and resolution	N/A
Update rate	Same as MIN_3DMi2a
Latency	Same as MIN_3DMi2a
Notes	These responses are foreseen as the by-product of the 3-D frequency domain inversion

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 76 of 136

Product identifier	MC3_VALi2_
Definition	Intermediate validation report for 3-D maps of C-responses
Input Data	MCR_3DMi2_
Data volume	< 1 Mb per day
Data format	PDF format
Output Data	PDF file
Update rate	Same as MCR_3DMi2_
Latency	Same as MCR_3DMi2_
Notes	

5.7.2 Final Level 2 Products

Product identifier	MI1_VAL_2_
Definition	Validation report for 1D mantle conductivity
Input Data	MIN_1DMi2_, MI1_VALi2_
Data volume	< 1 Mb per day
Data format	PDF format
Output Data	PDF file
Update rate	As for MIN_1DM_2_
Latency	1 month
Notes	

Product identifier	MI3_VAL_2_
Definition	Validation report for 3D mantle conductivity, candidate product a and b and intercomparison between a and b
Input Data	MIN_3DMi2a, MIN_3DMi2b, MI3_VALi2_
Data volume	< 1 Mb per day
Data format	PDF format
Output Data	PDF file
Update rate	Each time when both, MIN_3DM_2a and MIN_3DM_2b are released
Latency	1 month
Notes	

Product identifier	MC1_VAL_2_
Definition	Validation report for 1D C-response
Input Data	MCR_1DMi2_, MC1_VALi2_

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 77 of 136

Product identifier	MC1_VAL_2_
Data volume	< 1 Mb per day
Data format	PDF format
Output Data	PDF file
Update rate	As for MCR_1DM_2_
Latency	1 month
Notes	

Product identifier	MC3_VAL_2_
Definition	Validation report for 3D C-response
Input Data	MCR_3DMi2_, MC3_VALi2
Data volume	< 1 Mb per day
Data format	PDF format
Output Data	PDF file
Update rate	As for MCR_3DM_2_
Latency	1 month
Notes	

Product identifier	MIN_1DM_2_
Definition	1-D model of mantle conductivity
Input Data	MIN_1DMi2_, MC1_VAL_2_
Input Time Span	As for MIN_1DMi2_
Spatial representation	As for MIN_1DMi2_
Time representation	As for MIN_1DMi2_
Units	As for MIN_1DMi2_
Resolution	As for MIN_1DMi2_
Uncertainty	As for MIN_1DMi2_
Quality indicator	As for MIN_1DMi2_
Data volume	As for MIN_1DMi2_
Data format	As for MIN_1DMi2_
Output Data	As for MIN_1DMi2_
Output time span	As for MIN_1DMi2_
Update rate	As for MIN_1DMi2_
Latency	As for MIN_1DMi2_
Notes	As for MIN_1DMi2_

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 78 of 136

Product identifier	MIN_3DM_2a
Definition	3-D model of mantle conductivity (frequency domain)
Input Data	MIN_3DMi2a, MC3_VAL_2_
Input Time Span	As for MIN_3DMi2a
Spatial representation	As for MIN_3DMi2a
Time representation	As for MIN_3DMi2a
Units	As for MIN_3DMi2a
Resolution	As for MIN_3DMi2a
Uncertainty	As for MIN_3DMi2a
Quality indicator	As for MIN_3DMi2a
Data volume	As for MIN_3DMi2a
Data format	As for MIN_3DMi2a
Output Data	As for MIN_3DMi2a
Output time span	As for MIN_3DMi2a
Update rate	As for MIN_3DMi2a
Latency	As for MIN_3DMi2a
Notes	As for MIN_3DMi2a

Product identifier	MIN_3DM_2b
Definition	3-D model of mantle conductivity (frequency domain)
Input Data	MIN_3DMi2b, MC3_VAL_2_
Input Time Span	As for MIN_3DMi2b
Spatial representation	As for MIN_3DMi2b
Time representation	As for MIN_3DMi2b
Units	As for MIN_3DMi2b
Resolution	As for MIN_3DMi2b
Uncertainty	As for MIN_1DMi2b
Quality indicator	As for MIN_3DMi2b
Data volume	As for MIN_3DMi2b
Data format	As for MIN_3DMi2b
Output Data	As for MIN_3DMi2b
Output time span	As for MIN_3DMi2b
Update rate	As for MIN_3DMi2b
Latency	As for MIN_3DMi2b

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 79 of 136

Product identifier	MIN_3DM_2b
Notes	As for MIN_3DMi2b

Product identifier	MCR_1DM_2_
Definition	Global 1D C-responses
Input Data	MCR_1DMi2_, MC1_VAL_2_
Input Time Span	As for MCR_1DMi2_
Spatial representation	As for MCR_1DMi2_
Time representation	As for MCR_1DMi2_
Units	As for MCR_1DMi2_
Resolution	As for MIN_1DMi2_
Uncertainty	As for MIN_1DMi2_
Quality indicator	As for MCR_1DMi2_
Data volume	As for MCR_1DMi2_
Data format	As for MCR_1DMi2_
Output Data	As for MCR_1DMi2_
Output time span and resolution	As for MCR_1DMi2_
Update rate	As for MCR_1DMi2_
Latency	As for MCR_1DMi2_
Notes	

Product identifier	MCR_3DM_2_
Definition	2-D maps of C-responses
Input Data	MCR_3DMi2_, MC3_VAL_2_
Input Time Span	As for MCR_3DMi2_
Spatial representation	As for MCR_3DMi2_
Time representation	As for MCR_3DMi2_
Units	As for MCR_3DMi2_
Resolution	As for MCR_3DMi2_
Uncertainty	As for MCR_3DMi2_
Quality indicator	As for MCR_3DMi2_
Data volume	As for MCR_3DMi2_
Data format	As for MCR_3DMi2_
Output Data	As for MCR_3DMi2_

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 80 of 136

Product identifier	MCR_3DM_2_
Output time span	As for MCR_3DMi2_
Update rate	As for MCR_3DMi2_
Latency	As for MCR_3DMi2_
Notes	

5.8 External Field and Current Systems

5.8.1 Intermediate Level 2 Candidate Products

Product identifier	MMA_SHAi2C																				
Definition	Spherical harmonic representation of the large scale magnetospheric field and of its induced counterpart																				
Input Data	Same as MSW_EULi2C																				
Input Time Span	Same as MSW_EULi2C																				
Spatial representation	Spherical Harmonics of degree and order at least 1 for the external field and of degree and order at least 5 for its Earth induced counterpart																				
Time representation	Time series																				
Units	nT																				
Resolution	≤ 1 pT																				
Uncertainty	Refer to product quality report																				
Quality indicator	Statistics of data misfit provided in the validation report																				
Data volume	~2 MB/year																				
Data format	<div>CDF variables</div> <div>Various temporal resolutions may be employed for various external and internal coefficients, hence a number of CDF variable groups are used to store external (named "...qs_N") respectively internal (named "...gh_N") coefficients. Note: the temporal resolutions for the various groups of external and internal coefficients are usually not identical.</div> <table><tr><th>Name</th><th>Type</th><th>Dim</th><th>Unit</th><th>Contents</th></tr><tr><td>t_qs_1</td><td>CDF_EPOCH</td><td>1</td><td>ms</td><td>Time instants of external Gauss coefficients q (cosine) and s (sine)</td></tr><tr><td>qs_1</td><td>CDF_DOUBLE</td><td>1</td><td>nT</td><td>External Gauss coefficients q (cosine) and s (sine) in dipole frame corresponding to time instants t_qs_1</td></tr><tr><td>dqs_1</td><td>CDF_DOUBLE</td><td>1</td><td>nT</td><td>Formal error estimate for qs_1</td></tr></table>	Name	Type	Dim	Unit	Contents	t_qs_1	CDF_EPOCH	1	ms	Time instants of external Gauss coefficients q (cosine) and s (sine)	qs_1	CDF_DOUBLE	1	nT	External Gauss coefficients q (cosine) and s (sine) in dipole frame corresponding to time instants t_qs_1	dqs_1	CDF_DOUBLE	1	nT	Formal error estimate for qs_1
Name	Type	Dim	Unit	Contents																	
t_qs_1	CDF_EPOCH	1	ms	Time instants of external Gauss coefficients q (cosine) and s (sine)																	
qs_1	CDF_DOUBLE	1	nT	External Gauss coefficients q (cosine) and s (sine) in dipole frame corresponding to time instants t_qs_1																	
dqs_1	CDF_DOUBLE	1	nT	Formal error estimate for qs_1																	

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 81 of 136

Product identifier	MMA_SHAi2C					
	nm_qs_1	CDF_INT2	1	-	First column: vector of spherical harmonic degrees of the coefficients qs_1. Second column: vector of spherical harmonic orders. Nonnegative values denote coefficients q (cosine) while negative values denote coefficients s (sine)	
	t_qs_2	CDF_EPOCH	1	ms	Time instants of external Gauss coefficients q (cosine) and s (sine)	
	qs_2	CDF_DOUBLE	2	nT	External Gauss coefficients q (cosine) and s (sine) in dipole frame corresponding to time instants t_qs_2	
	dqs_2	CDF_DOUBLE	2	nT	Formal error estimate for qs_2	
	nm_qs_2	CDF_INT2	2	-	First column: vector of spherical harmonic degrees of the coefficients qs_2. Second column: vector of spherical harmonic orders. Nonnegative values denote coefficients q (cosine) while negative values denote coefficients s (sine)	
	t_gh_1	CDF_EPOCH	1	ms	Time instants of induced Gauss coefficients g (cosine) and h (sine)	
	gh_1	CDF_DOUBLE	1	nT	Internal induced Gauss coefficients g (cosine) and h (sine) in dipole frame	

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 82 of 136

Product identifier	MMA_SHAi2C					
	dgh_1	CDF_DOUBLE	1	nT	Formal error estimate for gh_1	
	nm_gh_1	CDF_INT2	1	-	First column: vector of spherical harmonic degrees of the coefficients gh_1. Second column: vector of spherical harmonic orders. Nonnegative values denote coefficients g (cosine) while negative values denote coefficients h (sine)	
	t_gh_2	CDF_EPOCH	1	ms	Time instants of induced Gauss coefficients g (cosine) and h (sine)	
	gh_2	CDF_DOUBLE	2	nT	Internal induced Gauss coefficients g (cosine) and h (sine) in dipole frame	
	dgh_2	CDF_DOUBLE	2	nT	Formal error estimate for gh_2	
	nm_gh_2	CDF_INT2	2	-	First column: vector of spherical harmonic degrees of the coefficients gh_2. Second column: vector of spherical harmonic orders. Nonnegative values denote coefficients g (cosine) while negative values denote coefficients h (sine)	
	t_qual	CDF_EPOCH	1	ms	Time instants of quality information (rms, n_data, and q_flag).	

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 83 of 136

Product identifier	MMA_SHAi2C					
	rms	CDF_DOUBLE	2	nT	Root-mean-square difference between models and input data (after processing to subtract non-magnetospheric sources) in dipole frame, for the time instants indicated by t_qual First column: RMS difference in radial direction. Second column: RMS difference in theta direction. Third column: RMS difference in phi direction.	
	n_data	CDF_UINT2	2	-	Number of data used at each time-instant from each satellite. First column: Number of data from SWARM A. Second column: Number of data from SWARM B. Third column: Number of data from SWARM C.	
Output Data	Time series of external and induced SH coefficients in dipole coordinate frame; root-mean-square differences between (processed) input data and models; number of data from each satellite used for each model; quality flag.					
Output time span	Time span as input					
Update rate	Same as MSW_EULi2C					
Latency	Same as MSW_EULi2C					
Notes						

Product identifier	MMA_VALi2C
Definition	Intermediate validation report for ionospheric fields from CI
Input Data	MMA_SHAi2C

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 84 of 136

Product identifier	MMA_VALi2C
Data volume	< 1 MB
Data format	PDF format
Output Data	PDF file
Update rate	Same as MMA_SHAi2C
Latency	Same as MMA_SHAi2C
Notes	

Product identifier	MIO_SHAi2C
Definition	Spherical harmonic representation of the daily geomagnetic variations at mid and low latitudes (Sq and EEJ) and of its induced counterpart
Input Data	Same as MSW_EULi2C
Input Time Span	Same as MSW_EULi2C
Spatial representation	Spherical Harmonics up to degree 60 and order 12 in dipole coordinates
Time representation	Fourier Series, seasonal and daily periodicity
Units	nT
Resolution	1 pT
Uncertainty	Refer to product quality report
Quality indicator	Statistics of data misfit provided in the validation report
Data volume	~130 kB
Data format	ASCII listing (section 4.3.4.3)
Output Data	Coefficients of SH model in dipole coordinates, with seasonal and diurnal periodicity
Output time span	N/A
Update rate	Same as MSW_EULi2C
Latency	Same as MSW_EULi2C
Notes	

Product identifier	MIO_VALi2C
Definition	Intermediate validation report for ionospheric fields from CI
Input Data	MIO_SHAi2C
Data volume	< 1 MB
Data format	PDF format
Output Data	PDF file
Update rate	Same as MIO_SHAi2C
Latency	Same as MIO_SHAi2C

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 85 of 136

Product identifier	MIO_VALi2C
Notes	

Product identifier	MIO_SHAi2D
Definition	Spherical harmonic representation of the daily geomagnetic variations at mid and low latitudes (Sq and EEJ) and its induced counterpart
Input Data	MAGx_LR_1B, AUX_KP__2_, AUX_DST_2_, AUX_F10_2_, AUX_IMF_2_, AUX_COR_2_, AUX_OBS_2_, AUX_LIT_2_, AUX_IGR_2_, MCO_SHA_2F, MCO_SHAi2D, MLI_SHAi2D, MCO_SHAi2C, MLI_SHAi2C, MMA_SHAi2C, MMA_SHA_2F, Q3D_CI_i2_
Input Time Span	3 months to 1 year, to be confirmed and aligned to update rate
Spatial representation	Spherical Harmonics up to degree 60 and order 12 in dipole coordinates
Time representation	Fourier Series, seasonal and daily periodicity
Units	nT
Resolution	1 fT
Uncertainty	Refer to product quality report
Quality indicator	Statistics of data misfits provided in the validation report
Data volume	~ 3.5 Mo
Data format	ASCII listing (section 4.3.4.3)
Output Data	Coefficients of SH model in dipole coordinates, with seasonal and diurnal periodicity
Output time span	N/A
Update rate	First after 6 months, 1 year, and update every year.
Latency	1.5 month
Notes	

5.8.2 Final Level 2 Products

Product identifier	MIO_VALi2D
Definition	Intermediate validation report for ionospheric fields from dedicated chain
Input Data	MIO_SHAi2D
Data volume	< 1 Mb per day
Data format	PDF format
Output Data	PDF file
Update rate	Same as MIO_SHAi2D
Latency	Same as MIO_SHAi2D
Notes	

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 86 of 136

Product identifier	MMA_VAL_2C
Definition	Validation report for magnetospheric field model from CI chain
Input Data	MMA_SHAi2C, MMA_SHA_2F, MMA_VALi2C
Data volume	< 1 Mb per day
Data format	PDF format
Output Data	PDF file
Update rate	As for MMA_SHA_2C
Latency	1 month
Notes	

Product identifier	MMA_SHA_2C
Definition	Spherical harmonic representation of the large scale magnetospheric field and of its induced counterpart
Input Data	MMA_SHAi2C, MMA_VAL_2_
Input Time Span	As for MMA_SHAi2C
Spatial representation	As for MMA_SHAi2C
Time representation	As for MMA_SHAi2C
Units	As for MMA_SHAi2C
Resolution	As for MMA_SHAi2C
Uncertainty	As for MMA_SHAi2C
Quality indicator	As for MMA_SHAi2C
Data volume	As for MMA_SHAi2C
Data format	As for MMA_SHAi2C
Output Data	As for MMA_SHAi2C
Output time span	As for MMA_SHAi2C
Update rate	As for MMA_SHAi2C
Latency	As for MMA_SHAi2C
Notes	

Product identifier	MMA_SHA_2F
Definition	Spherical harmonic representation of the large scale magnetospheric field and its induced counterpart
Input Data	MAGx_LR_1B, AUX_IGR_2_, AUX_COR_2_, MCO_SHA_2F, MCO_SHA_2C, MCO_SHA_2D, AUX_LIT_2_, MLI_SHA_2C, MIO_SHA_2C, AUX_F10_2_, AUX_IMF_2F, AUX_DST_2_, AUX_KP_2_, AUX_OBS_2_
Input Time Span	Full Swarm data set covering at least 30 days

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 87 of 136

Product identifier	MMA_SHA_2F				
Spatial representation	Degree 1 spherical Harmonics for the external and internally induced fields				
Time representation	Snapshot values 1.5 hours apart.				
Units	See variable 'Units' in 'Data format', below.				
Resolution	See variable 'Type' in 'Data format', below.				
Uncertainty	Overall uncertainty will include contributions from uncertainties in the Input Data, which are not calculated here. Estimates of the uncertainty resulting from the modeling process after the Input Data has been processed can be obtained from the 'rms' output variable.				
Quality indicator	Root-mean-square difference between model and (processed) input data; number of data used per model; quality flag.				
Data volume	~5 MB/year				
Data format	CDF Variables				
	Name	Type	Dim	Unit	Contents
	t_qs	CDF_EPOCH	1	ms	Time instants (CDFEPOCH) of external Gauss coefficients q (cosine) and s (sine)
	qs_geo	CDF_DOUBLE	2	nT	External Gauss coefficients q (cosine) and s (sine) in Geographic frame
	qs_sm	CDF_DOUBLE	2	nT	External Gauss coefficients q (cosine) and s (sine) in Solar Magnetic frame
	nm_qs	CDF_INT2	2	-	First column: vector of spherical harmonic degrees of the coefficients qs_geo and qs_sm. Nonnegative values denote coefficients q (cosine) while negative values denote coefficients s (sine) Second column: vector of spherical harmonic orders
	t_gh	CDF_EPOCH	1	ms	Time instants (CDFEPOCH) of induced Gauss coefficients g (cosine) and h (sine)
	gh_geo	CDF_DOUBLE	2	nT	Internal induced Gauss coefficients g (cosine) and h (sine) in Geographic frame
	gh_sm	CDF_DOUBLE	2	nT	Internal induced Gauss coefficients g (cosine) and h (sine) in Solar Magnetic frame

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 88 of 136

Product identifier	MMA_SHA_2F						
		nm_gh	CDF_INT2	2	-	First column: vector of spherical harmonic degrees of the coefficients gh_geo and gh_sm. Nonnegative values denote coefficients g (cosine) while negative values denote coefficients h (sine) Second column: vector of spherical harmonic orders	
		t_qual	CDF_EPOCH	1	ms	Time instants (CDFEPOCH) of quality information (rms, n_data, and q_flag).	
		rms	CDF_DOUBLE	2	nT	Root-mean-square difference between models and input data (after processing to subtract non-magnetospheric sources) in geographic frame. First column: RMS difference in radial direction. Second column: RMS difference in theta direction. Third column: RMS difference in phi direction.	
		n_data	CDF_UINT2	2	-	Number of data used at each time-instant from each satellite. First column: Number of data from SWARM A. Second column: Number of data from SWARM B. Third column: Number of data from SWARM C.	

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 89 of 136

Product identifier	MMA_SHA_2F																
		q_flag	CDF_UINT1	1	-	<p>Product quality flag. Value of zero indicates good quality / no issues. The meaning of individual bits are described below:</p> <table><thead><tr><th>Bit</th><th>Set if</th></tr></thead><tbody><tr><td>1</td><td>Input time-series is shorter than 1-year filter used to separate internal and external coefficients. This is unavoidable at the start of the mission.</td></tr><tr><td>2</td><td>Internal/external separation filter has at least one bad/missing datum. This is not necessarily serious (check n_data, above and bits 3 and 4, below).</td></tr><tr><td>3</td><td>total n_data for this model is < 90% of the expected maximum available.</td></tr><tr><td>4</td><td>Internal/external separation filter has at least one bad/missing datum amongst the most recent (five) where it is most sensitive.</td></tr></tbody></table> <p>Example: decimal ‘9’ means bits ‘1’ and ‘4’ set.</p>		Bit	Set if	1	Input time-series is shorter than 1-year filter used to separate internal and external coefficients. This is unavoidable at the start of the mission.	2	Internal/external separation filter has at least one bad/missing datum. This is not necessarily serious (check n_data, above and bits 3 and 4, below).	3	total n_data for this model is < 90% of the expected maximum available.	4	Internal/external separation filter has at least one bad/missing datum amongst the most recent (five) where it is most sensitive.
Bit	Set if																
1	Input time-series is shorter than 1-year filter used to separate internal and external coefficients. This is unavoidable at the start of the mission.																
2	Internal/external separation filter has at least one bad/missing datum. This is not necessarily serious (check n_data, above and bits 3 and 4, below).																
3	total n_data for this model is < 90% of the expected maximum available.																
4	Internal/external separation filter has at least one bad/missing datum amongst the most recent (five) where it is most sensitive.																
Output Data	Time series of external and induced SH coefficients in Solar Magnetic and Geographic coordinate frames; root-mean-square differences between (processed) input data and models; number of data from each satellite used for each model; quality flag.																
Output time span	1 day																
Update rate	Daily																
Latency	< 1 day																
Notes																	

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 90 of 136

Product identifier	MIO_VAL_2C
Definition	Validation report for ionospheric field model from CI chain
Input Data	MIO_SHAi2C, MIO_VALi2C
Data volume	< 1 Mb per day
Data format	PDF format
Output Data	PDF file
Update rate	As for MIO_SHA_2C
Latency	1 month
Notes	

Product identifier	MIO_VAL_2D
Definition	Validation report for ionospheric field model from dedicated chain
Input Data	MIO_SHAi2D, MIO_VALi2D
Data volume	< 1 Mb per day
Data format	PDF format
Output Data	PDF file
Update rate	As for MIO_SHA_2D
Latency	1 month
Notes	

Product identifier	MIO_VAL_2_
Definition	Comparison validation report for ionospheric field model
Input Data	MIO_SHA_2C, MIO_SHA_2D, MIO_VAL_2C, MIO_VAL_2D
Data volume	< 1 Mb per day
Data format	PDF format
Output Data	PDF file
Update rate	Each time when both, MIO_SHA_2C and MIO_SHA_2D are released.
Latency	1 month
Notes	

Product identifier	MIO_SHA_2C
Definition	Spherical harmonic representation of the daily geomagnetic variations at mid and low latitudes (Sq and EEJ)
Input Data	MIO_SHAi2C, MIO_VAL_2_
Input Time Span	Same as MIO_SHAi2C

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 91 of 136

Product identifier	MIO_SHA_2C
Spatial representation	Same as MIO_SHAi2C
Time representation	Same as MIO_SHAi2C
Units	Same as MIO_SHAi2C
Resolution	Same as MIO_SHAi2C
Uncertainty	Same as MIO_SHAi2C
Quality indicator	Same as MIO_SHAi2C
Data volume	Same as MIO_SHAi2C
Data format	Same as MIO_SHAi2C
Output Data	Same as MIO_SHAi2C
Output time span	Same as MIO_SHAi2C
Update rate	Same as MIO_SHAi2C
Latency	Same as MIO_SHAi2C
Notes	

Product identifier	MIO_SHA_2D
Definition	Spherical harmonic representation of the daily geomagnetic variations at mid and low latitudes (Sq and EEJ)
Input Data	MIO_SHAi2D, MIO_VAL_2_
Input Time Span	Same as MIO_SHAi2D
Spatial representation	Same as MIO_SHAi2D
Time representation	Same as MIO_SHAi2D
Units	Same as MIO_SHAi2D
Resolution	Same as MIO_SHAi2D
Uncertainty	Same as MIO_SHAi2D
Quality indicator	Same as MIO_SHAi2D
Data volume	Same as MIO_SHAi2D
Data format	Same as MIO_SHAi2D
Output Data	Same as MIO_SHAi2D
Output time span	Same as MIO_SHAi2D

Product identifier	IBIxTMS_2F
Definition	Ionospheric bubble index
Input Data	MAGx_LR_1B, EFIx_PL_1B, Satellite positions, Time stamps (UTC) AUX_IGR_2F, AUX_COR_2F, AUX_LIT_2F, AUX_PMF_2F, AUX_F10_2F, AUX_DST_2F, AUX_IMF_2F, AUX_SWV_2F, AUX_PSM_2F, AUX_PGM_2F

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 92 of 136

Product identifier	IBIxTMS_2F																																		
Input Time Span	3 days																																		
Spatial representation	One index per data point (characterising whether the magnetic observation is affected by bubble or not.)																																		
Time representation	1s time series																																		
Units	N/A																																		
Resolution	N/A																																		
Uncertainty	N/A																																		
Quality indicator	Flags_Bubble: 0 Quiet 1 Confirmed plasma bubble 2 Unconfirmed plasma bubble 4 Large peak in unfiltered magnetic field residuals 8 Time gap 16 Too many peaks in filtered magnetic field residuals 32 Outside equatorial orbit segment or invalid latitude/local time Flags_B, Flags_F and Flags_q provided in [AD-5].																																		
Data volume	~4 MB/day/satellite																																		
Data format	Swarm L2 CAT-2 IBI Product CDF Output Specification Variables <table border="1"> <thead> <tr> <th>Variable Name</th><th>Description</th><th>Type</th><th>Units</th></tr> </thead> <tbody> <tr> <td>Timestamp</td><td>Time stamp in UTC</td><td>CDF_EPOCH</td><td>ms</td></tr> <tr> <td>Latitude</td><td>Geographic latitude</td><td>CDF_DOUBLE</td><td>degree</td></tr> <tr> <td>Longitude</td><td>Geographic longitude</td><td>CDF_DOUBLE</td><td>degree</td></tr> <tr> <td>Radius</td><td>Geographic radius</td><td>CDF_DOUBLE</td><td>m</td></tr> <tr> <td>Bubble_Index</td><td> Plasma Bubble Index 0 Quiet 1 Bubble -1 Not analyzed </td><td>CDF_INT2</td><td>No unit</td></tr> <tr> <td>Bubble_Probability</td><td> Detection probability of the plasma bubble (in steps of 0.2; 0-not probable, 1-very probable) </td><td>CDF_DOUBLE</td><td>No unit</td></tr> <tr> <td>Flags_Bubble</td><td>Flags related to the plasma bubble index</td><td>CDF_UINT1</td><td>No unit</td></tr> </tbody> </table>			Variable Name	Description	Type	Units	Timestamp	Time stamp in UTC	CDF_EPOCH	ms	Latitude	Geographic latitude	CDF_DOUBLE	degree	Longitude	Geographic longitude	CDF_DOUBLE	degree	Radius	Geographic radius	CDF_DOUBLE	m	Bubble_Index	Plasma Bubble Index 0 Quiet 1 Bubble -1 Not analyzed	CDF_INT2	No unit	Bubble_Probability	Detection probability of the plasma bubble (in steps of 0.2; 0-not probable, 1-very probable)	CDF_DOUBLE	No unit	Flags_Bubble	Flags related to the plasma bubble index	CDF_UINT1	No unit
Variable Name	Description	Type	Units																																
Timestamp	Time stamp in UTC	CDF_EPOCH	ms																																
Latitude	Geographic latitude	CDF_DOUBLE	degree																																
Longitude	Geographic longitude	CDF_DOUBLE	degree																																
Radius	Geographic radius	CDF_DOUBLE	m																																
Bubble_Index	Plasma Bubble Index 0 Quiet 1 Bubble -1 Not analyzed	CDF_INT2	No unit																																
Bubble_Probability	Detection probability of the plasma bubble (in steps of 0.2; 0-not probable, 1-very probable)	CDF_DOUBLE	No unit																																
Flags_Bubble	Flags related to the plasma bubble index	CDF_UINT1	No unit																																

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 93 of 136

Product identifier	IBIxTMS_2F				
	Flags_F	Flags_F passed through from MAGx_L1_B	CDF_UINT1	No unit	
	Flags_B	Flags_B passed through from MAGx_L1_B	CDF_UINT1	No unit	
	Flags_q	Flags_q passed through from MAGx_L1_B	CDF_UINT1	No unit	
Output Data	time stamps, positions, Bubble Index, Bubble probability, flags				
Output time span	1 day				
Latency	6 min				
Update rate	1 per day				
Notes					

Product identifier	TECxTMS_2F																			
Definition	Time series of the ionospheric total electron content																			
Input Data	GPS RINEX observation and navigation files (GPSX_RO_1B) Swarm satellite ephemeris (MODX_SC_1B) GPS and Swarm satellite ephemeris (AUX_GPSEPH) GPS transmitter biases(AUX_DCB_2F) Leap seconds (AUX_USLEAP)																			
Input Time Span	3 days																			
Spatial representation	Line representation of GPS –Swarm link																			
Time representation	1-s time series for TEC and 1 day for DCB																			
Units	TECU (10 ¹⁶ electrons/m ²)																			
Resolution	1E-8 TECU																			
Uncertainty	2 TECU																			
Quality indicator	Relative_STEC_RMS (RMS deviation between code and carrier phases) and DCB_Error																			
Data volume	~4 MB / day / satellite																			
Data format	<div>Variables</div> <table><tr><th>Variable Name</th><th>Description</th><th>Type</th><th>Unit</th></tr><tr><td>Timestamp</td><td>Time stamp in UTC</td><td>CDF_EPOCH</td><td>ms</td></tr><tr><td>Latitude</td><td>Geographic latitude</td><td>CDF_DOUBLE</td><td>degree</td></tr><tr><td>Longitude</td><td>Geographic longitude</td><td>CDF_DOUBLE</td><td>degree</td></tr></table>				Variable Name	Description	Type	Unit	Timestamp	Time stamp in UTC	CDF_EPOCH	ms	Latitude	Geographic latitude	CDF_DOUBLE	degree	Longitude	Geographic longitude	CDF_DOUBLE	degree
Variable Name	Description	Type	Unit																	
Timestamp	Time stamp in UTC	CDF_EPOCH	ms																	
Latitude	Geographic latitude	CDF_DOUBLE	degree																	
Longitude	Geographic longitude	CDF_DOUBLE	degree																	

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 94 of 136

Product identifier	TECxTMS_2F				
	Radius	Geographic radius	CDF_DOUBLE	km	
	GPS_Position	X-,Y-,Z-coordinates (WGS84) of the GPS satellite	CDF_DOUBLE	km	
	LEO_Position	X-,Y-,Z-coordinates (WGS84) of the LEO satellite	CDF_DOUBLE	m	
	PRN	GPS satellite PRN	CDF_UINT2	No Unit	
	L1	GPS L1 carrier phase observation	CDF_DOUBLE	m	
	L2	GPS L2 carrier phase observation	CDF_DOUBLE	m	
	P1	GPS P1 code phase observation	CDF_DOUBLE	m	
	P2	GPS P2 code phase observation	CDF_DOUBLE	m	
	S1	GPS signal-to-noise ratio or raw signal strength on L1	CDF_DOUBLE	No Unit	
	S2	GPS signal-to-noise ratio or raw signal strength on L2	CDF_DOUBLE	No Unit	
	Absolute_STEC	Absolute slant TEC	CDF_DOUBLE	TECU	
	Absolute-VTEC	Absolute vertical TEC	CDF_DOUBLE	TECU	
	Elevation-Angle	Elevation angle	CDF_DOUBLE	degree	
	Relative_STEC	Relative slant TEC	CDF_DOUBLE	TECU	
	Relative_STEC_RMS	Root mean square error of relative slant TEC	CDF_DOUBLE	TECU	
	DCB	GPS receiver differential code bias	CDF_DOUBLE	TECU	
	DCB_Error	Error of the GPS receiver differential code bias	CDF_DOUBLE	TECU	
Output Data	time stamps, positions, PRN, L1, L2, P1, P2, S1, S2, TEC, RMS, DCB, DCB_Error				
Output time span	1 day				
Latency	6 min				
Update rate	1 per day				
Notes	The cadence of the TECxTMS_2F data has changed from 10-s (0.1 Hz) to 1-s (1 Hz) at 06:34:00 (HH:MM:SS) on 15 July 2014.				

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 95 of 136

Product identifier	FAC_TMS_2F								
Definition	Time series of field aligned current density and radial currents density along the orbit. Field-aligned current density is derived by the multiplication of the radial current density with the inclination angle of the geomagnetic field. The field-aligned current density can only be calculated at high latitudes, where the magnetic field is well inclined, i.e. $I > 30^\circ$ (except near the magnetic equator). At lower latitudes, the times series has no values (NaN). The radial current density can be provided along the whole orbit, except for latitudes $\theta > 86^\circ$. Scale size > 150 km.								
Input Data	MAGA_LR_1B, MAGC_LR_1B, Time stamps (UTC) AUX_IGR_2F, AUX_COR_2F, AUX_LIT_2F, AUX_PMF_2F, AUX_F10_2F, AUX_DST_2F, AUX_IMF_2F, AUX_SWV_2F, AUX_PSM_2F, AUX_PGM_2F								
Input Time Span	3 days								
Spatial representation	Current density estimates along entire orbits at positions between SwA and SwC								
Time representation	Time series of current density, $\Delta t = 1$ sec								
Units	Current density: $\mu\text{A}/\text{m}^2$								
Resolution	Current density: $1\text{E-}6 \mu\text{A}/\text{m}^2$								
Uncertainty	50 nA/m ² for periods 10s to 90min on top of constant bias of $< 200\text{nA}/\text{m}^2$, for latitudes below 80° , gradually degrading between 80° to 86° , no values beyond 86°								
Quality indicator	<p>Flags:</p> <p>There are 10 digits reserved in this flag: If the satellite is inside the region where FAC and/or IRC can in principle be calculated than digits 9 and 10 are both 0.</p> <p>If the satellite was outside this region than digit 9 or 10 is 1. (In this case, FAC and/or IRC value is NaN). Digit 9 and 10 can never be 1 for the same measurement.</p> <p>Digit 1 to 8 report about different problems that occur during the processing. All of them provide a fall back solutions. They can have values N=1-4, indicating the number of affected quad points.</p> <p>About NaNs: The FAC and/or IRC value is always NAN, when digit 9 or 10 is 1.</p> <p>When digit 9 and 10 are both 0, but the FAC/IRC value is NaN, the reason for NaN is unknown.</p> <p>The provided digits 1-8 do not inform about possible reasons for NaN. They provide information on the expected quality of the results. Digits 1-8 can be different to 0 irrespective of the values of digits 9 and 10.</p> <table><tr><th>Digit-Nr.</th><th>Value</th><th>Meaning</th></tr><tr><td>1</td><td>0/N</td><td>interpolated data (data gap)</td></tr></table>			Digit-Nr.	Value	Meaning	1	0/N	interpolated data (data gap)
Digit-Nr.	Value	Meaning							
1	0/N	interpolated data (data gap)							

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 96 of 136

Product identifier	FAC_TMS_2F			
		2	0/N	Data is in filter tuning range due to larger data gap before and/or after the gap
		3	0/N	no EST data were available because no AUX_DST_2F was available for magnetospheric field calculation; instead default value is used
		4	0/N	no IST data were available because no AUX_DST_2F was available for magnetospheric field calculation; instead default value is used
		5	0/N	no Aux data AUX_F10_2F available for magnetospheric field calculation; instead default value is used
		6	0/N	no Aux data (AUX_IMF_2F) available for magnetospheric field calculation; instead default value is used
		7	0/N	no <i>Em</i> data (merging electric field) was available because either AUX_IMF_2F or AUX_SWV_2F were not available for magnetospheric field calculation; instead default value is used.
		8	0/N	No magnetospheric field coefficients (Aux_PMF_2F or Aux_PSM_2F or Aux_PGM_2F) available; magnetospheric field is set to 0; resulting FACs are slightly less reliable.
		9	0/1	IRC=NaN and FAC=NaN because latitude $\theta > 86^\circ$ near geogr. pole
		10	0/1	FAC=NaN because inclination $I < 30^\circ$ near magn. equator
	<p>Flags_B, Flags_F and Flags_q are handed through from Level 1b processing [AD-5]. For each current estimate the flag values of the measurement points involved were added. Accordingly, the digits of these flags have values of N=0-4, corresponding to the number of (measurements involved in the FAC/IRC estimate (quad points) that have been affected.</p>			

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 97 of 136

Product identifier	FAC_TMS_2F																																																							
Data volume	5 MB per day																																																							
Data format	<table><tr><td>Variable Name</td><td>Data Type</td><td>Descriptions</td><td>Units</td></tr><tr><td>Timestamp</td><td>CDF_EPOCH</td><td>Time, UTC</td><td>milli-seconds</td></tr><tr><td>Latitude</td><td>CDF_DOUBLE</td><td>Position in ITRF, Latitude</td><td>degrees</td></tr><tr><td>Longitude</td><td>CDF_DOUBLE</td><td>Position in ITRF, Longitude</td><td>degrees</td></tr><tr><td>Radius</td><td>CDF_DOUBLE</td><td>Position in ITRF, Radius</td><td>m</td></tr><tr><td>IRC</td><td>CDF_DOUBLE</td><td>Ionospheric radial current (IRC)</td><td>μA/m²</td></tr><tr><td>IRC_Error</td><td>CDF_DOUBLE</td><td>uncertainty of IRC</td><td>μA/m²</td></tr><tr><td>FAC</td><td>CDF_DOUBLE</td><td>Field-aligned current (FAC)</td><td>μA/m²</td></tr><tr><td>FAC_Error</td><td>CDF_DOUBLE</td><td>uncertainty of FAC</td><td>μA/m²</td></tr><tr><td>Flags</td><td>CDF_UINT4</td><td>Flags characterizing the product quality (processing flags)</td><td>-</td></tr><tr><td>Flags_F</td><td>CDF_UINT4</td><td>Flags_F passed through from L1b and accumulated for quad points</td><td>-</td></tr><tr><td>Flags_B</td><td>CDF_UINT4</td><td>Flags_B passed through from L1b and accumulated for quad points</td><td>-</td></tr><tr><td>Flags_q</td><td>CDF_UINT4</td><td>Flags_q passed through from L1b and accumulated for quad points</td><td>-</td></tr></table>				Variable Name	Data Type	Descriptions	Units	Timestamp	CDF_EPOCH	Time, UTC	milli-seconds	Latitude	CDF_DOUBLE	Position in ITRF, Latitude	degrees	Longitude	CDF_DOUBLE	Position in ITRF, Longitude	degrees	Radius	CDF_DOUBLE	Position in ITRF, Radius	m	IRC	CDF_DOUBLE	Ionospheric radial current (IRC)	μA/m ²	IRC_Error	CDF_DOUBLE	uncertainty of IRC	μA/m ²	FAC	CDF_DOUBLE	Field-aligned current (FAC)	μA/m ²	FAC_Error	CDF_DOUBLE	uncertainty of FAC	μA/m ²	Flags	CDF_UINT4	Flags characterizing the product quality (processing flags)	-	Flags_F	CDF_UINT4	Flags_F passed through from L1b and accumulated for quad points	-	Flags_B	CDF_UINT4	Flags_B passed through from L1b and accumulated for quad points	-	Flags_q	CDF_UINT4	Flags_q passed through from L1b and accumulated for quad points	-
	Variable Name	Data Type	Descriptions	Units																																																				
	Timestamp	CDF_EPOCH	Time, UTC	milli-seconds																																																				
	Latitude	CDF_DOUBLE	Position in ITRF, Latitude	degrees																																																				
	Longitude	CDF_DOUBLE	Position in ITRF, Longitude	degrees																																																				
	Radius	CDF_DOUBLE	Position in ITRF, Radius	m																																																				
	IRC	CDF_DOUBLE	Ionospheric radial current (IRC)	μA/m ²																																																				
	IRC_Error	CDF_DOUBLE	uncertainty of IRC	μA/m ²																																																				
	FAC	CDF_DOUBLE	Field-aligned current (FAC)	μA/m ²																																																				
	FAC_Error	CDF_DOUBLE	uncertainty of FAC	μA/m ²																																																				
	Flags	CDF_UINT4	Flags characterizing the product quality (processing flags)	-																																																				
	Flags_F	CDF_UINT4	Flags_F passed through from L1b and accumulated for quad points	-																																																				
	Flags_B	CDF_UINT4	Flags_B passed through from L1b and accumulated for quad points	-																																																				
Flags_q	CDF_UINT4	Flags_q passed through from L1b and accumulated for quad points	-																																																					
Output Data	time stamps, positions, radial current density, field-aligned current density, quality flags																																																							
Output time span	1day																																																							
Update rate	1 per day																																																							
Latency	10 min																																																							
Notes																																																								

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 98 of 136

Product identifier	FACxTMS_2F
Definition	Time series of field-aligned current density and radial currents density along the orbit from single satellite measurements. Field-aligned current density is derived by the magnetic field in the MFA frame. No FACs will be estimated for cases with $V_x < 1.5$ km/s (near the magnetic equator). The FAC values at these current positions will be set to <i>NaN</i> . The radial current density, i.e. FAC multiplied by the inclination of the magnetic field, can be provided along the whole orbit. Scale size >7.5 km.
Input Data	MAGx_LR_1B, Satellite positions, Time stamps (UTC) AUX_IGR_2F, AUX_COR_2F, AUX_LIT_2F, AUX_PMF_2F, AUX_F10_2F, AUX_DST_2F, AUX_IMF_2F, AUX_SWV_2F, AUX_PSM_2F, AUX_PGM_2F
Input Time Span	3 days
Spatial representation	Current density estimates along entire orbits at positions of SwA, SwB, and SwC.
Time representation	Time series of current density, $\Delta t=1$ sec
Units	Current density: $\mu\text{A}/\text{m}^2$
Resolution	Current density: $1\text{E-}6 \mu\text{A}/\text{m}^2$
Uncertainty	less than FAC_TMS_2F, $70 \text{ nA}/\text{m}^2$ on top of constant bias of $<200 \text{ nA}/\text{m}^2$, for latitudes below 80° , gradually degrading between 80° to 86° , no values beyond 86°
Quality indicator	Flags same as for FAC_TMS_2F but N=1-2
Data volume	5MB per day, per satellite
Data format	Same as for FAC_TMS_2F
Output Data	time stamps, positions, radial current density, field-aligned current density, quality flags
Output time span	1day
Latency	10 min
Update rate	1 per day
Notes	

5.9 Precise Orbit Determination Products

Product identifier	EEFxTMS_2F
Definition	Dayside equatorial electric field
Input Data	MAGx_LR_1B, AUX_DST_2F, AUX_KP_2F, AUX_F10_2F, AUX_IGR_2F, AUX_COR_2F, AUX_LIT_2F, AUX_PMF_2F, AUX_PSM_2F, AUX_PGM_2F, AUX_IRZ_2F
Input Time Span	Every dayside equator crossing ± 20 minutes
Spatial representation	One longitude/latitude pair (on the magnetic equator) for each output value

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 99 of 136

Product identifier	EEFxTMS_2F																														
Time representation	Single values at time of dayside equator crossing																														
Units	V/m																														
Resolution	0.1 mV/m																														
Uncertainty	0.1 mV/m																														
Quality indicator	Relative error between modeled and observed current profile																														
Data volume	< 2 kB																														
Data format	<div> <div>CDF</div> <table> <tr> <th>Variable Name</th><th>Type</th><th>Description</th><th>Units</th></tr> <tr> <td>timestamp</td><td>CDF_EPOCH</td><td>milliseconds elapsed since 00:00:00 January 1, 2000 UTC</td><td>Milliseconds</td></tr> <tr> <td>longitude</td><td>CDF_DOUBLE</td><td>Geographic longitude of satellite crossing of the magnetic equator</td><td>Degrees</td></tr> <tr> <td>latitude</td><td>CDF_DOUBLE</td><td>Geographic latitude of satellite crossing of the magnetic equator</td><td>Degrees</td></tr> <tr> <td>EEF</td><td>CDF_DOUBLE</td><td>Estimate of the equatorial electric field</td><td>V/m</td></tr> <tr> <td>RelErr</td><td>CDF_DOUBLE</td><td>Quality indicator of EEF estimate; relative error between modeled and observed current profile</td><td>N/A</td></tr> <tr> <td>flags</td><td>CDF_UINT2</td><td> Flags describing data gaps and satellite identification <div> Bit Description 1 EEF estimate came from Swarm satellite A data 2 EEF estimate came from Swarm satellite B data 3 EEF estimate came from Swarm satellite C data 4 Processor failed due to a too large data gap in the Level 1b input data </div> </td><td>N/A</td></tr> </table> </div>			Variable Name	Type	Description	Units	timestamp	CDF_EPOCH	milliseconds elapsed since 00:00:00 January 1, 2000 UTC	Milliseconds	longitude	CDF_DOUBLE	Geographic longitude of satellite crossing of the magnetic equator	Degrees	latitude	CDF_DOUBLE	Geographic latitude of satellite crossing of the magnetic equator	Degrees	EEF	CDF_DOUBLE	Estimate of the equatorial electric field	V/m	RelErr	CDF_DOUBLE	Quality indicator of EEF estimate; relative error between modeled and observed current profile	N/A	flags	CDF_UINT2	Flags describing data gaps and satellite identification <div> Bit Description 1 EEF estimate came from Swarm satellite A data 2 EEF estimate came from Swarm satellite B data 3 EEF estimate came from Swarm satellite C data 4 Processor failed due to a too large data gap in the Level 1b input data </div>	N/A
Variable Name	Type	Description	Units																												
timestamp	CDF_EPOCH	milliseconds elapsed since 00:00:00 January 1, 2000 UTC	Milliseconds																												
longitude	CDF_DOUBLE	Geographic longitude of satellite crossing of the magnetic equator	Degrees																												
latitude	CDF_DOUBLE	Geographic latitude of satellite crossing of the magnetic equator	Degrees																												
EEF	CDF_DOUBLE	Estimate of the equatorial electric field	V/m																												
RelErr	CDF_DOUBLE	Quality indicator of EEF estimate; relative error between modeled and observed current profile	N/A																												
flags	CDF_UINT2	Flags describing data gaps and satellite identification <div> Bit Description 1 EEF estimate came from Swarm satellite A data 2 EEF estimate came from Swarm satellite B data 3 EEF estimate came from Swarm satellite C data 4 Processor failed due to a too large data gap in the Level 1b input data </div>	N/A																												
Output Data	Longitude, latitude, time, EEF value, quality-indicator, flags																														
Output time span	Continuous for entire mission. One value for each day-side equator crossing (90 minute sampling for day-night local time orbits, 45 minutes for dawn-dusk orbits)																														

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 100 of 136

Product identifier	EEFxTMS_2F
Update rate	One output file per day
Latency	20 minutes
Notes	

5.9.1 Final Level 2 Products

Product identifier	SP3xCOM_2_
Definition	Time series of dynamic position and velocity of the center of mass of each satellite in the ITRF (Earth-fixed) frame
Input Data	GPSA_RO_1B, GPSB_RO_1B, GPSC_RO_1B STRAATT_1B, STRBATT_1B, STRCATT_1B MODA_SC_1B, MODB_SC_1B, MODC_SC_1B External data from IGS, IERS, CODE
Input Time Span	30 hr (daily batches with overlap)
Spatial representation	N/A
Time representation	GPS time (seconds – s), time step = 10 s
Units	km for position, dm/s for velocity
Resolution	1 ps for time, mm for position, 0.1 $\mu\text{m/s}$ for velocity
Uncertainty	10 cm 3D for position
Quality indicator	Validation report SP3xVAL_2_
Data volume	< 2 Megabyte (MB) per satellite per day
Data format	SP3c (section 4.3.2)
Output Data	SP3c file
Output time span	24 hr
Update rate	Daily
Latency	21 days
Notes	Central 24 hr of input time span will be selected for SP3 product Quality report will be provided as separate Level 2 product

Product identifier	SP3xKIN_2_
Definition	Time series of kinematic position of the center of mass of each satellite in the ITRF (Earth-fixed) frame
Input Data	GPSA_RO_1B, GPSB_RO_1B, GPSC_RO_1B STRAATT_1B, STRBATT_1B, STRCATT_1B MODA_SC_1B, MODB_SC_1B, MODC_SC_1B External data from IGS, IERS, CODE
Input Time Span	30 hr (daily batches with overlap)

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 101 of 136

Product identifier	SP3xKIN_2_
Spatial representation	N/A
Time representation	GPS time (seconds – s), observation epochs
Units	km for position, dm/s for velocity
Resolution	1 ps for time, mm for position, 0.1 $\mu\text{m/s}$ for velocity
Uncertainty	10 cm 3D for position
Quality indicator	Validation report SP3xVAL_2_
Data volume	< 15 Megabyte (MB) per satellite per day
Data format	SP3c
Output Data	SP3c file
Output time span	24 hr
Update rate	Daily
Latency	21 days
Notes	Central 24 hr of input time span will be selected for SP3 product Quality report will be provided as separate Level 2 product

Product identifier	SP3xVAL_2_
Definition	Validation report for precise orbit solutions SP3xCOM_2_ and SP3xKIN_2_
Input Data	SP3xCOM_2_ and SP3xKIN_2_ ILRS Swarm tracking data Diagnostic and statistical output from orbit determination process
Input Time Span	30 hr
Data volume	< 20 Mb per satellite per day
Data format	PDF format
Output Data	PDF file
Output time span	24 hr
Update rate	1 day
Latency	21 per day
Notes	30 hr time input time span includes overlaps between consecutive orbit solutions

Product identifier	ACCxPOD_2_
Definition	Time series of non-gravitational accelerations obtained by POD
Input Data	SP3xCOM_2_, GPSx_RO_1B, STRxATT_1B, ACCx_PR_1B External data from CODE
Input Time Span	30 hr (daily batches with overlap)

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 102 of 136

Product identifier	ACCxPOD_2_				
Spatial representation	N/A				
Time representation	UTC (seconds – s), time step = 30 sec				
Units	m/s ²				
Resolution	64 bit double precision floating point number format				
Uncertainty	10 ⁻⁷ m/s ² variance for along-track and cross-track directions				
Quality indicator	Validation report DNSxVAL_2_				
Data volume	< 10 Kb per satellite per day				
Data format	CDF				
	Field name	Type	Dimension	Unit	Contents
	time	CDF_EPOCH	1	ms	Observation time
	acc_pod	CDF_REAL8	3	m/s ²	Estimated non-gravitational accelerations (X,Y,Z)
	validity_flag	CDF_INT1	1	-	Flag: 0 = nominal data, 1 = anomalous data
Output Data	CDF file with time series of accelerations				
Output time span	24 hr				
Update rate	1 day				
Latency	21 days				
Notes	As of version 0201 data is computed from GPS data using a Kalman filter approach. The reduced-dynamic orbit is used as a priori reference orbit. The level 1B accelerometer files are only used for spacecraft mass and CoG information				

5.10 Magnetic Forcing of the Upper Atmosphere

5.10.1 Intermediate Level 2 Products

Product identifier	ACCxDISi2_
Definition	List of disturbances in accelerometer data
Input Data	ACCx_PR_1B, ACCx_FMi2_
Input time span	Variable
Spatial representation	N/A
Time representation	UTC
Units	m/s ²
Resolution	64 bit double precision floating point format
Quality indicator	Validation report ACCxVAL_2_
Data volume	~10 kB / day

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 103 of 136

Product identifier	ACCxDISi2_				
Data format	CDF				
	Field name	Type	Dimension	Unit	Contents
	time	CDF_EPOCH	1	ms	Disturbance time in UTC
	type	CDF_REAL8	1	N/A	Type of disturbance
	duration	CDF_REAL8	1	s	Duration of disturbance
	mag_lin	CDF_REAL8	3	m/s ²	Magnitude of disturbance in linear accelerations
	mag_ang	CDF_REAL8	3	m/s ²	Magnitude of disturbance in angular accelerations
Output data	CDF file with list of disturbances in accelerometer data				
Output time span	Variable				
Update rate	Every 3 months				
Latency	1 month				
Notes	All accelerations are provided in the CRF (x-direction is roughly along-track, y-direction is roughly cross-track, z-direction is roughly nadir)				

Product identifier	ACCx_FMi2_				
Definition	Time series of non-gravitational acceleration from force models				
Input data	MODx_SC_1B, STRxATT_1B, AUX_KP__2F , AUX_F10_2F				
Input time span	24 hr				
Spatial representation	N/A				
Time representation	UTC (seconds – s), time step = 10 sec				
Units	m/s ²				
Resolution	64 bit double precision floating point format				
Quality indicator	Validation report ACCxVAL_2_				
Data volume	1.5 MB / day				
Data format	CDF				
	Field name	Type	Dimension	Unit	Contents
	time	CDF_EPOCH	1	ms	Epoch of observation
	a_total	CDF_REAL8	3	m/s ²	Total non-gravitational acceleration

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 104 of 136

Product identifier	ACCx_FMi2_				
	a_aero	CDF_REAL8	3	m/s ²	Aerodynamic acceleration
	a_solar	CDF_REAL8	3	m/s ²	Solar radiation pressure acceleration
	a_albedo	CDF_REAL8	3	m/s ²	Earth albedo radiation pressure acceleration
	a_infrared	CDF_REAL8	3	m/s ²	Earth infrared radiation pressure acceleration
Output data	CDF file with non-gravitational acceleration from force models				
Output time span	24 hr				
Update rate	daily				
Latency	21 days				
Notes	All accelerations are provided in the CRF (x-direction is roughly along-track, y-direction is roughly cross-track, z-direction is roughly nadir)				

5.10.2 Final Level 2 Products

Product identifier	ACCxCAL_2_				
Definition	Time series of corrected and calibrated acceleration, including all corrections and calibration parameters				
Input Data	ACCx_PR_1B, ACCxPOD_2_, ACCxDISi2_				
Input Time Span	24 hours				
Spatial representation	Three-dimensional time series along satellite orbit				
Time representation	UTC				
Units	m/s ² for accelerations, unitless for scale factors and flags				
Resolution	64 bit double precision floating point format				
Quality indicator	Validation report ACCxVAL_2_ Global attribute "DAILY_QUALITY_INDEX" of Type CDF_REAL, which ranges from 1.0 (good data quality) to 5.0 (bad data quality)				
Data volume	15 MB per day				
Data format	CDF				
	Field name	Type	Dimension	Unit	Contents
	time	CDF_EPOCH	1	ms	Epoch of observation (UTC)

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 105 of 136

Product identifier	ACCxCAL_2_					
		a_cal	CDF_REAL8	3	m/s ²	Calibrated linear acceleration (X,Y,Z)
		a_stp	CDF_REAL8	3	m/s ²	Step correction for linear accelerations
		a_tmp	CDF_REAL8	3	m/s ²	Temperature correction for linear accelerations
		a_gg	CDF_REAL8	3	m/s ²	Gravity gradient correction for linear accelerations
		a_aa	CDF_REAL8	3	m/s ²	Angular acceleration correction for linear accelerations
		a_ca	CDF_REAL8	3	m/s ²	Centrifugal acceleration correction for linear accelerations
		s	CDF_REAL8	3	N/A	Scale factor (time series) for linear accelerations
		b	CDF_REAL8	3	m/s ²	Bias for linear accelerations
		spike_index	CDF_REAL8	3	m/s ²	Vector indicating per axis the size of artificial spikes in linear accelerations
		flag_cor	CDF_UINT4	1	N/A	Flag indicating which corrections are applied
		flag_val	CDF_UINT4	1	N/A	Flag indicating if data is valid
		flag_thr	CDF_UINT4	1	N/A	Flag indicating if thruster activations
Output Data	CDF file with corrected and calibrated accelerations from the accelerometer, all					

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 106 of 136

Product identifier	ACCxCAL_2_
	corrections and calibration parameters, and flags; sampling rate is 1 Hz (accelerations are at original measurement epochs)
Output time span	1 day
Update rate	3 months
Latency	1 month
Notes	<p>All accelerations are provided in the CRF (x-direction is roughly along-track, y-direction is roughly cross-track, z-direction is roughly nadir)</p> <p>Calibration was performed against non-gravitational accelerations from POD that are contained in product ACCxPOD_2_</p> <p>Early versions of this product will contain only along-track acceleration data</p>

Product identifier	ACCx_AE_2_				
Definition	Time series of calibrated accelerometer data, pre-processed to represent external non-gravitational forces and aerodynamic accelerations				
Input Data	ACCx_PR_1B, STRxATT_1B, SP3xCOM_2_, ACCxCAL_2_, ACCxPOD_2_, AUX_F10_2_, AUX_KP__2_ External data from IERS				
Input Time Span	24 hr				
Spatial representation	Time-series along satellite track, altitude (m), latitude (deg), longitude (deg) and local solar time (hours) available based on MODX_SC_1B				
Time representation	UTC (seconds – s), nominally with 10 s time step				
Units	nm/s ² for accelerations, s for time, m for altitude, degrees for latitude, longitude, hours for local solar time				
Resolution	64 bit double precision floating point number format				
Uncertainty	N/A				
Quality indicator	Validation report TDWxVAL_2_				
Data volume	< 10 Mbyte per satellite per day				
Data format	CDF				
	Field name	Type	Dimension	Unit	Contents
	time	CDF_EPOCH	1	ms	Observation time
	acc_total_obs	CDF_REAL8	1	m/s ²	Non-gravitational acceleration from accelerometer and GPS receiver (X ≈ along-track)

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 107 of 136

Product identifier	ACCx_AE_2_						
		acc_aero_obs	CDF_REAL8	1	m/s ²	Aerodynamic accelerations ($X \approx$ along-track)	
Output Data	CDF file with time series						
Output time span	24 hr						
Update rate	3 months						
Latency	1 month						
Notes	The applied accelerometer bias and scale factors are available in the metadata.						

Product identifier	ACCxVAL_2_						
Definition	Validation report for measured, modeled and POD accelerations ACCxCAL_2_, ACCxFMi2_ and ACCxPOD_2_						
Input Data	ACCxDISi2_, ACCxCAL_2_, ACCxPOD_2_, ACCxFMi2_						
Input Time Span	Variable						
Data volume	1 – 10 MB / day						
Output Data	PDF file						
Output time span	Variable						
Update rate	3 months						
Latency	1 month						

Product identifier	DNSxWND_2_						
Definition	Thermospheric density at the satellite location estimated from calibrated non-gravitational accelerations (ACCx_AE_2_) that are based on precise orbit determination and accelerometer data						
Input Data	STRxATT_1B, ACCx_PR_1B, ACCx_AE_2_, SP3_COM_2_, AUX_IER_2_, AUX_AER_2_, AUX_F10_2_, AUX_KP_2_ External data from IERS						
Input Time Span	24 hr						
Spatial representation	Time-series along satellite track, altitude (m), latitude (deg), longitude (deg) and local solar time (hours) available based on MODX_SC_1B						
Time representation	UTC (seconds – s), nominally with 10 s time step						
Units	kg/m ³ for density, m/s for wind speed						
Resolution	64 bit double precision floating point number format						
Uncertainty	30% of variance from models for neutral density						
Quality indicator	Validation report TDWxVAL_2_						

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 108 of 136

Product identifier	DNSxWND_2_				
Data volume	< 15 Mbyte per satellite per day				
Data format	CDF				
	Field name	Type	Dimension	Unit	Contents
	time	CDF_EPOCH	1	ms	Observation time
	altitude	CDF_REAL8	1	m	Observation altitude
	latitude	CDF_REAL8	1	deg	Observation geodetic latitude
	longitude	CDF_REAL8	1	deg	Observation geodetic longitude
	local_solar_time	CDF_REAL8	1	hours	Observation local solar time
	density	CDF_REAL8	1	kg/m³	Thermospheric neutral density
Output Data	CDF file with time series				
Output time span	24 hr				
Update rate	3 months				
Latency	1 month				
Notes	None				

Product identifier	DNSxPOD_2_
Definition	Thermospheric density at the satellite location along with auxiliary parameters (altitude, latitude, longitude and local solar time). Derived from non-gravitational accelerations based on precise orbit determination data only (ACCxPOD_2_).
Input Data	MODx_SC_1B, STRxATT_1B, ACCx_PR_1B, ACCx_FMi2_, GPSx_RO_1B, ACCxPOD_2_
Input Time Span	24 hr
Spatial representation	Time-series along satellite track, altitude (m), latitude (deg), longitude (deg) and local solar time (hours) available based on MODx_SC_1B
Time representation	UTC (seconds – s), nominally with 30 s time step, as well as orbital averages
Units	kg/m ³ for density
Resolution	64 bit double precision floating point number format

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 109 of 136

Product identifier	DNSxPOD_2_				
Uncertainty	30% of variance from models for neutral density				
Quality indicator	Validation report DNSxVAL_2_				
Data volume	< 160 Kbyte per satellite per day				
Data format	CDF				
	Field name	Type	Dimension	Unit	Contents
	time	CDF_EPOCH	1	ms	Time of observation
	density	CDF_REAL8	1	kg/m³	Density derived from GPS accelerations
	density_orbitmean	CDF_REAL8	1	kg/m³	Orbit-average of density derived from GPS accelerations
	validity_flag	CDF_INT1	1	-	Flag: 0 = nominal data, 1 = anomalous data
	altitude	CDF_REAL8	1	m	Altitude
	latitude	CDF_REAL8	1	deg	Geodetic latitude
	longitude	CDF_REAL8	1	deg	Geodetic longitude
Output Data	CDF file with time series				
Output time span	24 hr				
Update rate	1 day				
Latency	21 days				
Notes	<p>The density data is derived from the ACCxPOD non-gravitational acceleration component along the spacecraft X-axis.</p> <p>The following processing steps have been performed:</p> <ul style="list-style-type: none">- Modelled radiation pressure accelerations have been subtracted from the full non-gravitational accelerations, to arrive at aerodynamic accelerations. Because the Kalman filter approach results in a smoothed representation of true accelerations, the radiation pressure model output has been smoothed as well, in order to avoid density jump artefacts at eclipse transitions.- The resulting aerodynamic accelerations are converted into densities, using an aerodynamic model based on a panelised representation of the satellite. The gas-surface interaction is based on diffuse reflection, and an energy accommodation coefficient of 0.93 is used.				

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 110 of 136

Product identifier	DNSxPOD_2_
	<ul style="list-style-type: none">- The densities are multiplied by a factor of 1.32, to compensate for the observed difference in scale between the panelised aerodynamic model, and an aerodynamic model based on a more accurate representation of the geometry of the Swarm satellites. The more accurate model will be implemented in a future updated version of the data.- The density_orbitmean field contains the mean density, taken over one orbital period, for each time step. The orbital period in seconds is provided as metadata in the CDF file. <p>At high altitude and low solar activity, the errors inherent in the radiation pressure model and acceleration determination using GPS data can become significant compared to the magnitude of the acceleration signal. This can result in large density errors and even negative densities. Users are advised to use the orbit mean densities in those conditions.</p>

Product identifier	TDWxVAL_2_
Definition	Validation report for thermospheric densities and winds DNSxWND_2_
Input Data	DNSxWND_2_, ACCx_AE_2_, ACCxCAL_2_, ACCxPOD_2_
Input Time Span	24 hr
Data volume	< 20 Mb per satellite per day
Data format	PDF format
Output Data	PDF file
Output time span	24 hr
Update rate	3 months
Latency	1 month
Notes	Associated with ACCxCAL_2_, ACCxPOD_2_, ACCx_AE_2_ and DNSxWND_2_

Product identifier	DNSxVAL_2_
Definition	Validation report showing plots of GPS-derived accelerations ACCxPOD_2_, as well as for thermosphere density and orbit-average thermosphere density, derived from these accelerations. Flagged data are included and marked in the plots.
Input Data	DNSxPOD_2_, ACCxPOD_2_
Input Time Span	24 hr
Data volume	< 20 Mb per satellite per day
Data format	PDF format
Output Data	PDF file
Output time span	24 hr
Update rate	1 day
Latency	21 days

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 111 of 136

Product identifier	DNSxVAL_2_
Notes	Associated with DNSxPOD_2, ACCxPOD_2_

5.11 Quick Look reports for L1b products

Product identifier	MAG_QL_2_
Definition	Quick-look report for L1b magnetic data
Input Data	MAGx_LR_1B, AUX_IGR_2_, AUX_COR_2F, AUX_COR_2_
Input Time Span	24 hr
Spatial representation	N/A
Time representation	N/A
Units	N/A
Precision	N/A
Quality indicator	N/A
Data volume	< 1 Mb/day
Data format	PDF format
Output Data	PDF file
Output time span and resolution	daily and mission-to-date
Update rate	daily
Latency	target is < 1 day on normal week days
Notes	May be developed as an online tool for operation at MPPF

5.12 Auxiliary data

Product identifier	EFI_QL_2_
Definition	Quick-look report for L1b plasma data
Input Data	EFIx_PL_1B
Input Time Span	24 hr
Spatial representation	N/A
Time representation	N/A
Units	N/A
Precision	N/A
Quality indicator	N/A
Data volume	<1 Mb/day
Data format	PDF format
Output Data	PDF file

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 112 of 136

Product identifier	EFI_QL_2_
Output time span and resolution	daily and mission-to-date
Update rate	daily
Latency	target is < 1 day on normal week days
Notes	May be developed as an online tool for operation at MPPF

Product identifier	AUX_KP_2_
Definition	Kp – Planetary three-hourly index of geomagnetic activity recorded at 13 mid-latitude ground-based observatories and corresponding ap series
Application	MSW_EULi2_C, MSW_EULi2_D, MSW_EUL_2F, MCO_SHAi2C, MCO_SHAi2D, MCO_SHA_2F, MLI_SHAi2C, MLI_SHAi2D, MIO_SHAi2C, MIO_SHAi2D, DNSxWND_2_, WP16000
Spatial representation	1 value describing the global state
Time representation	Time series in UT (3-hours average: 0-3h, 3-6h, 6-9h, 9-12h, 12-15h, 15-18h, 18-21h, 21-24h)
Units	Kp: Unitless, ap: nT
Resolution	Kp indices range in 28 steps from 0 (quiet) to 9 (greatly disturbed) with fractional parts expressed in thirds of a unit. A Kp-value equal to 27, for example, means 2 and 2/3 or 3-; a Kp-value equal to 30 means 3 and 0/3 or 3 exactly; and a Kp-value equal to 33 means 3 and 1/3 or 3+.
Uncertainty	N/A
Quality indicator	Not provided
Data format	ASCII listing # Three-hours indices Kp and ap # created @ 2010-12-06 04:40:01 # MJD2000 Kp ap -365.9375 3 2 -364.8125 27 12 -364.6875 10 4 ... Format description: • File starts with a number of header lines all starting with # • Followed by one 1 line for description of column variables • Afterwards each line is formatted as follows: Column Format Description ===== 1-11 f11.4 MJD2000 centered at the three-hours time interval (0-3, 3-6, 6-9, 9-12, 12-15, 15-18, 18-21, 21-24 UT) 12-14 i3 3-hourly Kp index 15-18 i4 3-hourly ap index
Data volume	27 kB / year

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 113 of 136

Product identifier	AUX_KP__2_
Update rate	2 updates per month
Latency	few days to one months
Data source	GFZ (based on information from http://www.gfz-potsdam.de/en/kp-index/)
Notes	

Product identifier	AUX_KP__2F
Definition	Kp – Planetary three-hourly index of geomagnetic activity recorded at 13 mid-latitude ground-based observatories.
Application	EEFXTMS_2F
Spatial representation	1 value describing the global state
Time representation	Time series (3-hours average: 0-3h, 3-6h, 6-9h, 9-12h, 12-15h, 15-18h, 18-21h, 21-24h)
Units	unitless
Resolution	Kp indices range in 28 steps from 0 (quiet) to 9 (greatly disturbed) with fractional parts expressed in thirds of a unit. A Kp-value equal to 27, for example, means 2 and 2/3 or 3-; a Kp-value equal to 30 means 3 and 0/3 or 3 exactly; and a Kp-value equal to 33 means 3 and 1/3 or 3+.
Uncertainty	N/A
Quality indicator	N/A
Data volume	27 kB / year
Data format	ASCII table; 11 1 12421 22017 31313171320 35 7 6 2 5 5 6 5 7 50.21 11 1 22421 32020 71010171717 35 7 7 3 4 4 6 6 6 50.21 11 1 32421 41313 71317232730 43 5 5 3 5 6 9 12 15 80.42 11 1 42421 51727171717202013 44 6 12 6 6 6 7 7 5 70.31 11 1 52421 6 3 0 01313101313 20 2 0 0 5 5 4 5 5 30.10 11 1 62421 72313 3 7 3132750 42 9 5 2 3 2 5 12 48 110.63 11 1 72421 85733333023233733 81 67 18 18 15 9 9 22 18 221.15 11 1 82421 92723233033272730 66 12 9 9 15 18 12 12 15 130.73 ... Format description file wdc_fmt.doc: Column Format Description ===== ===== ===== 1- 2 i2 yy, last two digits of year 3- 4 i2 mm, month (1-12) 5- 6 i2 dd, day of month (1-31) 7-10 i4 Bartels solar rotation number - a sequence of 27-day

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 114 of 136

Product identifier	AUX_KP_2F
	<p>56-58 i3 Ap equivalent daily amplitude - the arithmetic mean of the day's eight ap values</p> <p>59-61 f3.1 Cp or Planetary Daily Character Figure - a qualitative Estimate of overall level of magnetic activity for the day determined from the sum of the eight ap amplitudes. Cp ranges, in steps of one-tenth, from 0 (quiet) to 2.5 (highly disturbed)</p> <p>62-62 i1 C9 - a conversion of the 0 to 2.5 range of the Cp index to one digit between 0 and 9</p> <p>63-65 i3 International Sunspot Number. Records contain * Zurich number through December 31, 1980 * International Brussels number thereafter</p> <p>66-70 f5.1 Ottawa 10.7 cm Solar Radio Flux adjusted to 1 AU - measured at 1700 UT daily and expressed in units of $10^{-22} \text{ W/m}^2/\text{Hz}$. Observations began on February 14, 1947. From that date through December 31, 1973, the fluxes given here do not reflect the revisions Ottawa made in 1966.</p> <p>71-71 i1 Flux Qualifier 0: indicates flux required no adjustment; 1: indicates flux required adjustment for burst in progress at time of measurement; 2: indicates a flux approximated by either interpolation or extrapolation; 3: indicates no observation.</p> <p>(The last three fields in columns 63-71 are optional. If all three or one of them are missing a new line starts after the last record.)</p>
Latency	< 3 hours
Update rate	3 hours
Data source	<p>http://www-app3.gfz-potsdam.de/kp_index/qlyymm.wdc</p> <p>data format: ftp://ftp.gfz-potsdam.de/pub/home/obs/kp-ap/wdc/wdc_fmt.doc ,</p> <p>Adolf-Schmidt-Observatory for Geomagnetism Niemegk, Helmholtz Center Potsdam, German Research Centre for Geosciences, GFZ, Potsdam, Germany.</p>
Notes	<p>The 3 hourly KP index values are published with a delay between 1 and 3 hours with respect to the hour of the day.</p> <p>All the three hours KP index values of the day not yet available at the time of the download are filled with "99".</p> <p>E.g downloading the data after the 7.30 p.m a possible value of the Kp index is 1710102010999999. Please note that all the 8 i2 value have been filled.</p> <p>13-28 8i2 3-hourly Kp indices (0-3, 3-6, 6-9, 9-12, 12-15,15-18, 18-21, 21-24 UT)</p> <p>The Kp daily sum is computed only in case the three hourly KP index covering the whole day are available (all 8 i2 different from "99").</p> <p>In case of lack of data the Kp daily sum is not computed and the related 3 columns are filled white space. E.g " "</p> <p>29-31 i3 Daily Kp sum, expressed to the nearest third of a unit (supplied only for tradition, use Ap scientific purposes!)</p> <p>The 3 hourly Ap index are computed together with the Kp index so the related column will</p>

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 115 of 136

Product identifier	AUX_KP__2F
	be filled with the Ap values only if the Kp related to the same 3 hour column is available. E.g downloading the data after the 7 p.m a possible value of the Ap index is " 6 4 4 7 4". The value not already computed will remain empty, i.e. filled with spaces. 32-55 8i3 3-hourly ap indices (0-3, 3-6, 6-9, 9-12, 12-15,15-18, 18-21, 21-24 UT)

Product identifier	AUX_DST_2_
Definition	<p>Dst – Equivalent equatorial magnetic disturbance indices derived from hourly scaling of low-latitude horizontal magnetic variation. Dst is directly related to the intensity of the magnetospheric ring current.</p> <p>Est – Part of the magnetic disturbance which is attributed to external currents (ring current)</p> <p>Ist – Part of the magnetic disturbance which is attributed to induced currents in the Earth</p>
Application	MSW_EULi2_C, MSW_EULi2_D, MSW_EUL_2F, MCO_SHAi2C, MCO_SHAi2D, MCO_SHA_2F, MLI_SHAi2C, MLI_SHAi2D, MIO_SHAi2C, MIO_SHAi2D, WP16000
Spatial representation	1 value describing the global state
Time representation	Time series (1-hour average)
Units	nT
Resolution	1 pT
Uncertainty	N/A
Quality indicator	Not provided
Data volume	45 kB / year
Data format	<p>ASCII table;</p> <pre># Expanded and assembled Dst, Est and Ist, Zero Mean # created @ 2011-10-24 00:10:00 # # MJD2000 Dst Est Ist Flag -364.97917 -7.000 -8.994 1.994 D -364.93750 -4.000 -6.877 2.877 D -364.89583 -4.000 -6.873 2.873 D -364.85417 -8.000 -9.745 1.745 D -364.81250 -8.000 -9.770 1.770 D -364.77083 -5.000 -7.626 2.626 D -364.72917 -4.000 -6.895 2.895 D -364.68750 -1.000 -4.725 3.725 D -364.64583 3.000 -1.821 4.821 D Format description: Lines 1-3: header information Line 4: description of column variables Each line from Line 5 onward: Column Format Description ===== ===== ===== 1-12 f12.5 MJD2000 centered at the averaging time interval (1 hour) 13-22 f10.3 1 hour averaged Dst index 23-32 f10.3 1 hour averaged Est index 33-42 f10.3 1 hour averaged Ist index</pre>

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 116 of 136

Product identifier	AUX_DST_2_
	43-47 4x,a1 D - Definitive, P - Preliminary
Update rate	daily
Latency	real time (< 1 day) definitive (up to several years)
Data source	GFZ (based on information from http://swdcwww.kugi.kyoto-u.ac.jp/dstdir/index.html)
Notes	Explanation see, e.g., [RD-13]

Product identifier	AUX_DST_2F																																							
Definition	Dst – Equivalent equatorial magnetic disturbance indices derived from hourly scaling of low-latitude horizontal magnetic variation. Dst is directly related to the intensity of the magnetospheric ring current.																																							
Application	IBIxTMS_2F, FACxTMS_2F, FAC_TMS_2F, EEFxTMS_2F																																							
Spatial representation	1 value describing the global state																																							
Time representation	Time series (1-hour average)																																							
Units	nT																																							
Resolution	1.0																																							
Uncertainty	Not provided																																							
Quality indicator	Not provided																																							
Data volume	45 kB / year																																							
Data format	<div>ASCII listing (others)</div> <div>The format of the file is given in http://wdc.kugi.kyoto-u.ac.jp/dstae/format/dstformat.html.</div> <table><tr><th colspan="3">RECORD FORMAT (LENGTH: 120 BYTE FIXED)</th></tr><tr><th>COLUMN</th><th>FORMAT</th><th>SHORT DESCRIPTION</th></tr><tr><td>1-3</td><td>A3</td><td>Index name 'DST'</td></tr><tr><td>4-5</td><td>I2</td><td>The last two digits of the year</td></tr><tr><td>6-7</td><td>I2</td><td>Month</td></tr><tr><td>8</td><td>A1</td><td>'*' for index</td></tr><tr><td>9-10</td><td>I2</td><td>Date</td></tr><tr><td>11-12</td><td>A2</td><td>All spaces or may be "RR" for quick look</td></tr><tr><td>13</td><td>A1</td><td>'X' (for index)</td></tr><tr><td>14</td><td>A1</td><td>Version (0: quicklook, 1: provisional, 2: final, 3 and up: corrected final or may be space)</td></tr><tr><td>15-16</td><td>I2</td><td>Top two digits of the year (19 or space for 19XX, 20 from 2000)</td></tr><tr><td>17-20</td><td>I4</td><td>Base value, unit 100 nT</td></tr><tr><td>21-116</td><td>24I4</td><td>24 hourly values, 4 digit number, unit 1 nT, value 9999 for the</td></tr></table>	RECORD FORMAT (LENGTH: 120 BYTE FIXED)			COLUMN	FORMAT	SHORT DESCRIPTION	1-3	A3	Index name 'DST'	4-5	I2	The last two digits of the year	6-7	I2	Month	8	A1	'*' for index	9-10	I2	Date	11-12	A2	All spaces or may be "RR" for quick look	13	A1	'X' (for index)	14	A1	Version (0: quicklook, 1: provisional, 2: final, 3 and up: corrected final or may be space)	15-16	I2	Top two digits of the year (19 or space for 19XX, 20 from 2000)	17-20	I4	Base value, unit 100 nT	21-116	24I4	24 hourly values, 4 digit number, unit 1 nT, value 9999 for the
RECORD FORMAT (LENGTH: 120 BYTE FIXED)																																								
COLUMN	FORMAT	SHORT DESCRIPTION																																						
1-3	A3	Index name 'DST'																																						
4-5	I2	The last two digits of the year																																						
6-7	I2	Month																																						
8	A1	'*' for index																																						
9-10	I2	Date																																						
11-12	A2	All spaces or may be "RR" for quick look																																						
13	A1	'X' (for index)																																						
14	A1	Version (0: quicklook, 1: provisional, 2: final, 3 and up: corrected final or may be space)																																						
15-16	I2	Top two digits of the year (19 or space for 19XX, 20 from 2000)																																						
17-20	I4	Base value, unit 100 nT																																						
21-116	24I4	24 hourly values, 4 digit number, unit 1 nT, value 9999 for the																																						

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 117 of 136

Product identifier	AUX_DST_2F		
			missing data. First data is for the first hour of the day, and Last data is for the last hour of the day.
	117-120	I4	Daily mean value, unit 1 nT. Value 9999 for the missing data.
Latency	< 1 day		
Update rate	< 1 day		
Data source	<p>We can get the appropriate amount of data from Kyoto World Data Center using the following script.</p> <pre>===== url='http://wdc.kugi.kyoto-u.ac.jp/cgi-bin/dstae-cgi?' SCent=20 STens=0 SYear=2 SMonth=01 ECent=20 ETens=1 EYear=1 EMonth=01 Image='GIF' COLOR='COLOR' AE=0 Dst=0 Output='DST' Out='WDC' Email='bla@bla.de' output='test.txt' # original URL: # http://wdc.kugi.kyoto-u.ac.jp/cgi-bin/dstae-cgi?SCent=20&STens=1&SYear=1&SMonth=05&ECent=20&ETens=1&EYear=1&EMonth=06&Image+Type=GIF&COLOR=COLOR&AE+Sensitivity=0&Dst+Sensitivity=0&Output=DST&Out+format=WDC&Email=bla%40bla.de wget "http://wdc.kugi.kyoto-u.ac.jp/cgi-bin/dstae-cgi?SCent=\$SCent&STens=\$STens&SYear=\$SYear&SMonth=\$SMonth&ECent=\$ECent&ETens=\$ETens&EYear=\$EYear&EMonth=\$EMonth&Image+Type=\$Image&COLOR=\$COLOR&AE+Sensitivity=\$AE&Dst+Sensitivity=\$Dst&Output=\$Output&Out+format=\$out&Email=\$Email" -O \$output</pre> <p>What we need to input to the script is as follows:</p> <ol style="list-style-type: none"> (1) $Scent \cdot 100 + STens \cdot 10 + SYear = \text{Start year}$ (2) $SMonth = \text{Start month}$ (3) $ECent \cdot 100 + ETens \cdot 10 + EYear = \text{End year}$ (4) $EMonth = \text{End month}$ <p>Then, the script creates an output file named 'test.txt'</p>		
Notes	Preliminary Dst		

Product identifier	AUX_F10_2_
Definition	F10.7 : daily measure of the solar radio flux per unit frequency at a wavelength of 10.7 cm
Application	CI, MSW_EULi2D, MSW_EULi2F, MCO_SHAi2F, MLI_SHAi2C, MLI_SHAi2D, MIO_SHAi2D, DNSxWND_2_, WP16000

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 118 of 136

Product identifier	AUX_F10_2_
Spatial representation	One value for global state
Time representation	Time series (1 day average)
Units	10 ⁻²² Js ⁻¹ m ⁻² Hz ⁻¹
Resolution	0.1
Uncertainty	N/A
Quality indicator	Not provided
Data volume	32 kB / year
Data format	ASCII listing (others) # Assembled daily observed values of solar flux F10.7 # obtained from ftp.ngdc.noaa.gov/STP/SOLAR_DATA/SOLAR_RADIO/FLUX/Penticton_Observed/daily/DAILYPLT.OBS # on 17-Mar-2011 09:56:45 by program get_F107.m # MD2000 F10.7 in units of [10e ⁻²² W m ⁻² Hz ⁻¹] -729.5 101.6 -728.5 101.0 -727.5 101.1 -726.5 90.7 -725.5 89.3 -724.5 87.0 -723.5 84.9 -722.5 82.2 -721.5 81.6 -720.5 80.7 -719.5 84.8 -718.5 95.8 -717.5 90.4 ... Format description: Lines 1-4: header information Line 5: description of column variables Each line from Line 6 onward: Column Format Description ===== ===== ===== 1-08 f8.1 MJD2000 centered at noon 9-15 f7.1 F10.7 value ('*' if missing data)
Latency	< 10 days
Update rate	1 week
Data source	DTU based on information from ftp://ftp.ngdc.noaa.gov/STP/SOLAR_DATA/SOLAR_RADIO/FLUX/Penticton_Observed/
Notes	

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 119 of 136

Product identifier	AUX_F10_2F
Definition	F10.7: daily measure of the solar radio flux per unit frequency at a wavelength of 10.7 cm
Application	IBIxTMS_2F, FACxTMS_2F, FAC_TMS_2F, EEfxTMS_2F, AUX_PMF_2F
Spatial representation	One value for global state
Time representation	Time series (1 day average)
Units	$10^{-22} \text{ Wm}^{-2}\text{Hz}^{-1}$
Resolution	0.1
Uncertainty	Not provided
Quality indicator	Not provided
Data volume	< 1 MB
Data format	<p>The format of the data is described in the header of each data file.</p> <p>Ex.></p> <pre>:Product: Daily Solar Data quar_DSD.txt :Issued: 2025 UT 07 Jul 2011 # # Prepared by the U.S. Dept. of Commerce, NOAA, Space Weather Prediction Center # Please send comments and suggestions to SWPC.Webmaster@noaa.gov # # Quarterly Daily Solar Data # # Sunspot Stanford GOES15 # Area Solar X-Ray ----- Flares ----- # 10E-6 Mean Bkgd X-Ray Optical # Hemis. Regions Field Flux C M X S 1 2 3 #----- 2011 04 01 109 62 330 1 -999 B2.3 2 0 0 1 0 0 0 2011 04 02 108 66 280 0 -999 B2.2 0 0 0 1 0 0 0 2011 04 03 114 70 290 0 -999 B3.9 0 0 0 0 0 0 0 2011 04 04 113 83 340 1 -999 B3.3 0 0 0 1 0 0 0 2011 04 05 109 65 380 0 -999 B2.8 0 0 0 0 0 0 0 2011 04 06 117 56 230 1 -999 B3.1 3 0 0 0 0 0 0</pre> <p>Format description: Header lines of non-data information, header line starting with : or #, then 1 line per daily data.</p> <p>See also ftp://ftp.sec.noaa.gov/pub/indices/old_indices/README</p>
Latency	1 day
Update rate	daily
Data source	<p>ftp://ftp.sec.noaa.gov/pub/indices/old_indices/.</p> <p>The file names in the directory are as described below.</p> <ol style="list-style-type: none"> (1) From 1994 to the previous year (i.e. to 2010 as of June 2011): yyyy_DSD.txt (where yyyy signifies a year). (2) In the current year (i.e. in 2011 as of June 2011): yyyyQq_DSD.txt (where yyyy signifies a year and q the quarter of a year).
Notes	

Product identifier	AUX_IMF_2_
Definition	The Interplanetary Magnetic Field (IMF)
Application	MSW_EULi2D, MSW_EUL_2F, MCO_SHAi2D, MCO_SHA_2F, MLI_SHAi2D, MIO_SHAi2D

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 120 of 136

Product identifier	AUX_IMF_2_			
Spatial representation	Value of the IMF propagated to the Earth magnetosphere (1 global value per time stamp), provided in GSE and GSM format			
Time representation	Time series (1 hour averages)			
Units	nT for IMF, km/s for solar wind speed			
Resolution	0.1 nT for IMF, 1 km/s for solar wind speed			
Uncertainty	Not provided			
Quality indicator	Sigma B; sigma v			
Data format	CDF			
	Variable Name	Description	Type	Units
	Epoch	Epoch Time	CDF_EPOCH	
	YR	Year	CDF_INT4	
	Day	Decimal Day (JAN 1=1)	CDF_INT4	
	HR	Decimal Hour	CDF_INT4	
	Rot#	Bartels Rotation Number	CDF_INT4	
	IMF	ID for IMF spacecraft	CDF_INT4	
	PLS	ID for SW Plasma spacecraft	CDF_INT4	
	IMF_PTS	# fine time scale IMF points	CDF_INT4	
	PLS_PTS	# fine time scale plasma points	CDF_INT4	
	ABS_B	Field Magnitude Avg.	CDF_REAL4	nT
	F	Magnitude of avg. field vector	CDF_REAL4	nT
	THETA_AV	Lat. Angle of AV.	CDF_REAL4	Deg
	PHI_AV	Long. Angle of AV.	CDF_REAL4	Deg
	BX_GSE	Bx, GSE	CDF_REAL4	nT
	BY_GSE	By, GSE	CDF_REAL4	nT
	BZ_GSE	Bz, GSE	CDF_REAL4	nT
	BY_GSM	By, GSM	CDF_REAL4	nT
	BZ_GSM	Bz, GSM	CDF_REAL4	nT
	SIGMA-ABS_B	sigma-ABS_B	CDF_REAL4	nT
	SIGMA-B	sigma-B	CDF_REAL4	nT
	SIGMA-Bx	sigma-Bx	CDF_REAL4	nT
	SIGMA-By	sigma-By	CDF_REAL4	nT
	SIGMA-Bz	sigma-Bz	CDF_REAL4	nT
	T	Plasma temperature	CDF_REAL4	K
	N	Ion density	CDF_REAL4	cm ⁻³
	V	Flow speed	CDF_REAL4	km/s
	PHI-V	Flow longitude	CDF_REAL4	Deg
	THETA-V	Flow latitude	CDF_REAL4	Deg
	Ratio	Alpha/prot. ratio	CDF_REAL4	
	Pressure	Flow pressure	CDF_REAL4	nPa
	SIGMA-T	sigma-T	CDF_REAL4	K
	SIGMA-N	sigma-n	CDF_REAL4	cm ⁻³
	SIGMA-V	sigma-V	CDF_REAL4	Km/s
	SIGMA-PHI-V	sigma-phi-V	CDF_REAL4	Deg
	SIGMA-THETA-V	sigma-theta-V	CDF_REAL4	Deg
	SIGMA-ratio	sigma-ratio	CDF_REAL4	
	E	Electric Field	CDF_REAL4	mV/m
	Beta	Plasma beta	CDF_REAL4	
	Mach_num	Alfen mach number	CDF_REAL4	
	Mgs_mach_num	Magnetosonic mach number	CDF_REAL4	
	PR-FLX_1	PROT Flux > 1 MEV	CDF_REAL4 (cm2 ster s) ⁻¹	
	PR-FLX_2	PROT Flux > 2 MEV	CDF_REAL4 (cm2 ster s) ⁻¹	
	PR-FLX_4	PROT Flux > 4 MEV	CDF_REAL4 (cm2 ster s) ⁻¹	
	PR-FLX_10	PROT Flux >10 MEV	CDF_REAL4 (cm2 ster s) ⁻¹	
	PR-FLX_30	PROT Flux >30 MEV	CDF_REAL4 (cm2 ster s) ⁻¹	
	PR-FLX_60	PROT Flux >60 MEV	CDF_REAL4 (cm2 ster s) ⁻¹	

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 121 of 136

Product identifier	AUX_IMF_2_
	MFLX M'SPH Flux Flag CDF_INT4 (6=No,1=All,-1=n/a) R Sunspot number (daily) CDF_INT4 F10_INDEX F10.7 index (daily) CDF_REAL4 KP Kp*10 (3-h) CDF_INT4 DST Dst Index (1-h) CDF_INT4 nT AE AE-index (1-h) CDF_INT4 nT AP_INDEX ap-index (3-h) CDF_INT4 nT AL_INDEX AL-index (1-h) CDF_INT4 nT AU_INDEX AU-index (1-h) CDF_INT4 nT PC_N_INDEX PC(N) index CDF_REAL4
Data volume	2.2 MB / year
Latency	~ 1 month
Update rate	~ 1 month
Data source	DTU based on information from ftp://cdaweb.gsfc.nasa.gov/pub/istp/omni2/yyyy/omni2_h0_mrg1hr_yyyymmdd_v01.cdf with yyyy =year, mm = month, dd =day
Notes	For detailed description of the data see http://omniweb.gsfc.nasa.gov/html/omni2_doc.html

Product identifier	AUX_IMF_2F
Definition	The Interplanetary Magnetic Field (IMF) is described by the three component of the solar IMF provided in GSM coordinates.
Application	IBIXTMS_2F, FACxTMS_2F, FAC_TMS_2F
Spatial representation	Values at the L1 point (equilibrium between sun's and Earth's gravity force)
Time representation	Time series (1 h averages)
Units	nT for IMF
Resolution	< 0.1 nT
Uncertainty	Not provided
Quality indicator	S is the status of the data (0 nominal data, 1-8 bad data, 9 no data).
Data volume	~65 kB / month
Data format	Example file format for IMF 1h values (yyymm_ace_mag_1h.txt): :Product: 201102_ace_mag_1h.txt :Issued: 2011 Feb 21 1010 UT # Prepared by the U.S. Dept. of Commerce, NOAA, Space Weather Prediction Center # Please send comments and suggestions to SWPC.Webmaster@noaa.gov # # Magnetometer values are in GSM coordinates. # # Units: Bx, By, Bz, Bt in nT # Units: Latitude degrees +/- 90.0 # Units: Longitude degrees 0.0 - 360.0 # Status(S): 0 = nominal data, 1 to 8 = bad data record, 9 = no data # Missing data values: -999.9 # Source: ACE Satellite - Magnetometer # # Hourly Averaged Real-time Interplanetary Magnetic Field Values # # Modified Seconds

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 122 of 136

Product identifier	AUX_IMF_2F
	<pre># UT Date Time Julian of the ----- GSM Coordinates ----- ----- # YR MO DA HHMM Day Day S Bx By Bz Bt Lat. Long. #----- ----- 2011 02 01 0000 55593 0 0 6.7 -3.5 -2.5 8.0 -18.2 332.3 2011 02 01 0100 55593 3600 0 0.1 3.4 -2.7 4.4 -38.2 87.8 2011 02 01 0200 55593 7200 0 -5.4 0.9 1.4 5.6 14.1 170.6 2011 02 01 0300 55593 10800 0 2.3 -4.9 0.8 5.5 8.9 295.0 2011 02 01 0400 55593 14400 0 3.4 -3.0 -8.3 9.5 -61.6 318.6 ... Format description: header lines of non-data information, header line starting with : or #, then 1 line per 1 hourly data. B is in GSM coordinates. The format is '(i4,2i3,2x,2i2,2i8,i5,6f8.1)'. See also ftp://ftp.sec.noaa.gov/pub/lists/ace2/README</pre>
Update rate	Hourly data files are updated at 10 minutes past the hour.
Latency	10 min
Data source	ftp://ftp.sec.noaa.gov/pub/lists/ace2/ in this directory file is named: yyyyymm_ace_mag_1h.txt Space Weather Prediction Center, NOAA
Notes	

Product identifier	AUX_SWV_2F
Definition	Solar wind velocity
Application	IBIXTMS_2F, FACxTMS_2F, FAC_TMS_2F
Spatial representation	Values at the L1 point (equilibrium between sun's and Earth's gravity force)
Time representation	Time series (1 h averages)
Units	km/s for solar wind velocity
Resolution	1 km/s
Uncertainty	Not provided
Quality indicator	S is the status of the data (0 nominal data, 1-8 bad data, 9 no data).
Data volume	~55 kB / month
Data format	Example file format for 1h solar wind parameters (yyyyymm_ace_swepam_1h.txt): :Product: 201102_ace_swepam_1h.txt :Issued: 2011 Feb 21 1010 UT # Prepared by the U.S. Dept. of Commerce, NOAA, Space Weather Prediction Center # Please send comments and suggestions to SWPC.Webmaster@noaa.gov # # Units: Proton density p/cc

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 123 of 136

Product identifier	AUX_SWV_2F																																																							
	<div># Units: Bulk speed km/s</div> <div># Units: Ion temperture degrees K</div> <div># Status(S): 0 = nominal data, 1 to 8 = bad data record, 9 = no data</div> <div># Missing data values: Density and Speed = -9999.9, Temp. = -1.00e+05</div> <div># Source: ACE Satellite - Solar Wind Electron Proton Alpha Monitor</div> <div>#</div> <div># Hourly Averaged Real-time Bulk Parameters of the Solar Wind Plasma</div> <div>#</div> <div>#</div> <div><table><tr><th># UT Date</th><th>Time</th><th>Modified Julian</th><th>Seconds of the</th><th>Proton</th><th>Solar Wind</th><th>Ion</th></tr><tr><th># YR MO DA</th><th>HHMM</th><th>Day</th><th>Day</th><th>S</th><th>Density</th><th>Bulk Speed</th><th>Temperature</th></tr></table></div> <div><table><tr><td>2011 02 01</td><td>0000</td><td>55593</td><td>0</td><td>0</td><td>1.5</td><td>303.3</td><td>1.02e+05</td></tr><tr><td>2011 02 01</td><td>0100</td><td>55593</td><td>3600</td><td>0</td><td>2.7</td><td>330.4</td><td>1.24e+05</td></tr><tr><td>2011 02 01</td><td>0200</td><td>55593</td><td>7200</td><td>0</td><td>7.6</td><td>370.0</td><td>1.17e+05</td></tr><tr><td>2011 02 01</td><td>0300</td><td>55593</td><td>10800</td><td>0</td><td>18.2</td><td>364.6</td><td>5.29e+04</td></tr><tr><td>2011 02 01</td><td>0400</td><td>55593</td><td>14400</td><td>0</td><td>9.3</td><td>353.0</td><td>6.17e+04</td></tr></table></div> <div>...</div> <div>Format description:</div> <div>Header lines of non-data information, header line starting with : or #, then 1 line per 1 hour data.</div> <div>The format is ' (i4,2i3,2x,2i2,2i8,i5,2f11.2,e13.2E2) '</div> <div>See also ftp://ftp.sec.noaa.gov/pub/lists/ace2/README</div>	# UT Date	Time	Modified Julian	Seconds of the	Proton	Solar Wind	Ion	# YR MO DA	HHMM	Day	Day	S	Density	Bulk Speed	Temperature	2011 02 01	0000	55593	0	0	1.5	303.3	1.02e+05	2011 02 01	0100	55593	3600	0	2.7	330.4	1.24e+05	2011 02 01	0200	55593	7200	0	7.6	370.0	1.17e+05	2011 02 01	0300	55593	10800	0	18.2	364.6	5.29e+04	2011 02 01	0400	55593	14400	0	9.3	353.0	6.17e+04
# UT Date	Time	Modified Julian	Seconds of the	Proton	Solar Wind	Ion																																																		
# YR MO DA	HHMM	Day	Day	S	Density	Bulk Speed	Temperature																																																	
2011 02 01	0000	55593	0	0	1.5	303.3	1.02e+05																																																	
2011 02 01	0100	55593	3600	0	2.7	330.4	1.24e+05																																																	
2011 02 01	0200	55593	7200	0	7.6	370.0	1.17e+05																																																	
2011 02 01	0300	55593	10800	0	18.2	364.6	5.29e+04																																																	
2011 02 01	0400	55593	14400	0	9.3	353.0	6.17e+04																																																	
Update rate	Hourly data files are updated at 10 minutes past the hour.																																																							
Latency	10 min																																																							
Data source	ftp://ftp.sec.noaa.gov/pub/lists/ace2/ in this directory file is named: yyyyymm_ace_swepam_1h.txt Space Weather Prediction Center, NOAA																																																							
Notes																																																								

Product identifier	AUX_IRZ_2F
Definition	Ig/R12 – 12 month smoothed sunspot number
Application	EEFXTMS_2F
Spatial representation	1 value describing the global state
Time representation	Time series in 1 month steps
Units	unitless
Resolution	Sunspot number is given to 1 decimal point
Uncertainty	N/A
Quality indicator	N/A
Data volume	< 10 kB / year
Data format	<p>ASCII table;</p> <p>10,06,2011,</p> <p>1,1958,12,2013,</p> <p>165.7,</p> <p>164.6,164.3,165.6,166.6,167.2,167.7,167.6,166.5,165.4,164.1,162.3,161.2</p> <p>160.6,159.1,156.4,153.1,149.4,146.0,143.9,143.2,141.3,138.7,136.4,133.7</p>

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 124 of 136

Product identifier	AUX_IRZ_2F
	<p>131.0,129.1,128.1,127.3,125.2,122.3,117.3,111.0,105.6,101.3,97.0,92.2 87.6,83.3,78.4,73.1,68.6,63.5,58.8,55.9,54.7,53.7,52.5,51.3 49.4,46.3,43.2,41.4,40.5,39.6,38.4,36.8,34.4,31.9,30.3,28.6 ... 138.3,137.3,137.6,138.6,136.8,140.2,140.6,141.8,142.2,139.7,139.4,140.0, 141.3 200.1, 199.0,200.9,201.3,196.8,191.4,186.8,185.2,184.9,183.8,182.2,180.7,180.5, 178.6,176.9,174.5,169.2,165.1,161.4,155.8,151.3,146.3,141.1,137.2,132.5, 128.9,125.0,121.6,119.6,117.0,113.9,108.4,101.9, 97.2, 92.6, 87.2, 82.9, 80.2, 74.8, 68.9, 64.3, 60.1, 55.8, 53.1, 52.5, 52.3, 51.4, 50.5, 48.7, 45.2, 41.8, 39.8, 39.4, 39.2, 38.3, 36.8, 34.9, 32.7, 30.8, 30.0, 29.8, ... 74.2, 75.8, 76.5, 76.3, 76.8, 78.0, 77.8, 76.8, 76.4, 76.2, 76.8, 77.2, 76.9</p> <p>Format description:</p> <p>First line: day, month, year of the last update of this file, separated by comma and line closed with comma Second line: blank Third line: start month, start year, end month, end year, separated by comma and line closed with comma Fourth line: blank First block (IG index): Line 1: monthly mean for the month preceding the start month followed by comma Following lines: Monthly values separated by comma or line break; some values may contain whitespace after the comma Last Line: monthly mean for the month after the end month</p> <p>Blank line separates first and second block</p> <p>Second block (Rz, sunspot number): Line 1: monthly mean for the month preceding the start month followed by comma Following lines: Monthly values separated by comma or line break; some values may contain whitespace after the comma Last Line: monthly mean for the month after the end month</p> <p>A negative Rz index means that the given index is the 13-months- running mean of the solar radio flux (F10.7). The close correlation between (Rz)12 and (F10.7)12 is used to derive the (Rz)12 indices.</p> <p>An IG index of -111 indicates that no IG values are available for the time period. In this case a correlation function between (IG)12 and (Rz)12 is used to obtain (IG)12.</p> <p>See also ftp://nssdcftp.gsfc.nasa.gov/models/ionospheric/iri/iri2012/00readme.txt or</p>

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 125 of 136

Product identifier	AUX_IRZ_2F
	ftp://nssdcftp.gsfc.nasa.gov/models/ionospheric/iri/iri2012/irifun.for
Latency	Monthly
Update rate	Monthly
Data source	ftp://nssdcftp.gsfc.nasa.gov/models/ionospheric/iri/iri2012/ig_rz.dat
Notes	

Product identifier	AUX_DCB_2F
Definition	GPS satellite differential code biases (dcb)
Application	TECxTMS_2F
Spatial representation	Ordered by satellite number
Time representation	1 value/day
Units	m
Resolution	0.001 ns
Uncertainty	Not provided
Quality indicator	Value for root mean scatter (RMS) of the daily solution
Data volume	~170 kB/day
Data format	ASCII listing (others) Example of dcb for day 1 of year 2008 'igsg0010.08i': ... DCB values in nanoseconds, reference is Sum_of_SatDCBs = 0 COMMENT DIFFERENTIAL CODE BIASES START OF AUX DATA 01 -3.381 0.024 PRN / BIAS / RMS 02 5.561 0.022 PRN / BIAS / RMS 03 -2.884 0.029 PRN / BIAS / RMS 04 -1.670 0.029 PRN / BIAS / RMS 05 -3.015 0.046 PRN / BIAS / RMS 06 -2.499 0.017 PRN / BIAS / RMS 07 -4.369 0.035 PRN / BIAS / RMS 08 -2.979 0.032 PRN / BIAS / RMS 09 -2.112 0.014 PRN / BIAS / RMS 10 -3.982 0.060 PRN / BIAS / RMS 11 2.015 0.018 PRN / BIAS / RMS 12 2.162 0.039 PRN / BIAS / RMS 13 1.655 0.044 PRN / BIAS / RMS 14 0.257 0.007 PRN / BIAS / RMS ... See also ftp://cddis.gsfc.nasa.gov/pub/reports/formats/ionex1.pdf
Latency	3-9 hours
Update rate	Daily
Data source	ftp://cddis.gsfc.nasa.gov/pub/gps/products/ionex/ , NASA Goddard Space Flight Center
Notes	

Product identifier	AUX_OBS_2_
---------------------------	-------------------

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 126 of 136

Product identifier	AUX_OBS_2_
Definition	Geomagnetic Observatory Data are hourly means of the three components of the Earth's magnetic field measured at magnetic observatories, in geocentric (North-East-Centred) coordinates..
Application	Comprehensive Inversion chain products, MIO_SHAi2D, MMA_SHA_2F, MCO_VAL_2_, MIO_VAL_2_
Spatial representation	Values at about one hundred magnetic observatories at the Earth's surface
Time representation	Time series (1 hour averages)
Units	nT
Resolution	0.1nT
Quality indicator	5.12.1.1.1 The 'Quality' channel identifies data as INTERMAGNET 'Quasi-definitive' (available within three months) or 'Definitive' (available after about one year). See http://www.intermagnet.org/faqs-eng.php for details.
Data volume	< 150Mb/yr
Data format	ASCII listing (others) Example: #Observatory hourly mean values selected from WDC Edinburgh/INTERMAGNET #File created on 6 2 2012 #obs gc_lat long rad yyyy mm dd UT N=-Btheta E=Bphi C=-Br ##### #AAE1 AAE1 8.974 38.767 6380.055 1998 1 1 0.5 35961.0 NaN 968.0 AAE1 8.974 38.767 6380.055 1998 1 1 1.5 35960.0 746.0 968.0 AAE1 8.974 38.767 6380.055 1998 12 31 22.5 35987.0 758.0 1036.0 AAE1 8.974 38.767 6380.055 1998 12 31 23.5 35988.0 756.0 1036.0 #ABK0 ABK0 68.218 18.817 6360.064 1998 1 1 0.5 11466.0 966.0 51282.0 ABK0 68.218 18.817 6360.064 1998 1 1 1.5 11467.0 965.0 51281.0 Format description: Variable number of header lines each starting with '#'. Note, embedded header lines expected, such as introducing a next station (see example above) Missing value flag = NaN Column Format Description ===== 1-4 s4 3-letter IAGA code, followed by digit 5-12 f8.3 geocentric latitude (degrees) 13-20 f8.3 geocentric longitude (degrees) 21-39 f9.3 radius (km) 30-34 i5 year 35-37 i3 month 38-40 i3 day 41-45 f5.1 UT (hours) 46-54 f9.1 North (-B_theta) component (nT) 55-63 f9.1 East (B_phi) component (nT) 64-72 f9.1 Centered (-B_r) component (nT)
Update rate	Every 3 months

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 127 of 136

Product identifier	AUX_OBS_2_
Latency	3 months for quasi-definitive – 1-2 years for definitive
Availability	BGS
Notes	

Product identifier	AUX_OBSM2_																																							
Definition	Geomagnetic Observatory Data are 1 minute means of the three components of the Earth’s magnetic field measured at magnetic observatories, in geocentric (North-East-Centred) coordinates..																																							
Application	Comprehensive Inversion chain products, MIO_SHAi2D, MMA_SHA_2F, MCO_VAL_2_, MIO_VAL_2_																																							
Spatial representation	Values at about one hundred magnetic observatories at the Earth’s surface																																							
Time representation	Time series (1 minute averages)																																							
Units	nT																																							
Resolution	0.1nT																																							
Quality indicator	The ‘Quality’ channel identifies data as INTERMAGNET ‘Quasi-definitive’ (available within three months) or ‘Definitive’ (available after about one year). See http://www.intermagnet.org/faqs-eng.php for details.																																							
Data volume	< 3Mb/day																																							
Data format	<table><tr><td colspan="4">CDF</td></tr><tr><td>Field name</td><td>Type</td><td>Unit</td><td>Contents</td></tr><tr><td>IAGA_code</td><td>CDF_CHAR</td><td>-</td><td>IAGA three letter observatory identification code associated with datum</td></tr><tr><td>Quality</td><td>CDF_CHAR</td><td>-</td><td>Data quality: D for definitive and Q for quasi-definitive</td></tr><tr><td>Timestamp</td><td>CDF_EPOCH</td><td>-</td><td>Date and time</td></tr><tr><td>Longitude</td><td>CDF_DOUBLE</td><td>deg</td><td>Longitude</td></tr><tr><td>Latitude</td><td>CDF_DOUBLE</td><td>deg</td><td>Geocentric latitude</td></tr><tr><td>Radius</td><td>CDF_DOUBLE</td><td>m</td><td>Radius</td></tr><tr><td>B_NEC</td><td>CDF_DOUBLE</td><td>nT</td><td>Geocentric-north, east, and geocentric-down component of magnetic field. NaN values are used as placeholders for missing data</td></tr></table>				CDF				Field name	Type	Unit	Contents	IAGA_code	CDF_CHAR	-	IAGA three letter observatory identification code associated with datum	Quality	CDF_CHAR	-	Data quality: D for definitive and Q for quasi-definitive	Timestamp	CDF_EPOCH	-	Date and time	Longitude	CDF_DOUBLE	deg	Longitude	Latitude	CDF_DOUBLE	deg	Geocentric latitude	Radius	CDF_DOUBLE	m	Radius	B_NEC	CDF_DOUBLE	nT	Geocentric-north, east, and geocentric-down component of magnetic field. NaN values are used as placeholders for missing data
CDF																																								
Field name	Type	Unit	Contents																																					
IAGA_code	CDF_CHAR	-	IAGA three letter observatory identification code associated with datum																																					
Quality	CDF_CHAR	-	Data quality: D for definitive and Q for quasi-definitive																																					
Timestamp	CDF_EPOCH	-	Date and time																																					
Longitude	CDF_DOUBLE	deg	Longitude																																					
Latitude	CDF_DOUBLE	deg	Geocentric latitude																																					
Radius	CDF_DOUBLE	m	Radius																																					
B_NEC	CDF_DOUBLE	nT	Geocentric-north, east, and geocentric-down component of magnetic field. NaN values are used as placeholders for missing data																																					
Update rate	Daily																																							
Latency	4-days, 1-, 3-, 6-months, 1-, 2- and 4-years																																							
Availability	BGS																																							
Notes																																								

Product identifier	AUX_OBSS2_
Definition	Geomagnetic Observatory Data are 1 second values of the three components of the Earth's magnetic field measured at magnetic observatories, in geocentric (North-East-Centred) coordinates..
Application	Comprehensive Inversion chain products, MIO_SHAi2D, MMA_SHA_2F, MCO_VAL_2_, MIO_VAL_2_

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 128 of 136

Product identifier	AUX_OBSS2_																																			
Spatial representation	Values at about one hundred magnetic observatories at the Earth’s surface																																			
Time representation	Time series (1 second values)																																			
Units	nT																																			
Resolution	0.01nT																																			
Quality indicator	The ‘Quality’ channel identifies data as INTERMAGNET ‘Quasi-definitive’ (available within three months) or ‘Definitive’ (available after about one year). See http://www.intermagnet.org/faqs-eng.php for details.																																			
Data volume	< 50Mb/day																																			
Data format	CDF <table><tr><th>Field name</th><th>Type</th><th>Unit</th><th>Contents</th></tr><tr><td>IAGA_code</td><td>CDF_CHAR</td><td>-</td><td>IAGA three letter observatory identification code associated with datum</td></tr><tr><td>Quality</td><td>CDF_CHAR</td><td>-</td><td>Data quality: D for definitive and Q for quasi-definitive</td></tr><tr><td>Timestamp</td><td>CDF_EPOCH</td><td>-</td><td>Date and time</td></tr><tr><td>Longitude</td><td>CDF_DOUBLE</td><td>deg</td><td>Longitude</td></tr><tr><td>Latitude</td><td>CDF_DOUBLE</td><td>deg</td><td>Geocentric latitude</td></tr><tr><td>Radius</td><td>CDF_DOUBLE</td><td>m</td><td>Radius</td></tr><tr><td>B_NEC</td><td>CDF_DOUBLE</td><td>nT</td><td>Geocentric-north, east, and geocentric-down component of magnetic field. NaN values are used as placeholders for missing data</td></tr></table>				Field name	Type	Unit	Contents	IAGA_code	CDF_CHAR	-	IAGA three letter observatory identification code associated with datum	Quality	CDF_CHAR	-	Data quality: D for definitive and Q for quasi-definitive	Timestamp	CDF_EPOCH	-	Date and time	Longitude	CDF_DOUBLE	deg	Longitude	Latitude	CDF_DOUBLE	deg	Geocentric latitude	Radius	CDF_DOUBLE	m	Radius	B_NEC	CDF_DOUBLE	nT	Geocentric-north, east, and geocentric-down component of magnetic field. NaN values are used as placeholders for missing data
Field name	Type	Unit	Contents																																	
IAGA_code	CDF_CHAR	-	IAGA three letter observatory identification code associated with datum																																	
Quality	CDF_CHAR	-	Data quality: D for definitive and Q for quasi-definitive																																	
Timestamp	CDF_EPOCH	-	Date and time																																	
Longitude	CDF_DOUBLE	deg	Longitude																																	
Latitude	CDF_DOUBLE	deg	Geocentric latitude																																	
Radius	CDF_DOUBLE	m	Radius																																	
B_NEC	CDF_DOUBLE	nT	Geocentric-north, east, and geocentric-down component of magnetic field. NaN values are used as placeholders for missing data																																	
Update rate	Daily																																			
Latency	4-days, 1-, 3-, 6-months, 1-, 2- and 4-years																																			
Availability	BGS																																			
Notes																																				

5.13 Auxiliary models

5.13.1 Magnetic field models

Product identifier	AUX_IGR_2_
Definition	IGRF (International Geomagnetic Reference Field) latest (11 th) generation is a continuous model of the Earth's main magnetic field. It is based on data from permanent observatories and from land, airborne, marine and satellite surveys (CHAMP, Ørsted). [RD-3] IGRF11 is valid for dates from 1900.0 to 2015.0. Values for dates before 1945.0 and after 2005.0 are preliminary, otherwise the values are definitive.
Application	MSW_SHA_2C, MSW_SHA_2D, MSW_SHA_2F, MCO_SHA_2C, MCO_SHA_2D, MCO_SHA_2F, MLI_SHA_2C, MMA_SHA_2C, MMA_SHA_2D, MIO_SHA_2C, MIO_SHA_2D, WP16000
Spatial representation	Spherical harmonics (degree 13)
Time representation	Coefficients for snap shot SH models 5 yrs apart; linear interpolation recommended, prediction of linear Secular Variation
Units	nT

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 129 of 136

Product identifier	AUX_IGR_2_
Resolution	N/A
Uncertainty	Modelled field uncertainty ~20nT [RD-3]
Quality indicator	N/A
Data format	ASCII listing (SHC format); See section 4.3.1
Data volume	36 kB
Update rate	5 years
Data source	DTU based on information from http://www.ngdc.noaa.gov/IAGA/vmod/igrf.html
Notes	A predictive model is required to estimate near-real time magnetic field observations from the satellite measurements. The IGRF is actually the only predictive model expected to be available at the launch time of <i>Swarm</i> . However, IGRF is known to provide not sufficiently accurate results for precise magnetic field modelling studies. It is anticipated to replace the IGRF by models known to produce higher quality results as soon as they are available also for predictions. This model will be contained in AUX_COR_2_.

Product identifier	AUX_IGR_2F
Definition	IGRF (International Geomagnetic Reference Field) latest (11 th) generation is a continuous model of the Earth's main magnetic field. It is based on data from permanent observatories and from land, airborne, marine and satellite surveys (CHAMP, Ørsted). [RD-3] IGRF11 is valid for dates from 1900.0 to 2015.0. Values for dates before 1945.0 and after 2005.0 are preliminary, otherwise the values are definitive.
Application	IBIxTMS_2F, FACxTMS_2F, FAC_TMS_2F, EEfxTMS_2F
Spatial representation	Spherical harmonics (degree 13)
Time representation	Coefficients for snap shot SH models 5 yrs apart; linear interpolation recommended, prediction by linear Secular Variation
Units	nT
Resolution	N/A
Uncertainty	Modelled field uncertainty ~20nT [RD-3]
Quality indicator	N/A
Data format	ASCII listing (SHC format); See section 4.3.1 .
Data volume	36 kB
Update rate	5 years
Latency	N/A
Data source	The content of AUX_IGR_2_ is copied to AUX_IGR_2F every time, when a new version of AUX_IGR_2_ is available.
Notes	

Product identifier	AUX_COR_2_
Definition	Spherical harmonic model of the core magnetic field
Application	MSW_SHA_2D, MSW_SHA_2F, MCO_SHA_2D, MCO_SHA_2F, MLI_SHA_2C, MMA_SHA_2D, MIO_SHA_2D

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 130 of 136

Product identifier	AUX_COR_2_
Spatial representation	Spherical harmonics up to degree 20
Time representation	Snapshot models
Units	nT
Resolution	1pT
Uncertainty	< 10 nT
Quality indicator	N/A
Output data format	ASCII listing (SHC format); See section 4.3.1 .
Data volume	~10 kB
Update rate	Depending on the choice of model (see Notes below).
Data source	GFZ
Notes	During the operational phase, each chain will use the auxiliary core field model most suitable to the chain. This model might be updated with new Swarm data. This model might have prediction capability. (During the test phase, the CHAOS-3 model is set here to specify the format of the product.)

Product identifier	AUX_COR_2F
Definition	Model for the core magnetic field
Application	IBIXTMS_2F, FACxTMS_2F, FAC_TMS_2F, EEFX_TMS_2F
Spatial representation	Spherical harmonics up to degree 20
Time representation	Snapshot models
Units	nT
Resolution	1pT
Uncertainty	< 10 nT
Quality indicator	N/A
Output data format	ASCII listing (SHC format); See section 4.3.1 .
Data volume	~10 kB
Update rate	Once per 5 years (see also section 5 in [AD-11])
Data source	See below.
Notes	The content and the format of the product file will be copied from AUX_COR_2_ . (see also section 3.15 in [AD-11])

Product identifier	AUX_LIT_2_
Definition	The applied lithospheric field model is required to describe as accurately as possible the magnetic field of the Earth's lithosphere. At present, we assume the MF7 to be a suitable model for this purpose. MF7 is a lithospheric model which is based on 3 years (2008-2010) of CHAMP scalar and vector magnetic field observations.
Application	MSW_SHA_2D, MSW_SHA_2F, MCO_SHA_2D, MCO_SHA_2F, MLI_SHA_2C, MMA_SHA_2D, MIO_SHA_2D
Spatial representation	Spherical harmonic degree 130 corresponding to ~300 km
Time representation	N/A
Units	nT
Resolution	N/A
Uncertainty	Modeled field uncertainty ≤ 1 nT [RD-9]
Quality indicator	N/A

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 131 of 136

Product identifier	AUX_LIT_2_
Data format	ASCII table (SHC, see section 4.3.1)
Data volume	< 10kB
Update rate	~1 years
Latency	N/A
Data source	IPGP based on information from http://geomag.org/models/MF7.html
Notes	Presently, the lithospheric model is described by MF7. It is anticipated to use the most accurate lithospheric model available during the <i>Swarm</i> mission.

Product identifier	AUX_LIT_2F
Definition	The applied lithospheric field model is required to describe as accurately as possible the magnetic field of the Earth's lithosphere. At present, we assume the MF7 to be a suitable model for this purpose. MF7 is a lithospheric model, which is based on 3 years (2008-2010) of CHAMP scalar and vector magnetic field observations.
Application	IBIxTMS_2F, FACxTMS_2F, FAC_TMS_2F, EEfxTMS_2F
Spatial representation	Spherical harmonic degree 130 corresponding to ~300 km
Time representation	N/A
Units	nT
Resolution	N/A
Uncertainty	Modelled field uncertainty ≤ 1 nT [RD-9]
Quality indicator	N/A
Data format	ASCII table (SHC, see section 4.3.1)
Data volume	400 kB
Update rate	~1 years
Latency	N/A
Data source	http://geomag.org/models/MF7.html
Notes	Presently, the lithospheric model is described by MF7. It is anticipated to use the most accurate lithospheric model available during the <i>Swarm</i> mission.

Product identifier	AUX_MTI_2_
Definition	Magnetic signals of major (8) tidal constituents (tides)
Application	Correction of magnetic field measurements for ocean tidal signals
Spatial representation	Spherical harmonic coefficients (real and imaginary parts) of the magnetic potential
Time representation	Time harmonics specific for each tide
Units	nT
Resolution	Up to spherical harmonic degree 45
Accuracy	Of the order of 10 %
Quality indicator	N/A
Data format	ASCII listing (others) # Arbitrary number of comment lines starting with # sign 8 T_1 T_2 T_3 T_8

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 132 of 136

Product identifier	AUX_MTI_2_
	<p>Then matrix(array) of dimension $[45*(45+2)] \times 18$ follows which columns are:</p> <p><Columns 1 - 2>: degree and order of spherical harmonic <Columns 3 - 4>: real and imaginary parts of SHC of the potential for K2 tide <Columns 5 - 6>: real and imaginary parts of SHC of the potential for S2 tide <Columns 7 - 8>: real and imaginary parts of SHC of the potential for M2 tide <Columns 9 -10>: real and imaginary parts of SHC of the potential for N2 tide <Columns 11 -12>: real and imaginary parts of SHC of the potential for K1 tide <Columns 13 -14>: real and imaginary parts of SHC of the potential for P1 tide <Columns 15 -16>: real and imaginary parts of SHC of the potential for O1 tide <Columns 17 -18>: real and imaginary parts of SHC of the potential for Q2 tide</p> <p>Here 8 is the number of tidal constituents, and T_1, T_2, \dots, T_8 are the periods of the tidal constituents (in days) in ascending order</p>
Data volume	A few Mb
Update rate	N/A
Data source	ETH
Notes	The predicted magnetic signals from 8 major tides were validated on CHAMP magnetic field residuals in producing the MF4 crustal field model (see Figure 2 of [RD-11])

5.13.2 Mantle conductivity model

Product identifier	AUX_MCM_2_
Definition	Auxiliary (preliminary) mantle conductivity model
Application	Mantle conductivity chains
Spatial representation	Conductivity distribution with respect to depth (1-D layered model of the Earth)
Time representation	N/A
Units	Kilometers (for layer radii), Siemens per meter (for conductivities)
Resolution	Variable radial resolution from 0.5 km (near surface) to > 120 km (lower mantle)
Accuracy	N/A
Quality indicator	N/A
Data format	As for MIN_1DMi2_
Data volume	A few Kb
Update rate	N/A
Data source	ETH
Notes	1-D Mantle conductivity model based on joint inversion of CHAMP, Oersted, and SAC-C satellite data [RD-10]

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 133 of 136

5.13.3 Surface conductance models

Product identifier	AUX_OCM_2_
Definition	Surface conductance map in dipolar coordinates
Application	Mantle conductivity chains
Spatial representation	2-D grid
Time representation	N/A
Units	Siemens
Resolution	1x1 degree
Accuracy	N/A
Quality indicator	N/A
Data format	As for MIN_1DMi2_ Additional information: The product is compatible with the ASCII format designed for storage of conductivity models, assuming: - only one heterogeneous layer is used ($N_layers = 1$, $3DFlag_1 = 3$) - conductance values are stored in Siemens (instead of conductivity in S/m)
Data volume	A few Mb
Update rate	N/A
Data source	ETH
Notes	Surface conductance map based on continental topography, ocean bathymetry, salinity, temperature, pressure, and thickness of sediments [RD-12]

5.13.4 Magnetospheric models

Product identifier	AUX_PMF_2F
Definition	Model of spherical harmonic coefficients of the external, magnetospheric field
Application	FACxTMS_2F, FAC_TMS_2F, IBIXTMS_2F, EEFX_TMS_2F
Spatial representation	Spherical harmonics to degree 2
Time representation	N/A
Units	nT
Resolution	N/A
Uncertainty	~ 5 nT [RD-14]
Quality indicator	N/A
Data format	AUX_PMF_2F has the following format, as defined by the originator and available at http://geomag.org/models/Pomme6/pomme-6.1.cof : Line 1: epoch header Line 2: epoch year Line 3: data range header Line 4: 2 columns (start year, end year) Line 5: IMF-By header Line 6: 2 columns of floating point Line 7: Em header Line 8: 1 column of floating point Line 9: 3 columns of floating point

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 134 of 136

Product identifier	AUX_PMF_2F
	<div>Line 10: F10.7 correlated header</div> <div>Line 11: 1 column floating point</div> <div>Line 12: 3 columns floating point</div> <div>Line 13: 5 columns floating point</div> <div>Line 14: Est/Ist header</div> <div>Line 15: 1 column floating point</div> <div>Line 16: SM-External header</div> <div>Line 17: 1 column floating point</div> <div>Line 18: 3 columns floating point</div> <div>Line 19: 5 columns floating point</div> <div>Line 20: GSM-External header</div> <div>Line 21: 1 column floating point</div> <div>Line 22: 3 columns floating point</div> <div>Line 23: 5 columns floating point</div> <div>Lines 24-25: header</div> <div>Line 26: 4 columns integer (degree static field, degree 1st derive, degree 2nd derive before epoch, degree 2nd derive after epoch)</div> <div>Lines 27-28: header</div> <div>Lines 29-180: 10 columns (degree n (integer), order m (integer), 8 floating point coefficients)</div> <div>Lines 181-8673: 4 columns (degree n integer, order m integer, 2 floating point coefficients)</div> <div>Epoch: 2005.0</div> <div>Data-range: 2000.5 2009.7</div> <div>IMF-By correlated fields in GSM (f1,1 * IMF-By * Y1,1 and f1,-1 * IMF-By * Y1,-1): 0.0732 -0.2635</div> <div>Em-correlated fields in GSM (fn,m * (Em_eff-0.5) * Yn,m): 1 1.3828 0 0</div> <div>F10.7-correlated fields in SM (fn,m * (F107a-120) * Yn,m): 2 0.0803 0 0 0 -0.0024 0.0001 0 0</div> <div>Est/Ist correlated fields in SM (f1,0 * Est * Y1,0 and f1,0 * Ist * Y1,0_intern 0.8681</div> <div>SM-External field: 2 5.4291 0 0 0 -0.9469 0.9038 0 0</div> <div>GSM-External field: 2 8.3148 0.0943 0.4332 0.1297 -0.6767 -1.2871 -0.0047 0.5217</div> <div>Internal field: Degree: static 1st-deriv 2nd-deriv-before-epoch 2nd-deriv-after-epoch 130 16 16 16 n m g_lm h_lm gd hd gdd- hdd- gdd+ hdd+ ----- 1 0 -29553.9685 0.0000 12.1671 0.0000 0.0496 0.0000 -0.2509 0.0000 ... where the coefficients written in red boldfaces are really used for the calculation of magnetospheric fields.</div>
Data volume	300 kB

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 135 of 136

Product identifier	AUX_PMF_2F
Update rate	N/A (time independent)
Latency	N/A
Data source	http://geomag.org/models/Pomme6/pomme-6.1.cof
Notes	The initially used magnetospheric field model is the POMME-6. It is anticipated to use the best quality version of the magnetospheric field model available during the <i>Swarm</i> mission.

Product identifier	AUX_PSM_2F
Definition	Coefficients to transform from Solar Magnetic (SM) to geographic coordinates for computing the external magnetic field
Application	FACxTMS_2F, FAC_TMS_2F, IBIXTMS_2F, EEFxTMS_2F
Spatial representation	Spherical harmonics to degree 3
Time representation	Temporal degree 6
Units	N/A
Resolution	N/A
Uncertainty	N/A
Quality indicator	N/A
Data format	ASCII listing defined by originator Line 1: header information Line 2: 2 columns (spatial and temporal degrees of expansion) Lines 3-4: header Lines 5-1083: 5 columns of data (degree n, SM order m, geographic order m, daily index, coefficient) Example: expansion degrees: SM spatial, daily variation 3 6 n, m_SM, m_GEO, dailyindx, coeff 1 0 0 -6 -0.00000 1 0 0 -5 0.00000 1 0 0 -4 -0.00000 1 0 0 -3 0.00000 1 0 0 -2 -0.00000 1 0 0 -1 0.00000 1 0 0 0 0.98282 ...
Data volume	< 50 kB
Latency	N/A
Update rate	N/A
Data source	http://geomag.org/models/Pomme6/sm2geo_coeff_3_6
Notes	The initially used magnetospheric field model is the POMME-6. It is anticipated to use the best quality version of the magnetospheric field model available during the <i>Swarm</i> mission.

Product identifier	AUX_PGM_2F
---------------------------	-------------------

Swarm Level 2 Processing System

Product specification for L2 Products and Auxiliary Products

Doc. no: SW-DS-GFZ-GS-0001, Rev: 2X

Page 136 of 136

Product identifier	AUX_PGM_2F
Definition	Coefficients to transform from Geocentric Solar Magnetospheric (GSM) to geographic coordinates for computing the external magnetic field
Application	FACxTMS_2F, FAC_TMS_2F, IBIXTMS_2F, EEFX_TMS_2F
Spatial representation	Spherical harmonics to degree 3
Time representation	Temporal degree 6
Units	N/A
Resolution	N/A
Uncertainty	N/A
Quality indicator	N/A
Data format	<p>ASCII listing defined by originator</p> <p>Line 1: header</p> <p>Line 2: 3 columns (spatial, daily, and annual degrees of expansion)</p> <p>Lines 3-4: header</p> <p>Lines 5-1083: 17 columns of data (degree n, GSM order m, geographic order m, daily index, 13 columns of coefficients)</p> <p>Example:</p> <p>expansion degrees: GSM spatial, daily variation, annual variation</p> <pre> 3 6 6 n m_GSM m_GEO, dailyindx, annualindx --> 1 0 0 -6 -0.00000 0.00000 -0.00000 0.00000 -0.00000 0.00000 -0.00000 0.00000 -0.00000 - 0.00000 -0.00000 -0.00000 -0.00000 1 0 0 -5 0.00000 0.00000 0.00000 0.00000 0.00000 0.00000 -0.00000 0.00000 -0.00000 - 0.00000 -0.00000 -0.00000 -0.00000 1 0 0 -4 0.00000 0.00000 0.00000 0.00000 0.00001 0.00000 0.00008 -0.00000 0.00003 0.00000 0.00000 0.00000 0.00000 1 0 0 -3 -0.00000 -0.00000 -0.00000 - 0.00002 -0.00003 0.00004 -0.00002 0.00041 0.00001 0.00004 0.00000 0.00000 0.00000 ... </pre>
Data volume	< 200 kB
Latency	N/A
Update rate	N/A
Data source	http://geomag.org/models/Pomme6/gsm2geo_coeff_3_6
Notes	The initially used magnetospheric field model is the POMME-6. It is anticipated to use the best quality version of the magnetospheric field model available during the <i>Swarm</i> mission.